ENVIRONMENTAL AND SOCIAL IMPACT ASSESSMENT (ESIA)

of

COMMERCIAL BIOGAS PLANT

in

Shivam Jaivik Khad Tatha Urja Pvt. Ltd, Janakitola, Jagarnathpur Rural Municipality

Parsa

Submitted To:

Shivam Jaivik Khad Tatha Urja Pvt. Ltd

Janakitola, Jagarnathpur, Parsa

Bioenergy Sub Component

Alternative Energy Promotion Center,

Kathmandu

Prepared and Submitted By:

Innovative and Sustainable Technology Solution Pvt. Ltd.
Sankhamul, Kathmandu

ACRONYMS AND ABBREVIATIONS

AD Anaerobic Digester

AEPC Alternative Energy Promotion Center

AVR Automatic Voltage Regulation

BOD Biological Oxygen Demand

CBG Compressed Bio Gas

COD Chemical Oxygen Demand CHP Combined Heat And Power

CSTR Continuously Stirred Tank Reactor

DAG Disadvantaged Group

DM Dry Matter

DN Diameter Nominal

DSCR Debt Service Coverage Ratio

EIA Environmental Impact Assessment

EPA Environment Protection Act

EPR Environment Protection Regulation

ESIA Environment And Social Impact Assessment

ESP Standby Power Rating

GPR Guaranteed Performance Requirement

HP Horse Power

HRT Hydraulic Retention Time

INR Indian Rupees

IRR Internal Rate Of Return

ISTS Innovative And Sustainable Technology Solutions

KVA Kilo Volt Ampere

KW Kilo Watt

KWH Kilo Watt Hour

LCC Local Control Center
MCC Motor Control Centre

NEA Nepal Electricity Authority

NOPAT Net Operating Profit After Tax

NPV Net Project Value

NRREP National Rural And Renewable Energy Programme

NTFP Non Timber Forest Product

PAT Profit After Tax
PBT Profit Before Tax

PCC Portland Cement Concrete
PH Potential of Hydrogen

PLC Programme Logistic Control

PM Particulate Matter

PRP Prime Power

PVC Polyvinyl Chloride

PVDF PolyvinylideneDifluoride RCC Reinforced Cement Concrete

SLS Solid Liquid Separate

SME Small And Medium Enterprises

SREP Scaling-up Renewable Energy Program

TPD Tons Per Day UV Ultra Violet

VAT Value Added Tax

VSS Volatile Suspended Solids

WB World Bank
ZOI Zone of Influence

कार्यकारी सारांश

यस परियोजनाको उद्देश्य ६० TPD ठूलो आकारको बायोग्यास प्लान्ट निर्माण गर्नु हो जसले दैनिक करिब टन अर्गानिक फोहोर प्रयोग गर्ने र दैनिक ११२० केजी स्वच्छ प्राकृतिक ग्यास (बायो-सीएनजी) र १३.५ मेट्रिक टन कच्चा मल उत्पादन गर्ने छ।।

प्रस्तावित बायोग्यास प्लान्ट जगरनाथपुर गाउँपालिका-३ पर्सामा निर्माण गरिने भएको छ। प्रस्तावित बायोग्यास प्लान्टले गाईको गोबर, पोल्ट्री फार्म, होटेलहरु बाट संकलन गरियक कुहिने फोहर र प्रेस मडलाई फिडस्टकको रूपमा प्रयोग गर्नेछ। यस परियोजनाबाट उपलब्ध सब्सट्रेट ६० टन/दिन बाट दैनिक २८०० घनमिटर कच्चा बायोग्यास उत्पादन गरिनेछ। उत्पादन भएको ११२० केजी प्रति दिन कम्प्रेस्ड बायोग्यासलाई बायो-सीएनजीको रूपमा बोतलमा राखेर नजिकका व्यवसायिक उद्योग तथा होटलहरूमा आपूर्ति गरिनेछ। तेसै गरि परियोजनाबाट उपउत्पादनको रूपमा कुल परिष्कृत ९.५ टन कम्पोष्ट मल उत्पादन गरिनेछ।

परियोजनाको कार्यान्वयनका लागि निर्माण गतिविधिहरूबाट निस्कने सम्भावित प्रदूषणहरू निर्माण सामग्रीहरूबाट हुने प्रदूषण, तरल पदार्थ, निर्माण सामग्री बोक्ने सवारी साधनबाट उत्सर्जन गर्ने ग्यास, धूलो र कणहरू आकलन गरियका छन्। त्यसैगरी सञ्चालनको क्रममा प्रशोधित फोहोरलाई पोस्ट-डाईजेस्टेट स्लरीको डिवॉटरिङ पछि, वर्षायाममा कच्चा फिडस्टकबाट जिमनको पानीमा हुने प्रदुषण, फोहोर संकलन र ढुवानीसँग सम्बन्धित समस्या, डाईजेसन पछिको स्लरी व्यवस्थापन, गन्ध, आवाज, ढल व्यवस्थापन र प्लान्ट सञ्चालन कर्मचारीहरुको स्वास्थ्य सम्बन्धी समस्याहरुको लागि न्यूनीकरण उपाय व्यवस्था गरिएको छ। नकारात्मक प्रभावहरूका बाबजुद पनि परियोजनाको कार्यान्वयनबाट सकारात्मक प्रभावहरू पार्ने आकलन गरियका छन। स्थानीयलाई रोजगारीको अवसर, स्थानीयको सीप विकास र स्थानीय अर्थतन्त्रमा बृद्धि निर्माण चरणका केही परिकल्पना गरिएको लाभदायक प्रभावहरू हुन्। त्यसैगरी नवीकरणीय उर्जाको प्रविद्धन, स्थानीयलाई रोजगारीको अवसर, स्थानीयको सीप विकास उप-आयोजनाको सञ्चालन चरणमा हुने केही लाभकारी प्रभावहरू हुन्।

यद्यपि, यस ESIA प्रतिवेदनमा प्रस्तावित न्यूनीकरण उपायहरूलाई कडाईका साथ पालना गरेर माथिको अनुमानित सम्भावित नकारात्मक प्रभावहरूलाई कम गर्न सिकन्छ। निर्माण तथा सञ्चालन चरणमा प्रयोग हुने सबै सवारी साधन र मेसिनरीहरू वन तथा वातावरण मन्त्रालयले तोकेको उत्सर्जन मापदण्ड अनुरूप हुनुपर्छ, वर्षायाममा चुवावटबाट बच्न स्टकपाइलहरू छोपिएको हुनुपर्छ, एग्रीगेटहरू मिसाउने र धुने कार्य तोकिएको क्षेत्रमा गर्नुपर्छ, स्लरी र डिकेन्टेड फोहोरको सीधा निकासीबाट रोक्नु पर्ने । यसका साथै निर्माण र सञ्चालन दुवै चरणमा सबै कामदारले हेल्मेट, सेफ्टी ज्याकेट, पञ्जा, जुत्ता जस्ता सुरक्षात्मक उपकरण लगाउनु पर्ने । दुर्घटना र रोगबाट बच्नका लागि कर्मचारीहरूलाई उचित तालिम प्रदान गर्नु पर्ने । तसर्थ, वातावरण र सामाजिक दृष्टिकोणबाट, यस प्रतिवेदनमा प्रस्तावित न्यूनीकरणका उपायहरू सही तरिकाले पालना गरिएमा, यस परियोजनाले वातावरण र सामाजिक नकारात्मक प्रभाव पार्ने देखिदैन ।

EXECUTIVE SUMMARY

The Environmental and Social Impact Assessment (ESIA) for Commercial biogas plant of Shivam Jaivik Khad Tatha Urja Pvt. Ltd is being carried out at the land of the proponent which lies on ward no. 3 of Jagarnathpur Rural Municipality, Parsa. The proposed biogas plant will use 60 tons of organic waste from commercial sectors such as poultry farm, cattle farms, sugar industry, hotels, etc. for co-feeding. The proposed biogas plant is expected to produce 2800 m³/Day of biogas each day and subsequently 1120 kg/Day of refined bio CNG which will be filled in cylinders and supplied to hotels, and industries. Also 9.5 tons of organic manure will be produced each day which will be processed and packaged and sold to the market

The project is located in Jagarnathpur Rural Municipality, ward no. 3 in the land of the proponent. The total area of the project site is 14,800 .00 m² (2 Bigha and 4 Kathha). Prior to the commencement of the project, an environmental and social impact assessment (ESIA) is conducted to look at the physical, biological, social, cultural, and economic aspects. Various impacts were discovered during the study's construction and operation phase. The defined impacts can be reduced by implementing the mitigation strategies outlined in this study. The subproject would have far less negative environmental consequences if additional mitigation steps specified in this ESA are implemented. Compliance steps, as well as an environmental monitoring plan, institutional arrangements for grievance management, and occupational health and safety measures, are all listed in the study.

The potential pollutants resulting from implementation of the proposed project during construction phase are construction spills, mucks, washout liquid wastes, gaseous emission, dust, suspended particle whereas potential impacts that are found during operation phase are processed wastewater after dewatering of post-digestate slurry, leaching of raw feedstock into groundwater during rainy season, post-digestate slurry management, odor, noise, drainage management and matter concerning with health of operational staffs. Despite the project's negative consequences, there are some benefits, including municipal waste management, local job opportunities, local skill growth, fertilizer production, and the promotion of renewable energy, to name a few.

As a result, biogas and slurry for agricultural use are expected to be generated as a result of the project. This project will help with urban waste management by reducing the danger of leaching, flies, and vector-borne disease, as well as waste flooding during the rainy season and foul odor after decomposition. The biogas produced will be used as an alternative to LPGs and fuelwood and will be compressed in cylinders and sold and distributed to hotels and industries, while the fertilizer produced will be sold at subsidized rates to the general public. As a result, both the proponent and the local communities tend to benefit from the plan.

TABLE OF CONTENTS

ACRONYMS AND ABBREVIATIONS	i
कार्यकारी सारांश	iii
EXECUTIVE SUMMARY	i
TABLE OF CONTENTS	ii
LIST OF TABLE	v
LIST OF FIGURES	vi
1. INTRODUCTION	1
1.1 Project Description and Location	1
1.2 Project Location and Accessibility	1
1.3 Salient Features	4
1.4 The Proponent	5
1.5 The Consultant	5
1.6 Objective of ESIA	6
1.7 Study Methodology	6
1.7.1 Desk Review	6
1.7.2 Field Based Study	7
1.7.3 Impact Assessment	8
1.7.4 Project Impact Area Delineation	8
2. PLANT DESIGN AND TECHNOLOGY	9
2.1 Description of the Technology	9
2.2 Process Design	10
2.3 Large Biogas Project Requirements	12
2.3.1 Construction materials	12
2.3.2 Water Requirement	12
2.3.3 Land Requirement	12
2.3.4 Work Force Requirement	13
2.3.5 Energy Requirement	13
2.4 Potential Pollutants/Emission Resulting from Implementation of the	Proposal13
3. DESCRIPTION OF EXISTING ENVIRONMENTAL CONDITION	14
3.1 Physical and Cultural Environment	14
3.1.1 Physiography and Topography	14
3.2 Biological Environment	17

	3.2.1 Vegetation and Forest	. 17
	3.2.2 Wildlife	. 17
	3.2.3 Birds	. 18
	3.2.4 Herpeto Fauna	. 18
	3.2.5 Fish Species	. 18
3.	3 Socio-economic Environment	. 18
	3.3.1 Project District and Rural Municipality	. 18
	3.3.2 Demography	. 18
	3.3.3 Caste/Ethnicity	. 20
	3.3.4 Religion	. 21
	3.3.5 Mother Tongue	. 22
	3.3.6 Literacy and Education	. 23
	3.3.7 Status of population with disability	. 24
	3.3.8 Source of Drinking Water	. 25
	3.3.9 Energy use for cooking	. 26
	3.3.10 Energy use for Lightening	. 27
	4. Review of Plans/Polices/Legislations and Guidelines	. 29
5.	IMPACT ASSESSMENT	. 31
	5.1 Beneficial Impacts	. 31
	5.1.1 Construction Phase	. 31
	5.1.2 Operation Phase	. 31
	5.2 Adverse Issues	. 32
	5.2.1 Construction Phase	. 32
	5.2.2 Operation Phase	. 36
6.	ENVIRONMENTAL AND SOCIAL IMPACT MITIGATION	. 48
	6.1 Mitigation Measures	. 48
	STAKEHOLDER CONSULTATION, COMMUNITY PARTICIPATION AND	(2
ט	ISCLOSURE	
0	7.1 Public Consultation	
ŏ.	ALTERNATIVE ANALYSIS	
	8.1 No project option	
	8.2 Design Alternative/Technology	
	X 3 Altornativo Rocourco	61

8.4 Alternative Project Site	64
8.5 Alternative Time-schedule	64
9. ENVIRONMENTAL MONITORING	65
9.1 Project Management Responsibility	65
9.2 Environmental Standards	65
9.3 Environmental Monitoring Plan	65
10. INSTITUTIONAL ARRANGEMENT AND GRIEVANCE REDRESS MECHANISM	76
10.1 Project Environmental Management Plan Structure and Stakeholders Responsibility	76
10.2 Conflict /Grievance Redress Mechanism	78
10.3 Capacity Development and Enhancement Measures	79
11. COMPANY'S ENVIRONMENTAL HEALTH AND SAFETY PLAN	81
11.1 Health and Safety Plan	81
11.2 Emergency Preparedness Plan	82
11.3 Gender Action Plan	83
11.4 Substrate Handling and Slurry Management Plan	83
11.5 Labor Management Plan	83
12. Conclusion	84
13. ANNEXES	85
Annex A-1: Company Registration Certificate	85
Annex A-2: Environmental and Social Screening Checklist	87
Annex A-3: Meeting Minute of Public Consultation	97
Annex A-4: Description of Technology	102
Annex A-5 : Land Document	110
Annex A-6: Reviews of Plans/ Policies/Legislations and Guidelines	111
Annex A-7: Environmental Standards	122
Annex A-8: Grievance Redress Format	125
Annex A-9: Plant Layout and Drawings	127
Annex A-10: Emergency Preparedness Plan	128
Annex-A11: Occupational Health and Safety Plan	133
Annex A -12: Photos	138

LIST OF TABLE

Table1 Parameters considered for plant design	. 11
Table 2 Design Criteria	. 12
Table 3 Land Required for main components	. 13
Table4 Potential pollutants/emissions resulting from implementation of the project	t 13
Table5 Climatology data of Parsa district	
Table 6 Land use pattern of the rural municipality	. 16
Table7 Population of rural municipality	. 19
Table8 Population density according to ward	. 19
Table9 Population distribution according to age group	. 19
Table10 Population data of parsa district	. 20
Table11 Caste distribution in the rural muicipality	. 20
Table12Caste distribution of Parsa district	. 21
Table13 Population distribution according to religion in rural municipality	. 21
Table14 Population by religion	. 22
Table15 Population distribution according to mother tongue	. 22
Table16 Language spoken in Parsa district	. 23
Table17 Literacy rate of the rural municipality	. 23
Table18 Literacy of Parsa district	. 23
Table19 Disabilities population in the rural municipality	. 24
Table20 Disability population on the district	. 24
Table21 Drinking water source in different households	. 25
Table22 Households by drinking water source	. 26
Table23 Household utilizing different source of energy for cooking	. 26
Table24 Households by main type of cooking fuel	. 27
Table25 Household using different source of energy for lightening	. 27
Table26 Households by main type of lighting fuel	. 27
Table 27 Impact assessment	. 40
TABLE 28 Impact weightage criteria, national eia guidelines (1993)	. 47
Table 29 Mitigating measures	. 49
Table 30 Baseline monitoring, construction and operation phase	. 66
Table31 Compliance monitoring, construction and operation phase	. 66
Table32 Impact monitoring, construction and operation phase	. 73
Table 33Summary of Environmental Monitoring Cost	. 74
Table34 Environmental and social screening checklist	. 87
Table35Standards for effluents discharged into inland waters	122
Table36Drinking water quality standards	122
Table37National standard for noise quality	123
Table 38Permissible emission standards for biogas generator (adopted from diesel	
generator standard)	124
Table39Grievance redress format	126

LIST OF FIGURES

Figure 1 GIS map showing political map of project site	2
Figure 2 GIS map of Jagarnath rural municipality	
Figure 3 Google map of project site	3
Figure 4 Tropographical map of location	3
Figure 5 Google map showing direct and indirect impact zones	9
Figure 6 Schematic Diagram of Biogas Plant	10
Figure 7 Project flow diagram	11
Figure 8 PEM Framework	77
Figure 9 GRM framework	78
Figure 10 Company registration of proponent	85
Figure 11 PAN application	86
Figure 12 Minute	100
Figure 13 Public consolidation	101
Figure 14 Layout of land	111
Figure 15 Plant layout	127
Figure 17 Field location of project	144
Figure 18 Poultry farm for biogas production	144
Figure 19 Cattle farm for biogas production	145

1. INTRODUCTION

1.1 Project Description and Location

Shivam Jaivik Khad tatha Urja Pvt. Ltd. is located at Janakitola of Parsa district, Madesh Province who is the proponent for this project. The proponent aims to build a biogas plant at ward no. 3 of Jagarnath Rural Municipality at its land with total area of approx. 14800.00m² (2 Bigha and 4 Kathha). The project site is located at 27°8'51.81" N and 84°42' 7.74" E. the proposed biogas plant will use the wastes coming from cattle farm, poultry, sugar industry, hotels, etc. to produce the gas and sell it to nearest hotels and industries. The objective of the project is to prepare a holistic, integrated, sustainable, environment friendly and executable Commercial Biogas Plants which is in line with objective of the Alternative Energy Promotion Center (AEPC), under Nepal- Private Sector Led Mini Grid Energy Access Project (MGEAP).

The Detail Project Report has proposed for the installation of 5000 m³ biogas digester. The digester of proposed biogas plant is based on CSTR, (continuously stirred tank reactor) mesophilic fitted with Otto power cycle and double membrane gas holder. With 65 tons of waste, it is estimated that 2800 m³ of biogas will be produced each day and subsequently 1120 kg/Day of refined bio CNG will be produced which will be filled in cylinders and supplied to hotels, and industries. Also 9.5 TPD of organic manure will be produced each day which will be processed and packaged and sold to the market

The DPR study revealed that the production of biogas and fertilizer from the project is feasible on all terms, the availability of biomass substrates, or the financial indicators like NPV, IRR and Payback Period. The main sources of biomass substrates for the biogas project are cow dung, poultry litter, food waste, and agro waste (paddy/maize). For the current biogas production capacity of the project, the resource availability is readily available. Moreover, the perception of the market towards the products is found to be extremely positive owing to its local manufacturing base. A standby generator in case of failure of the original generator has also been proposed to ensure continuous power generation.

The project also falls under Category "B" as the rapid assessment checklist shows that the project is unlikely to cause significant adverse impact. This Environmental and Social Impact Assessment (ESIA) is prepared to address possible environmental and social impacts from construction and operation of digester and its components

1.2 Project Location and Accessibility

The project will be built in the land of the proponent, located at ward no. 3 of Jagarnathpur Rural municipality. It lies in the Terai belt having flat lands. Geographically, it lies at 27° 8′ 55.71″N and 84°42′ 5.32″E . An earthen road lies 8m from the project site




Figure 1 GIS map showing political map of project site




Figure 2 GIS map of Jagarnath rural municipality



Topographic Map of the Location

Project site

Topographic Map of the Location

Topographic Map of the Location

Project site

Topographic Map of the Location

Topographic Map of the Location

Topographic Map of the Location

Project site

Topographic Map of the Location

Topogra

Figure 4 Topographical map of location

1.3 Salient Features

Name of project	: Commercial Biogas Plant Shivam Jaivik Khad Tatha Urja Pvt. Ltd
Location	: Jaganathpur Rural Municipality-3, Janakitola,
	Parsa, Nepal
Project Site	: Shivam Jaivik Khad Tatha Urja Pvt. Ltd
Province	: Madesh
Estimated Waste:	
Design for the Waste	: 60.00 Tons/ day
Proposed Technology	: Continuous Stirred-Tank Reactor (CSTR)
Plant Capacity	: 60 Tons/Day (Mix Substrate)
Expected Quantity Of Biogas Gas	: 2800 m3/Day
Estimated Refined Bio CNG	:1120 kg/Day
Organic Fertilizer	:13.5 MT/day
Refined Organic Fertilizer	:9.5 MT/day
Water Required	:60000 Liter/day(15000 Liter/Day Recycled)
Size of Digester	: 5000 m ³
Geographical Coordinates:	
Latitude/Longitude	: 27° 8' 55.71"N 84°42' 5.32"E
Altitude	:100 m
Land Area [Approx. Project Site]	: 14,800 m ²
Estimated Financial & Financial Ir	ndicators: NRs.
Project Cost with Vat	211,244,737.17
Project Cost	186,942,245.28
Equity	41,127,294.00
Loan	71,038,053.00
Subsidy	74,776,898.00
Return On Investment	14%(5 th Year)

Net Present Value	154,397,621.05
BCR	1.73
IRR	18.88%
Payback Period(Year)	6.55

1.4 The Proponent

The Proponent of this project is Shivam Jaivik Khad tatha Urja Pvt. Ltd. **Shivam Jaivik Khad tatha Urja Pvt. Ltd**is a private limited company registered in office of the company registrar Nepal. The company was established in Mangsir 17, 2077.

Please see Company Registration Certificates and PAN Application submission confirmation in the Appendices A.

Name and address of the proponent is:

Name of organization	Shivam Jaivik Khad Tatha Urja Pvt. Ltd
Activity	Biogas Plant Construction
Address	Jaganathpur Rural Municipality-3, Janakitola, Parsa, Nepal
Contact name	Ashok Kumar Yadav, Dilip Sharma
Contact number	9855036664,9855023153
Email address	shivamjktu@gmail.com

1.5 The Consultant

Innovative and Sustainable Technology Solutions Pvt. Ltd (ISTS) is the consultant for Detail Project Report (DPR) for Commercial Project through Anaerobic Digestion (Biogas) Technology at **Shivam Jaivik Khad Tatha Urja Pvt. Ltd**.

ISTS is registered under Company Registrar on 2070 initially known as B and B Multipurpose Company Private Limited. ISTS has been working on Detail Feasibility Study, Design, Installation and monitoring of different Renewable Energy Technologies like Micro Hydro, Biogas Plants, Solar Plants and Biomass technologies. ISTS has successfully conducted Detail Feasibility Study of number of commercial and institutional biogas projects. ISTS has done DFS of Commercial Biogas Plants, Micro Hydro and Solar Plants. ISTS has also competed IEE of different biogas projects Name and address of the consultant is:

Innovative and Sustainable Technology Solutions Pvt. Ltd (ISTS)

Main Office Center Office

Dipayal Silgadhi Muncipality-7 Sankhamul, Kathmandu

Phone: 094-440462 Phone: 01-4782766

E-Mail: istsnepal@gmail.com

The details of company registration are attached in Annex A-1of this report.

1.6 Objective of ESIA

The objectives of ESIA are as follows:

- To identify the main environmental and social issues/impacts related to construction and operation of biogas plant to its existing bio-methanation plant.
- To describe and predict the extent of potential impacts on physical, biological and socio-economic environment (based on both field inspections and desk research).
- To identify pragmatic mitigation measures to avoid, minimize or compensate the predicted impacts.
- To define monitoring and management systems which are applicable and suitable in the project area.
- To define the institutional framework required for the execution of monitoring and management programs.
- To integrate environmental and social considerations into project planning, design and costing. Allow proponent, designers, implementing agencies and funding agencies to address environmental and social issues in a timely and cost-effective manner during the pre-feasibility stage.
- Organize meaningful consultations with the concerned stakeholders including affected people/parties if any, along with the local levels and involve them, in the all phases of the project (planning, designing and implementing stage).

1.7 Study Methodology

The ESIA was undertaken considering Environment Management Framework (EMF) and Social Management Framework (SMF) of MGEAP, EPA/EPR and National EIA Guidelines 1993.

1.7.1 Desk Review

Relevant information for the study was collected through extensive review of literature and all pertinent relevant documents like Plans, Policies, legislation, guidelines, environmental acts, international policies and conventions, environmental standards and district profiles and municipality profiles were reviewed, and detail attached in **Annex A-6**. The following steps were followed during the desk review:

a) Collection and review of secondary information from various sources

Secondary information was collected through published and unpublished reports and interpretation of maps and photographs. During the ESIA report preparation, study

team met, discussed and interacted with concerned staff of the Government of Nepal, Jagarnathpur Rural Municipality, in the province headquarter, community-based organization member and knowledgeable key persons of surrounding areas.

b) Delineation of the geographical boundary of the influence area on the topographical map

During the ESIA report preparation, the influence area has been drawn on the topographical map and Google Earth Map according to Direct Impact Zone (100 m) and Indirect Impact Zone (500 m) from the proposed project site.

c) Preparation of project specific checklist

A checklist was prepared to collect physical, biological, socio-economic and cultural environment related information in the field. This checklist was based on National IEE Guideline-1993 and attached in Annex A-2.

1.7.2 Field Based Study

Field survey comprised of project site visit, which took place from 6th to 9th March 2024 for consultation with community, site inspection and observation a team comprising Environmentalist, Engineer and Sociologist. During the field visit, site specific data was collected by visiting the sites where the large biogas will be installed. The following tools were used for the collection of primary data.

- To conduct consultation with the local people, informal interaction and discussion was carried out on 7th March, 2024 at Ward office of Ward no 3 of Jagarnathpur Rural Municipality with concerned government officials, which includes Ward Chairperson, Ward members, Environmental Officers, general public and other knowledgeable persons. It was done to collect biological, socioeconomic and cultural environment related information.
- Topographical map It was used to show environmental features on the map during project site survey.
- Walkover survey- The survey was carried out at installation site to study the environmental impacts

Physical Environment and Cultural Environment: Checklist and matrix were used to collect site-specific information about the physical environment of the project area. The checklist and questionnaire are attached in Annex A-2. Information collected during the field visit includes land use pattern, land stability, topography, geology, drainage characteristics, climate, rainfall and available infrastructures near changed project structures. Topographical map, site observation and site-specific photography have been presented. Physical infrastructures that are likely to be affected due to large biogas installation have been identified and appropriate mitigation measures have been proposed.

Biological Environment: The proposed construction activity will be confined within the existing project boundary and found that the project construction and operation activity won't require cutting of trees. Documentation has been done as baseline information on local vegetation, wildlife in the project site including mammals, birds, and fishes known in the study area. Documentation of vegetation status, endangered plants, and NTFPs have been recorded and likely impact upon has been identified and presented in the ESIA report. Site visit, interaction with community and photograph etc. has been taken for the record.

Socio-Economic Environment and Natural Environment

Information on socio-economic and cultural features of the project area including population, ethnic composition, literacy, language, health service etc. has been collected. Similarly, cultural and religious sites, sources of energy, infrastructures, market centre etc. has been collected through visit, site survey. The general socio-economical information of the Jagarnath Rural Municipality was extracted from village profile of Jagarnathpur rural municipality 2075. The socio-economic information of the direct impact zone was collected through a public consultation in the presence of Ward Chairperson. Meeting minutes are attached in **Annex A-3**.

1.7.3 Impact Assessment

After the complete documentation of baseline environmental and social data of the project area, each of the environmental and social parameters were examined against the project activities in the different stages of project development using various methods and tools. Then the impacts were categorized as direct and indirect. Each of the direct and indirect impacts was further evaluated in terms of their extent as site specific, local or regional. Each of these was further analyzed in terms of duration as short-term, medium-term and long-term. The magnitude of each of the impact is then evaluated based on the National Environmental Assessment Guideline (1993).

1.7.4 Project Impact Area Delineation

The project affected areas are classified into direct and indirect impact area based on scale, nature and location of the sub-project.

Direct Impact Area (DIA): The direct impact area includes the area of 100m radius from the project site, where direct activity during construction and operation takes place. It includes areas where the construction work will be done. In this area environmental components might be affected by the project activities. The project area is proposed at Janakitola, ward no. 3 of Jagarnathpur Rural Municipality. As per the assessment, there are not any households within the 100m radius in DI area. This area experiences site specific impacts. The environmental impacts of this area could not be avoided but its effect could be minimized or compensated by taking relevant measures.

Indirect Impact Area (IIA): The indirect impact area includes the area of 500 m radius from the project site, where indirect activity during construction and operation takes place. Indirect impact area includes all the areas that will have indirect impacts by construction and operation activities which can be mitigated or minimized and mostly the activities of construction workers. This area includes 79 households and covers Gadhaiya village. The physical, socio-economic, cultural and biological environment of this area will experience minimal impacts.



Figure 5 Google map showing direct and indirect impact zones

Zone of Influence (ZOI): The **Zone of Influence** extends beyond both the direct and indirect impact areas, considering broader and more diffuse impacts that can extend further due to various environmental, social, and economic factors. For the project, the ZOI includes Jirabhawani Rural Municipality, Paterasugauli Rural Municipality, Dhobini Rural Municipality, and Pokhariya Municipality, where raw materials for the biogas plant will be collected. Additionally, Birgunj Municipality is part of the ZOI, as the gas and fertilizer produced will be sold there. The roadways used for these activities will include the Gandak Nahar Sadak (Janki Tola to Thori) and the Birgunj Dry Port to Thori Hulaki Sadak.

2. PLANT DESIGN AND TECHNOLOGY

2.1 Description of the Technology

The proposed technology is Continuous Stirred-Tank Reactor. Anaerobic co-digestion of many different substrates has achieved the most success when utilizing a Continuous Stirred-Tank Reactor (CSTR). This is the most popular, and proven technology worldwide. CSTR systems are very large, heated insulated tanks,

constructed of metal or concrete. The digester of proposed biogas plant is based on CSTR, (continuously stirred tank reactor) mesophilic fitted with double membrane gas holder. The CSTR is a proven digester design consisting of an above-ground tank with a Flexible Double membrane roof. Biogas is collected at the top of the tank and is pumped to a separate gas holder. Digestate is removed from the base of the digester tank. The major components of the plants are:

- Mixing Tank
- Digester Tank with mixing and heating system
- Fertilizer Tank
- Biogas Up gradation Unit
- Electric Control Panels
- Solid Liquid Separate

From the available feedstock, the sizing of biogas plant has been done. With reference to CSTR Technology, the recommended size is found to be 2800 m³ daily gas productions. The digester technology and final size will be defined during DFS Stage. Anaerobic co-digestion of many different substrates has achieved the most success when utilizing a Continuous Stirred-Tank Reactor (CSTR). This is the most popular, and proven technology worldwide. It is our recommendation that the most effective and flexible technology for the digestion project is a CSTR system. The major components will be the mixing tank, digester tank, fertilizer tank, Organic and Inorganic Waste Separator, Solid Liquid Separator, Purification unit, Biogas Pipeline and control units, Electric Control Panel.

The details of technology are attached in Annex A-4.




Figure 6 Schematic Diagram of Biogas Plant

2.2 Process Design

The figure below shows the process flow diagram of the plant.




Figure 7 Project flow diagram

The parameters considered for the design is given in below table

Design and sizing criteria for all process units are listed in table below:

Table 1 Parameters considered for plant design

Digester				
feed		Total digester Volume	Biogas plant volume	
(m3/day)	HRT (days)	(m3)	(m3)	
140	30	4200	5000	
Mass loading to digester (wet)		140000.0	kg solids/day	
% DS		21	no water added	
Digester feed %DS		10.0%		
Dilution water required		60000	l/day	
OLR		2.64	kg VS/(m3 * day)	
C:N ratio		18.3		
VS destruction		20.0		
Digester Slurry mass dry		60%	kg solids/day	
Digester Slurry Mass wet		7362.0	kg/day	

Digester Slurry DS%	140000	%DS
VS load (kg/day)	VS dest (kg/day)	
11096.0	6657.0	
Compost DS%	70.0%	%DS
Compost production	17500	kg/day

Table 2 Design Criteria

Waste	Fed Waste
Poultry Waste (Kg/Day)	8,000.00
Cow Dung (Kg/Day)	46,000.00
Press Mud (Kg/Day)	5,000.00
Organic Waste (Kg/Day)	1,000.00
	60,000.00

2.3 Large Biogas Project Requirements

2.3.1 Construction materials

The various construction materials are needed during construction period. The construction materials like concrete, cement, sand etc. will be required for construction of civil structures like sumps; foundation of digester and decantation tank etc. The main digester will be constructed with pre-fabricated mild steel (MS) structure. These materials will be acquired from local market as well as from abroad.

2.3.2 Water Requirement

The projected site owns the water sources, so there will be no issues and no conflicts. The nearby river in this area includes Gangol Nadi which is 700m east prom the project site and Uriya Nadi which is about 1.65 km west from the project site. There is a boring in the site, from water can be extracted sustainably. Therefore, water requirement will be met through the water source present within the premises of the site.

2.3.3 Land Requirement

The total land required for the development of various components of the subproject is 5,255 m², as outlined in Table 3. However, the developer has arranged approximately 14,800 m² of land to accommodate ancillary facilities. The proposed site for the subproject is situated on private land owned by Ashok Yadav, a board member of Shivam Jaibik Khad Tatha Urja Pvt. Ltd. The company has leased the land from Ashok Yadav at a rate of Rs. 2,500 per katha per year (refer to Annex 12). The site is located in Janakitola, Ward No. 3, Jagarnathpur Rural Municipality, Parsa District. The land requirement for the main components are:-

Table 3 Land required for main components

S.N	Components	Area	Remark
1	Digester	1200 m ²	
2	Panel and Control room	105 m ²	
3	PSA shed (Compressor, purification unit, filling area,	500 m ²	
	empty & fill cylinder storage area)		
4	Press mud and Raw material mixing plateform	800 m ²	
5	Fertilizer packing, godown and fertilizer drying yard	1200 m ²	
6	Dewatering Plateform	550 m ²	
7	Slurry Lagoon	500 m ²	
8	Slurry and Feeding Pit	400 m ²	
Total		5,255 m ²	

The layout of the land of the plant site are presented in Annex A-5.

2.3.4 Work Force Requirement

During the construction phase of the project, it is estimated that about 25-30 person of unskilled and skilled human resource will be required. 6 months of construction time is estimated for the construction activities for installation of biogas plant. The project has the strategy to give priority to local people for unskilled labor requirement. The sub-project will ensure that no child labor and forced labor are used in the construction site.

The sub-project requires about 21 skilled and semiskilled workers during operation phase. While employing workers, the preference will be given to local according to their qualification, skill and interest. Except for the skilled human resource, all the semiskilled and unskilled workers will be employed from the surrounding vicinity of the sub-project area.

2.3.5 Energy Requirement

Fossil fuel energy (Gasoline) and electrical energy will be used during the construction phase. National grid electricity will be used for meeting electrical demand. Diesel will be used for vehicular transportation of construction materials and operating generators as and when required. The labors at the camp will use own bio-methane energy for cooking and heating purpose.

2.4 Potential Pollutants/Emission Resulting from Implementation of the Proposal

Different types of wastes and pollutants are assumed to be produced during the construction and operation phase of the proposed project. Different nature of wastes produced during the construction phase and operation phase are discussed in Table 2-2.

Table 4 Potential pollutants/emissions resulting from implementation of the project

Pollutant	Pollutants/Emissions	Sources
Category		
Construction Phas	se	

C 11 1 TAT 4	3.6 1.70 11	T
Solid Waste	Muck/Spoil	Excavation and civil
		construction work for
		foundation of digester
	Food wastes, polythene,	Construction Workforce
	papers etc.	
Liquid and	Wash out Liquid Wastes	Aggregate Washing, Wash outs
Semi-Liquid		from concrete
Wastes	spent grease, lubricants,	Vehicles and Generators
	spills and leaked petroleum	
Gaseous	Dust, CO ₂ , CO, NOx, SO ₂	Various excavation processes,
Emission	and suspended particulate	crushing and mixing activities,
	matter	vehicles and diesel generator
Operation Phase		
Solid Waste	Polythene, packaging bags	Packaging of manure
	(additional to existing waste	
	generation)	
Liquid and	Process wastewater after	Biogas production and post-
Semi-Liquid	dewatering of post digestive	digestive decantation, washing
Wastes	slurry (additional to existing	and cleaning
	waste generation)	_
Gaseous	CO/CO ₂ , NOx and SO ₂ and	Combustion of fossil fuels
Emission	suspended particulate	(Operation of Diesel Generator)
	matter (less gaseous	– less hours will be required
	emission than existing	after commencement of project
	scenario due to replacement	,
	of Diesel Generator by	
	biogas electricity)	
Noise Pollution	Noise level from biogas	Transportation vehicles,
	generator and vehicle	components of plant
	movements, pumps	
Odor Pollution	Foul odor	Pre-storage of biodegradable
		raw materials, storage in
		effluent lagoon
	I .	U

3. DESCRIPTION OF EXISTING ENVIRONMENTAL CONDITION

This section describes the existing environmental condition of the project area based on the site-specific information gathered through primary and secondary sources of information. The existing environment related to physical, biological, socio economic and cultural environment are described below.

3.1 Physical and Cultural Environment

3.1.1 Physiography and Topography

The proposed project site lies in Jagarnathpur rural municipality of Parsa district. It lies in the western part of the Parsa district. The proposed location for plant is situated

at Janakitola, ward no. 3 of Jagarnathpur rural municipality of parsa district, having coordinates 27° 8' 55.71"N $84^{\circ}42'$ 5.32"E.

The rural municipality is extended from 27°5′40″N to 27°11′31″N and from 84°40′19″E to 84°46′56″E with a total area of 45.29 sq. km at an altitude ranging from 85 to 925m. The rural municipality is bordered by six local level, namely Sakhuwa Prasauni in the east, Paterwa Sugauli rural municipality in the north-east, India in the west, Pokhariya municipality, Kalikamai rural municipality and Dhobini rural municipality in the south and Jirabhawani rural municipality in the north. The total area of the rural municipality is 45.29 sq. km. which is 3.34 percentage of total area of Parsa district. The rural municipality was formed in 2073 B.S. by combing seven VDCs. The rural municipality consists of six administrative wards. The Jaganathpur rural municipality is considered as flat terai region. Temperate and tropical type of climate prevail in this region.

Geology and Soil Type

Geographically the subproject is situated at latitude 27° 8′ 55.71″N and longitude 84°42′ 5.32″E and 85m above sea level. The project location is 27.3 km far from the district's headquater Birgunj and has good transportation links. The project is located in the Terai plain (northward extension of Indo-Gangetic plain). The proposed location is flat land of area of 14,800 m² without any disturbance for direct solar radiation. Hence, the location is viable for big biogas plant construction. The project district, Parsa has predominantly alluvial and clay fertile soil, which is loose, and unconsolidated soil type.

Climate

The proposed plant site lies in the Parsa district. Parsa is 99m above sea level. The climate here is mild, and generally warm and temperate. The summers here have a good deal of rainfall, while the winters have very little. This climate is considered to be (Cwa) according to the Köppen-Geiger climate classification. The Koppen Geiger climate¹ classification is the empirical classification based on the vegetation. This classification aims to define the climatic boundaries as per the vegetation zones (biomes) which was developed by climatologist Wladimir Koppen. Climatic type Cwa in Koppen Geiger climate classification refers to the monsoon influence results in a modified humid subtropical climate (Cwa) that has a clearly defined dry winter. The temperature here averages 23.7 °C | 74.7 °F. The annual rainfall is 1890 mm | 55.2 inch. Precipitation is the lowest in November, with an average of 5 mm | 0.2 inch. Most of the precipitation here falls in July, averaging 401 mm | 15.8 inch. At an average temperature of 29.4 °C | 84.9 °F, May is the hottest month of the year. January is the coldest month, with temperatures averaging 14.7 °C | 58.5 °F.Between the driest and wettest months, the difference in precipitation is 396 mm | 16 inch. Throughout the year, temperatures vary by 14.7 °C | 58.4 °F.

_

¹ https://www.britannica.com/science/Koppen-climate-classification (Köppen climate classification)

Table5 Climatology data of Parsa district

))			aibtifet			
	January	February	March	April	May	June	July	August	September	October	November	December
Avg.	14.7 °C	17.8 °C	22.8	27.9	29.4	29.3	27.5	27.4 °C	26.6 °C	24.2 °C	20.5 °C	16.5 °C
Temperature °C	(58.5) °F	(64.1) °F	°C	°C	°C	°C	°C	(81.3)	(79.9) °F	(75.5) °F	(68.9) °F	(61.7) °F
(°F)			(73.1)	(82.1)	(84.9)	(84.8)	(81.6)	°F				
			°F	°F	°F	°F	°F					
Min.	9.2 °C	11.6 °C	15.3	20.2	23.5	25.3	25.2	25.1 °C	23.9 °C	19.8 °C	15.2 °C	11.2 °C
Temperature °C	(48.5) °F	(52.9) °F	°C	°C	°C	°C	°C	(77.1)	(75) °F	(67.6) °F	(59.3) °F	(52.2) °F
(°F)			(59.6)	(68.4)	(74.3)	(77.6)	(77.4)	°F				
			°F	°F	°F	°F	°F					
Max.	20.6 °C	24.2 °C	30 °C	35 °C	35 °C	33.4	30.3	30.3 °C	29.9 °C	28.8 °C	26.1 °C	22.2 °C
Temperature °C	(69.1) °F	(75.5) °F	(86) °F	(94.9)	(95)	°C	°C	(86.6)	(85.8) °F	(83.9) °F	(79) °F	(71.9) °F
(°F)				°F	°F	(92.2)	(86.6)	°F				
						°F	°F					
Precipitation /	18	24	13	15	57	254	401	363	198	43	5	11
Rainfall mm (in)	(0.7)	(0.9)	(0.5)	(0.6)	(2.2)	(10)	(15.8)	(14.3)	(7.8)	(1.7)	(0.2)	(0.4)

Source: en.climate-data.org

Drainage and Hydrology

The rural municipality covers 1.77 percentage of the area with lakes or ponds. Similarly, the rural municipality is also composed of wetlands. Source of water present in the locality is boring water. Sustainable quantity of water is available. The boring water source is available within the premises of the proposed plant site. There is no any forest area within periphery of 3 km from sub-project.

In most of the dry season, it is difficult to see water in the stream. People use deep boring, tube well and hand pump to extract water from underground.

Land Use

The rural municipality lies in the Parsa district. It has total area of 45.29 sq.km The rural municipality is known for agriculture due to its fertile lands. The land use pattern of the rural municipality is dominated by agricultural land which covers 94.33% of the total area, followed by riverbank (3.33%), lakes or ponds (1.77%), Grazing land (0.33%), wetlands (0.11%), gardens (0.08%) and unused land of 0.05%. The different land uses pattern and its percentage coverage is presented in Table 4.

Table 6 Land use pattern of the rural municipality

	Jagarnathpur Rural	municipality	
S.N.	Land Use Pattern	Area (sq.km)	Percentage
1	Agricultural Land	42.72	94.33
2	Unused land	0.02	0.05
3	Garden	0.04	0.08
4	Grazing land	0.16	0.33
5	Riverbank	1.51	3.33
6	Lakes or ponds	0.80	1.77
7	Wetlands	0.05	0.11
	Total	45.29	100

Source: village profile of Jagarnathpur rural municipality, 2075

Air Quality, Water Quality and Noise Levels

There are no instrumentally monitored baseline data on air quality. The project vicinity is devoid of any industrial activities and thus the quality of air was found to be good. Considering the local anthropogenic sources of air pollutants is vehicular movement, dust re-suspension into ambient air from graveled access road.

The proponent has not been found discharging any effluent into nearby river. River water is not used for drinking purpose by human.

Regarding the noise pollution, the main noise emitting sources within project boundary are operation of diesel generator and other machinery and vehicular operation. The intensity of sound was found to be 55db in the projected area.

3.2 Biological Environment

The project development area doesn't lie in any National Parks, Wildlife Sanctuary, Reserve, Buffer zone or any other legally protected area listed by the Government of Nepal for the conservation of critical and sensitive ecology or habitat of vegetation and wildlife. The proposed project is covers land area of 14,800.00 m². The area is covered with agricultural field. The vegetation found in the district are stated below:

3.2.1 Vegetation and Forest (Please specify the distance of the nearest forest from the project location and detail the presence of these specific species, rather than providing a general inventory of plants and animals at the district level.)

The project site is located in the Terai plain surrounded by the agricultural land. The dense forest area is in Parsa National Park which is 8 Km radial distance from the project site in the northern direction. The plant species found in the project site are Sugarcane, (Saccharum officinarum), Papaya (Carica papaya), and Banana (Musa paradisicia)

Some vegetation found in the district were Sissau (*Delbergia sissoo*), Simal(*Bombax ceiba*), Khayar (*Acacia catechu*), Sal (*Shorea robusta*), Mango,, Bar (*Ficusbengalensis*), Peepal (*Ficus religiosa*), Bhalayo (*Semecarpus anacardium*), Jackfruit, Jamun, Mouwa, bambooetc. Medicinal herbs found in this region are Gumma, Pudina, Tulasi, Aloe Vera, Tejapat, Harro, Taal Mishri, Bahera, etc. similarly, Non timber trees in this area are Sugar Cane, Kurilo, Kaulo, Amala, Ban Lasun, Chiraito, Setak Chini etc.

The proponent has proposed to install large biogas within the well demarcated land, hence no issues for the construction and running the project for overall management. To install the large biogas project, no trees are needed to be cut and no vegetation are needed to be destroyed.

3.2.2 Wildlife

Some wildlife observed in this region are Indian giant squirrels (Ratufa Indica), Common grey mongoose (Herpestesedwardsi), Jackals (Cannes aurous), monkey (Macaca mulatta), etc.

3.2.3 Birds

Major bird species reported are Battai (Turnix suscitator), Bhangera (Passer (Cacomantis merulinus), Parewa (Columba livia), Dhukur (Streptopelia chinensis), Dangre (Acriotherus tristis) and Kauwa (Corvus splendens).

3.2.4 Herpeto Fauna

Some of the Herpeto fauna found in the river area and project vicinity are King Cobra (Ophiophagus Hannah), Oriental rat snake (Ptyas mucosa) and Common krait (Bungarus caeruleus)...

3.2.5 Fish Species

The major fish species in these areas are: bighead carp (Aristichthys nobilis), silver carp (Hypophthalmichthys molitrix), grass carp (Ctenopharyngodon idella), common carp (Cyprinus carpio carpio), and rohu (Labeo rohita

3.3 Socio-economic Environment

3.3.1 Project District and Rural Municipality

The proposed project site lies in Jagarnathpur rural municipality of Parsa district. Parsa district consists of one metropolitan city, 3 municipalities and 10 rural municipalities, 14 local levels in total. Jagarnathpur rural municipality is one of the rural municipality of the district which lies in the western part of the Parsa district. The rural municipality is bordered by six local levels, namely Sakhuwa Prasauni in the east, Paterwa Sugauli rural municipality in the north-east, India in the west, Pokhariya municipality, Kalikamai rural municipality and Dhobini rural municipality in the south and Jirabhawani rural municipality in the north. The total area of Jagarnathpur rural municipality is 45.29 sq. km., which is 3.34 percentage of total area of Parsa district.

This rural municipality was formed in 2073 B.S. by combing seven VDCs, namely, Janaki Tole, Ghoddaud Pipra, Jagarnathpur Sira, Pidariguthi, Auraha and Mashihani. The rural municipality consists of six administrative wards. The office of this rural

3.3.2 Demography

According to national census 2078, the total population of Parsa district is 6,01,017 where 48% are female and 52% are male. The average household size is 6.29 which is 1.3 times the figure is Nepal: 4.89 and male per female is 108.21 which is 20% more than that of Nepal i.e. 94.16

Similarly, as per national census 2078, the total population of the rural municipality is 32,649. The most populated ward is ward no 5 which consists of 6551 populations while the ward no. 3 consists of least population of 4072 members. The population density of the district is 713.35 per square kilometer which is much higher than the national average density of 180 per square kilometer. The average household size is 5.85 person and sex ratio is 105.15. The demographic distribution according to sex, population density and age distribution of population in Jagarnathpur Rural

Municipality are listed in Table 6, Table 7 and Table 8 respectively. The demographic distribution of Parsa district is shown in table 9

Table 7 Population of rural municipality

Ward no.	Household no.		Population		Average Household	Sex ratio
		Male	Female	Total	size	
1	1036	3081	2872	5953	5.75	107.28
2	850	2571	2358	4929	5.80	109.03
3	725	1994	2078	4072	5.62	95.96
4	950	2806	2760	5566	5.86	101.67
5	1033	3427	3124	6551	6.34	109.70
6	988	2855	2723	5578	5.65	104.85
Total	11,164	16734	15915	32649		
					5.75	107.28

Source: Central Bureau of Statistic (CBS), 2078

Table 8 Population density according to ward

WARD	POPULATION DI	ESCRIPTION		SCRIPTION	DENSITY
NO.	Population	Percentage	Area (sq.km)	Percentage	(PER SQ. KM)
1	4540	16.19	8.01	17.69	566.78
2	5093	18.16	6.84	15.1	744.59
3	4163	14.85	4.65	10.27	895.27
4	5891	21.01	13.03	28.77	452.11
5	5546	19.78	4.3	9.49	1289.77
6	2805	10.00	8.46	18.68	333.56
Total	28038	100	45.29	100	713.35

Source: Central Bureau of Statistic(CBS), 2078

Table 9 Population distribution according to age group

W	Population according to age group (years)															
ar d	Bel	ow 5	6-	-14	15	-18	19	-24	25	-49	50	-59	60)-69		and ove
no	m al e	fe ma le	m al e	fe ma le	m al e	fe ma le	m al e	fe ma le	m al e	fe ma le	m al e	fe ma le	m al e	fe ma le	m al e	fe ma le
1	32 7	271	60 5	508	23 0	143	74 9	671	22 4	164	17 4	115	13 7	102	75	45
2	35 3	294	65 8	641	22 0	185	83 4	786	20 7	169	17 0	133	12 8	117	11 3	85

3	28 3	290	50 7	414	24 4	187	69 0	444	20 0	135	15 1	93	11 5	84	64	62
4	32 2	253	83 5	615	29 7	208	11 09	933	26 8	179	22 9	153	17 0	131	11 8	68
5	48 9	383	64 5	544	24 0	178	91 8	821	24 9	203	19 9	154	18 5	164	11 0	64
6	19 6	141	35 3	249	13 3	87	49 9	447	14 8	101	11 2	62	66	77	81	53
tot al	19 70	163 2	36 06	297 1	13 64	988	47 99	430 2	12 96	951	10 35	790	80 1	675	56 1	377

Source: Source: Central Bureau of Statistic (CBS), 2078

Table 10 Population data of parsa district

District	Household	Arrama an Hawankald	Popul	Male per	
	Housenoia	Average Household	Male	Female	Female
Parsa	654,471	5.79	338,362 (51.7%)	316,109 (48.3%)	106.99

Source: Central Bureau of Statistic (CBS), 2078

3.3.3 Caste/Ethnicity

The caste and ethnicity distribution table of the Jagarnathpur rural municipalities shows the mixed settlement, which has majority of population from Terai indigenous group followed by Terai others, muslim and Terai Dalit. Similarly, Parsa district records highest number of musalmans than other castes. The list of caste and ethnic distribution of the rural municipality and that of Parsa district is shown in the table below.

Table 11 Caste distribution in the rural Municipality

Ward				Desc	ription o	f caste	•				
no	Mountai n Chhetri/ Bramhin	Chhetri/Br in Indigen		Terai Indige nous	Moun tain Dalit	Terai Dalit	Mus lim	Mou ntain other s	Tera i othe rs	Not men tion ed	Total
1	230	165	125	1225	8	1290	2125	40	725	20	5953
2	38	71	3	2234	1	828	1213	0	525	16	4929
3	4	7	0	10	3	640	1651	7	1748	2	4072
4	0	27	6	3808	5	783	762	0	1	174	5566
5	10	181	3	577	13	150	194	0	5408	15	6551
6	25	98	7	4695	151	158	255	23	9	157	5578
Total	307	549	144	12549	181	3849	6200	70	8416	384	32649
Percen tage	0.94	1.68	0.44	38.44	0.55	11.79	18.99	0.21	25.78	1.18	100.00

Source: Central Bureau of Statistic (CBS), 2078

Table 12 Caste distribution of Parsa district

Castes	Pa	ırsa
Musalman	17.2	16.8
Kurmi	8.9	9.1
Tharu	6.9	7.1
Yadav	6.8	6.5
Kanu	6.2	6.4
Chamar/Harijan/Ram	5.1	5.1
Teli	4.4	4.5
Dusadh/Pasawan/Pasi	2.8	2.8
Koiri/Kushwaha	2.5	2.6
Baraee	1.9	2

Source: Central Bureau of Statistic (CBS), 2078

3.3.4 Religion

About 72.5% of people follow Hinduism in the rural municipality. It is then followed by Islam and Buddhism. In the district 83.1% follows Hinduism, wheras 14.5% follow Islam. The distribution of population according to religion is given below

Table 13 Population distribution according to religion in rural municipality

Ward no		Popula	ntion distribu	tion according	to religio	n	J
	Hinduism	Buddhism	Islam	Christianity	Kirat	Not mentioned	Total
1	3201	17	2653	13	2	67	5953
2	3640	15	1234	12	7	21	4929
3	2542	6	1509	0	0	15	4072
4	3519	15	1493	2	0	537	5566
5	4913	47	1553	17	0	21	6551
6	2927	143	2132	165	19	192	5578
Total	20742	243	10574	209	28	853	32649

Source: Central Bureau of Statistic (CBS), 2078

Table14 Population by religion

Religion	Parsa				
Hindu	83.1%	499,438			
Islam	14.5%	87,033			
Buddism	1.7%	10,069			
Kirat	0.4%	2,571			
Others	0.2%	882			
Christianity	0.1%	753			
Sikhism	0%	130			
Jainism	0%	116			
Prakriti	0%	24			
Bahai	0%	1			
Bon	0%	0			

Source: Central Bureau of Statistic (CBS), 2078

Cultural and Religious Sites

The main festivals celebrated in this region are Rakshya bandhan, Krishna Janmastami, JItiya, Karmadharma, Dashain, Tihar, Chhath, Ekadashi Parwa, Sorha Sombar, Karthik Puja, Maghe Sakranti, Holi, Chaite Dashain, Chaite Chhath, etc. Ramjanaki Mandir is the famous temple of this rural municipality. Deruwa mai mandir is at 300m east to the project site

3.3.5 Mother Tongue

Bhojpuri is spoken by majority of the population both in the district and in this rural municipality which is about 98.04% of total population in rural municipality. The distribution of population according to mother tongue in the rural municipality is enlisted in Table 14 and that of the district in table 15.

Table 15 Population distribution according to mother tongue

			,		
	Mother	Population			
SN	Tongue	Total	Male	Female	
1	Nepali	188	103	85	
2	Maithili	18	11	7	
3	Bhojpuri	32012	16423	15589	
4	Tharu	308	142	166	
5	Urdu	101	49	52	
6	Hindi	10	1	9	
7	Others	12	5	7	
	All MTongues	32649	16734	15915	

Source: Central Bureau of Statistic(CBS), 2078

Table 16 Language spoken in Parsa district

	Population in Percentage						
Language	Both Sexes	Male	Female				
Bhojpuri	84.7	85.2	84.2				
Nepali	4.8	4.7	4.9				
Tharu	3.8	3.6	4				
Urdu	2.1	2	2.1				
Tamang	1.2	1.2	1.3				
Maithili	1.1	1.05	1.08				
Hindi	0.5	0.5	0.5				
Nepalbhasha							
(Newari)	0.5	0.4	0.5				
Marwadi	0.4	0.4	0.4				

Source: Central Bureau of Statistic(CBS), 2078

3.3.6 Literacy and Education

In the Parsa district 43.8% female and 66.7% male can both read and write whereas 2.9% of both male and female can only read. Similarly, the literacy rate of the rural municipality is 54.97%. The literacy rate of male in the area is 63.63% which is higher than that of female (46.32%). The literacy status of the Jagarnathpur rural municipality is shown in Table 16 below and that of Parsa district in table 17.

Table17 Literacy rate of the rural municipality

Table 17 Electacy rate of the ratal manacipality							
Ward no.	Literacy rate						
	Male Female Total						
1	55.30	35.96	45.93				
2	57.77	35.85	46.81				
3	82.74	79.64	79.69				
4	63.35	47.17	55.29				
5	59.87	40.58	50.22				
6	62.72	41.74	52.23				
Total	63.63	46.32	54.97				

Source: Central Bureau of Statistic (CBS), 2078

Table 18 Literacy of Parsa district

Sex	Parsa		
Can Read and Write: Female	43.8%	111,632	
Can Read and Write: Male	66.7%	183,615	
Not Literate: Female	53.1%	135,268	
Not Literate: Male	30.3%	83,412	
Can Read: Female	2.9%	7,485	

Sex	Parsa		
Can Read: Male	2.9%	7,868	
Not Stated: Female	0.2%	379	
Not Stated: Male	0.1%	273	

Source: Central Bureau of Statistic(CBS), 2078

3.3.7 Status of population with disability

Out of various types of disabilities, physical disabilities prevails the most in the rural municipality. Ward no.1 has the highest disability population of 35. The district has about 1% disabled people. The disability status of the rural municipality is shown in the table 18 and that of district in table 19

Table 19 Disabilities population in the rural municipality

Ward		Disability types							
no	No	Physic	Intellect	Visual	Hearin	Vocal	Mental	Not	Tot
	disabil	al	ual	disabil	g	Disabil	Disabil	mention	al
	ity	disabil	disabilit	ity	Disabil	ity	ity	ed	
		ity	y		ity				
1	3334	20	4	5	3	0	3	1171	4540
2	4181	14	1	0	3	3	0	891	5093
3	4126	14	2	0	5	0	0	16	4163
4	3697	8	1	2	0	0	0	2183	5891
5	5495	11	0	2	1	2	0	35	5546
6	2728	3	1	1	2	0	1	69	2805
total	23561	70	9	10	14	5	4	4365	2803
									8
Percent	84.03	0.25	0.03	0.04	0.05	0.02	0.01	15.57	100
age									

Source: Central Bureau of Statistic(CBS), 2078

Table 20 Disability population on the district

Population by disability type	Number
Blind/low vision	
Female	801
Male	914
Deaf/hard of hearing	
Female	280
Male	315
Deaf-Blind	
Female	40
Male	64
Intellectual disable	
Female	63
Male	86

Mental disable	
Female	156
Male	283
Multiple disable	
Female	165
Male	210
No disability	
Female	285758
Male	305846
Physical	
Female	789
Male	1344
Speech problem	
Female	245
Male	410

Source: Central Bureau of Statistic (CBS), 2078

3.3.8 Source of Drinking Water

Out of 5117 households in the rural municipality, 4576 households (89.43%) uses tube well/hand pump as the source of drinking water whereas 359 households uses Tap/piped water as source of drinking water. In the Parsa district tube well is the most common source of drinking water which is 81%, followed by piped tap which is 14.4%. From different sources, the source of drinking water in the households as per ward in the rural municipality is in the table 21 and district in table 22

Table 21 Drinking water source in different households

Ward no	Drinking water source per household						
	House Public		Deep	Hand	Covered	Others	Total
	tap	Tap	Boring	Pump	Well		
	water	water					
1	215	54	1	614	0	5	889
2	61	20	0	921	1	1	1004
3	2	0	0	635	0	1	638
4	80	94	1	900	0	0	1075
5	1	1	0	858	0	2	862
6	0	0	0	648	1	0	649
Total	359	169	2	4576	2	9	5117
Percentage	7.02	3.30	0.04	89.41	0.04	0.18	100

Source: Central Bureau of Statistic(CBS), 2078

Table 22 Households by drinking water source

Source	Parsa (Households)				
Tube Well	81% 77,392				
Piped Tap	14.4% 13,715				
Sprout Water	1.3%	1,241			
Others	1.3%	1,203			
Not Stated	1.1%	1,082			
Uncovered Well	0.5%	461			
Covered Well	0.3%	297			
River or Stream	0.1% 125				

Source: Central Bureau of Statistic (CBS), 2078

3.3.9 Energy use for cooking

According to municipal household survey 2074, about 97.54% of household use firewood for cooking purpose in the rural municipality. Other source of energy for cooking include LPG, which is utilized by 1.93% households. Similarly, 11 households utilize kerosene and 15 household uses other source of energy for cooking. Similarly, in the district also, firewood is the main source of cooking which covers about 65.8% of total households. The utilization of different source of energy per household for cooking in the rural municipality is given in table 23 and that of district in table 24

Table 23 Household utilizing different source of energy for cooking

Ward no	H	Household utilizing different source of energy							
	Firewood	Firewood Kerosene L.P. Gas Cow		Others	Total				
				dung					
1	839	2	45	1	2	889			
2	989	3	9	0	3	1004			
3	628	1	7	0	2	638			
4	1056	1	15	0	3	1075			
5	856	1	0	0	5	862			
6	623	3	23	0	0	649			
Total	4991	11	99	1	15	5117			
Percentage	97.54	0.21	1.93	0.02	0.29	100			

Source: Central Bureau of Statistic(CBS), 2078

Table 24 Households by main type of cooking fuel

Column	Parsa (Ho	ouseholds)
Wood	65.8%	62,805
LPG	15.7%	14,970
Cow Dung	15.7%	14,994
Biogas	0.3%	258
Kerosene	1.1%	1,067
Electricity	0%	34
Others	0.3%	265
Not Stated	1.2%	1,123

Source: Central Bureau of Statistic (CBS), 2078

3.3.10 Energy use for Lightening

Electricity, Kerosene, Solar are the source of energy both for the district and rural municipality for the purpose of lightening. 94.51% of household use electricity for lightening while 4.96% use kerosene in rural municipality. Similarly, in the district about 72.2% uses electricity and 24% depend on kerosene. The usage of different energy source for lightening is given in table 25 and table 26

Table 25 Household using different source of energy for lightening

Ward number	Household	Household using different source of energy for lightening							
	Electricity	Electricity Kerosene Solar Others							
1	772	105	8	4	889				
2	944	50	8	2	1004				
3	611	26	1	0	638				
4	1009	64	0	2	1075				
5	859	2	0	1	862				
6	641	7	0	1	649				
Total	4836	254	17	10	5117				
Percentage	94.51	4.96	0.33	0.20	100				

Source: Central Bureau of Statistic (CBS), 2078

Table 26 Households by main type of lighting fuel

Column	Parsa (Households)				
Electricity	72.2% 69,000				
Kerosene	24%	22,959			
Solar	2.1%	1,962			
Not Stated	1.2%	1,118			
Others	0.3%	308			
Biogas	0.2%	169			

Source: Central Bureau of Statistic (CBS), 2078

Industries and Trades

There are no industries within the municipality, and the primary occupation of the residents is agriculture, which yields an annual production of 1,038 metric tons of crops.

Livestock and Poultry

The municipality has 8 dairy farms and 12 poultry farms. In addition to these, many households also engage in small-scale livestock and poultry farming, contributing to the local food supply and supplementing their income.

Socio economic information of direct impact area.

There are no any households within direct impact zone i.e. within 100m radius.

Socio economic information of indirect impact area.

The indirect impact area includes the area of 500 m radius from the project site, where indirect activity during construction and operation takes place. This area includes 79 households and covers Gadhaiya village.

- a. There are 79 houses in Gadhaiya village.
- b. In this village 70 houses of Yadav ethnicity, 3 houses of Giri ethnicity and 6 houses of Dalit ethnicity.
- c. Approximate 60 percent people are educated.
- d. Average yearly income of each family is approximate two lakh.
- e. There are 10 tractors in this village, No any another large vehicle in this village.
- f. 94 percent families depend on agriculture and 6 percent on Job.
- g. 18 percent families are using LPG for cooking and 82 percent families are using wood, charcoal.
- h. There is electricity line of Nepal government.
- i. 3 disable person in whole village.
- j. 4 house head is single women (widow)

4. Review of Plans/Polices/Legislations and Guidelines

Government of Nepal (GoN) has adopted various policies, acts, regulations and guidelines to ensure the integration of development with the environmental conservation. In addition, for implementation of SREP large biogas projects, EMF and SMF are prepared for guiding overall safeguard implementation. The ESIA will be guided by the requirements and provisions of the following acts, rules and guidelines as applicable. The descriptions are provided in Annex A-6.

The Constitution of Nepal

1. Plans and Policies

- a. National Environment Policy, 2076
- b. National Forest Policy, 2076
- c. National Transport Policy, 2058
- d. Fifteenth Plan (2076/77-2080/81)
- e. Climate change policy 2019 AD
- f. Renewable Energy Subsidy Policy, 2073
- g. National Energy Crisis Reduction and Electricity Development Concept Paper, 2072

2. Acts

- a. Environment Protection Act, 2076
- b. Environmental Protection Act of Bagmati Province, 2077 B.S.
- c. Local Government Operation Act, 2074
- d. Labor Act, 2074
- e. Land Acquisition Act, 2039
- f. The industrial Act,2039
- g. Child Labor (Prohibition and Regulation Act, 2056)
- h. Soil and Water resource conservation Act, 2039
- i. Solid Waste Management Act, 2068
- Water Resource Act, 2049
- k. Forest Act, 2076

3. Rules

- a. Environment Protection Rules, 2077
- b. Solid waste Management Rules, 2070
- c. Labor Regulations, 2075

4. Guidelines and Criteria

- a. National EIA Guidelines, 2050
- b. EIA Guidelines related to forest sector, 2052
- c. Environment Friendly Local Governance Framework, 2070
- d. Other Directives related to forest
- e. National Ambient Air Quality Standard, 2059
- f. Noise Level Standard of Nepal, 2069
- g. Generic Standard for discharging industrial effluent in inland surface water, 2058

- h. National Diesel Generator Emission Standard, 2068
- 5. International Policies, Convention and Treaty Agreement
- a. Convention on Biodiversity, 1992

UN Framework Convention on Climate Change 1992

- b. World Bank Safeguard Policy (OP 4.10Indigenous Peoples)
- c. World Bank Safeguard Policy (OP 4.11 Physical Cultural Resources)
- d. World Bank Safeguard Policy (OP 4.12 Involuntary Resettlement)

5. IMPACT ASSESSMENT

This section provides the predicted impact of the implementation of the proposal on surrounding environment and community (both beneficial and adverse) without mitigation scenario. Every development project comes with some adverse impact along with its community benefit. The main purpose of conducting environmental and social assessment is to enhance the beneficial impacts and to reduce potential adverse impacts. This section distinctly categorizes the envisaged beneficial impacts as well as adverse impacts in the subsequent subsections. The adverse impacts are categorized into physical, chemical, biological and socio-economic environment and assessed with extent, magnitude and duration of the predicted impacts.

5.1 Beneficial Impacts

5.1.1 Construction Phase

a. Employment Opportunity to Locals

The construction period of the project is six months. The number of workforce will vary during civil construction work and installation of necessary equipment that require average 25-30 skilled and unskilled human resources during construction phase. The technology provider will supply the skilled human source while unskilled human resource requirement will be fulfilled from the local area. This will increase the employment opportunities to locals. *The impact is direct, have a medium level of magnitude with local extent and short term in nature.*

b. Skill Development of Locals and improvement in livelihood

After involvement of local people in the project during construction period, the unskilled labor will get chance to improve themselves and help them to get skill and capacity for construction procedure, fabrications and installation of equipment. Their skilled knowledge will help them to get jobs in future. Apart of those, retail shops and restaurants will be benefitted with their daily income by selling foods and other items to the workers during construction period. The impact is direct, have a low level of magnitude with local extent and short term in nature.

5.1.2 Operation Phase

c. Reduction in Greenhouse Gas Emission

Methane is released from poultry manure and unsustainable management ofwastes from poultry, cattle farm, sugar industry, which contributes in greenhouse gas emission and is 28 times more potent than CO₂. The implementation of project uses such biodegradable wastes as input and produce usable gas which will directly help in reducing emission of GHG into atmosphere. The impact is direct, have a medium level of magnitude with regional level extent and long term in nature. The impact is significant.

d. Sustainable Waste Management

The project will utilize the large amount of poultry, cattle farm, sugar industry and hotels waste to operate the large biogas plant. This helps industry to manage the

organic waste as well as it helps to clean the environment without disposing in landfill site which otherwise could have created unwanted flies and vectors borne disease, bacteria and odor pollution in the nearby environment. The project will convert the waste into biogas and fertilizer. The impact is direct, have a medium level of magnitude with regional level extent and long term in nature. The impact is significant.

e. Employment Opportunity

During the operation phase, for regular cleaning, garbage disposal, and protection of the biogas plant, locals will be hired. This will also help for the support of their dependents. The impact is direct, have a medium level of magnitude with local extent and long term in nature. The impact is significant.

f. Skill Development of Locals

During the operation period, the locals involved will get to learn the skills and techniques required to run and manage the plant. This will help them to build their capacity and can use their learned skills to apply in similar projects. *The impact is direct, have a low level of magnitude with local extent and short term in nature.*

g. Availability of Organic Fertilizer& CNG

The biogas and the fertilizer will be available of the locals in competitive cost which can support to increase agriculture production and dependency of imported fertilizer. Similarly, CNG gas will be available for the commercial entities. *The impact is direct, have a medium level of magnitude with regional extent and long term in nature. The impact is significant.*

5.2 Adverse Issues

5.2.1 Construction Phase

5.2.1.1 Physical Environment

a. Change in land use

The proposed land of the sub-project is agricultural land and it is owned by one of board member of the developer (Annex: 12). The Land 5,255 m2 will be used for the construction of the proposed biogas plant. Apart from this land, the subproject is not using any land parcels of the community people for the development of subproject. In addition the land is not currently being used by any other parties besides the landowner and it has been left fallow for the purpose implementing the bio gas subproject. Furthermore, as the subproject is not using the agricultural land from the community members, it will not affect the livelihood of the local people.

The construction work shall be carried out with no loss of trees and greenery measures will be undertaken around the sub-project site. Therefore, the envisaged impact is direct, low magnitude, site-specific and long term.

b. Issues related with Air

The construction activities such as operation of vehicles to transport the construction materials, excavation, mixing of aggregates generate dust, smoke involve emission of

CO₂, dusts, and other harmful gases. However, the air pollution is less likely to affect the local people as there is no settlement in the direct impact zone of 100m radius and nearest settlement is in the indirect impact zone of 500m radius away from the project site. Such activities will only continue until the construction work completes, thus the envisaged impact can be considered as direct, site-specific in nature, low in magnitude and short term in duration.

c. Issues Related with Water

Percolation of wastewater generated from washing of construction materials, spillage of lubricants, grease, petroleum fuels and percolation of black and grey water generated from construction camp could pollute the groundwater. The local people depending on groundwater source for running various domestic purposes can also get affected from such activities. However, there does not seem much construction activities as most of the construction components are prefabricated so the predicted impact on water sources can be considered as direct, low in magnitude, local in nature and short term.

d. Issues related with Soil Pollution

Another impact that could result from construction activities is depletion of soil quality. The construction materials such as cement contain certain level of chemicals which when mixed with soil can deplete its fertility over the time. Besides, haphazard disposal of construction debris can cause formation of muddy ditches during rainy season which would possibly hinder the staff members and local passersby to walk comfortably. Other chemicals like grease and petroleum fuel if spilled will also reduce fertility of soil in the project site. The envisaged impact is direct, *site specific*, *low in magnitude*, *and short term in duration*.

e. Increase in Noise Level due to Construction Activities

The operations of different machineries during the construction period like excavators, movement of vehicles generate noise in the project site and around project vicinity. However, the locals would not be significantly affected since the nearest settlement is away from direct impact zone of 100 m radius. But the increase in noise is likely to impact construction workers. The envisaged impact is direct, *low in magnitude*, *sitespecific in nature and short term*.

f. Issues Related with Spoil Disposal and Stockpiling of Construction Materials

It is likely to have construction debris and stockpiles of construction materials in any construction activities. But haphazard disposal of such materials causes disturbance in aesthetic beauty of the surrounding area and besides, percolated water from these construction materials during rainy season can reach agricultural field. In addition, such activities can also reduce soil fertility, increase in dust during windy season and formation of mud during rainy season. However, the project is small scale and most of the components are prefabricated. So only small quantity of construction material is required and only small quantity of construction debris will be generated which would not cause significant impact in the sub-project vicinity. Hence, the envisaged

impact can be considered direct, low in magnitude, site-specific in nature and short term.

g. Traffic Management

While transporting the construction materials to the project site, there may be the possibility of traffic congestion in the road as the transportation vehicles are quite bigger than other types of vehicles. These vehicles could take up much space in the road creating trouble to other people using the same route. The foreseen *impact is direct, low, local and short term in duration*.

5.2.1.2 Biological Environment

The project development area doesn't lie in any National Parks, Wildlife Sanctuary, Reserve, Buffer zone or any other legally protected area listed by the Government of Nepal for the conservation of critical and sensitive ecology or habitat of vegetation.

The proposed project is located at the land of the developer which occupies 14,800.00 m² of land area. The area is covered with agricultural field. Few fruit bearing trees such as mango, banana and papaya can also be found in the project site vicinity, however; the project will not require felling down of any trees. Therefore, the impact on vegetation is not envisaged.

5.2.1.3 Socio-economic Environment

a. Occupational Safety and Health of Workers

During the construction phase, the construction work force is expected to be exposed to a number of construction related health hazards. The construction fugitive emissions, noise, and physical injury are some of the occupational health issues for construction workforce. Moreover, work in height, confined space and hazardous environment are other potential threats to workers. Besides that, communicable diseases may increased risks to the workers. The envisaged impact is direct, high in magnitude, site-specific in nature and medium term.

b. Pressure on Utilities and Infrastructure

The construction activities generally cause pressure on community water supply system, increase in solid waste generation due to increase in construction workforce etc. Since the project construction period is 6 months and construction workers are in limited numbers, there will be very negligible pressure on utilities from community. Moreover, the project has its own water source, which is sufficient for entire project period so there will be no any community water supply source used by the subproject. Hence, the impact is not envisaged.

c. Health and Sanitation Related Issues In and Around Sub-Project Site

During the construction phase, the workers are exposed to various kind of machineries which if mishandled can cause injuries. In addition, nearby locals especially children can also meet an accident around the project area. The envisaged *impact is direct, moderate, local and short -term*.

d. Trespassing and Nuisance to Nearby Community

The construction workforce can sometime intrude into nearby community and cause annoyance among the residents. Such activities can create opposition and conflict from the community side. However, the construction workforce will reside inside the project premises, which has completely barricaded with wall and they will be mandated not to create any conflict in the community, the envisaged impact will be indirect, *low*, *site-specific and short term*.

e. Conflict and Grievance management

The installation of biogas plant will be a new concept to the surrounding village. Therefore, to avoid the conflict, villagers need to be well informed about the positive effect of biogas.

- a) Though biogas/methane gas is highly flammable, and a naked flame can easily catch fire if leaked, there will be a safety measure present like fire extinguisher nearby the subproject place.
- b) They should be aware about positive effect brought about by biogas plant which will help to manage the poultry organic waste by preventing leaching to ground-water causing contamination, prevent inland degradation, prevent flies and different disease vectors, will prevent flood away of the organic waste in rainy seasons, disease prevention and prevent foul smell coming from the poultry waste.
- c) Involuntary Land Acquisition and Displacement Issue: The proponent has its own land and has full ownership. Hence there won't be any problem in land ownership.
- d) Labor Influx and associated impacts in the local community: Due to the development of the project, the area will become a center of attraction to many people of the surrounding vicinity. The labor influx during construction phase is estimated to be around 750 person days, which is lower to cause significant community disturbances. Hence, the impact caused by influx of labors to local community is negligible.

During the field visit, such social conflict issues were well discussed in presence of Ward Chairperson, Ward members, Environmental Officers, public and other knowledgeable persons. If any grievances arise the mishandling could invite social demonstration, opposition and conflict. Hence, they have taken responsibility to well manage the conflict if anything is raised. The envisaged impact will be indirect, *moderate*, *local and long term*.

5.2.2 Operation Phase

5.2.2.1 Physical Environment

a. Issues Related with Management of raw materials storage and post digestate organic waste

The by-product generated from the anaerobic digestion to produce biogas is organic waste. They are mostly semi solid slurry and liquid slurry, generally known as digestate. These digestate have high BOD, nitrogen content and can contaminate land and water if not managed properly. Besides the digested, the storage of organic poultry waste in large amount can also create nuisance. If these poultry waste feeds are not stored in a proper roofed place with sealed ground, leaching of such substrate can possibly contaminate groundwater especially during rainy season. The project has to build the storage place for post digested effluent. The envisaged impact is direct, moderate, site-specific to local in nature and long term.

b. Impact associated with collection and transportation of waste

The biogas plant will be using substrates from poultry, cattle farm, sugar industry and hotels collected from nearby areas to produce biogas. These substrates are organic waste (green masses, and poultry waste). It may create foul odor during transportation, dropping of wastes, vehicular emission. The envisaged *impact is direct, local, short term and moderate in magnitude*

c. Issues related to odor during storage of raw material and slurry production

The raw materials to be used for biogas production are organic waste. Open storage of such large amount of substrate could cause foul odor in the project area and would attract flies and vector diseases. Similarly, haphazard disposal of digestate and absence of proper composting will also create foul smell. The foul odor might possibly impact the surrounding vicinity at the nearest settlement. So the receptors of impact are apparently the in-house staff. The envisaged impact is direct, moderate, site-specific in nature and long term.

d. Issues Related to Over Extraction of Ground Water for Meeting Demand

The water required to operate the plant is 65 m3/day. However, only 40 m3 of fresh water will be used for dilution purpose as the remaining volume will be sourced in from recirculation of separated slurry water. Similarly, the project site is mostly agricultural open land and has greater availability of groundwater recharge zone so the extraction of groundwater will not impact significantly on groundwater depletion. Hence, the envisaged impact is direct, low in magnitude, local and long term

e. Management of Wastewater from Digested Slurry

The digested slurry produced from anaerobic digestion will be used as compost and also sold in the market as fertilizer. The digested slurry will be separated into liquid and solid through Screw Press Separator. The semi-solid slurry will be further dried to make compost while liquid slurry will be recirculated for operation of plant and remaining liquid slurry is proposed to be used in the owner's farm itself. However, if

the liquid effluent is directly discharged to the near water body, it would increase BOD, TS and turbidity of the receiving water. Therefore, the envisaged *impact* is direct, moderate, site-specific to local in extent and long term.

f. Impact of spilled chemicals from gas cleaning facilities

Biogas contains CO₂, H₂S, and moisture along with methane production at about 35%-45%. Especially, H₂S and moistures are necessary to remove so as to prevent the equipment from corroding and to prevent impact on biogas generator. The technology proposed to remove H₂S is Ferrous and biogenic scrubbing. This technology will not produce any chemical waste during the process however regeneration of ferrous element is needed periodically. Hence, issue related with spilled chemicals is not envisaged.

g. Increase in noise from plant operation

The noise is generated from various components to operate the plant such as agitators, pumps, substrate and feed loaders. Such operational activity can increase surrounding noise level greater than 85 dB and can cause temporary hearing loss, annoyance among the working staff if exposed for long time. In this regard, the envisaged *impact is direct, low in magnitude, site-specific in nature and long term*.

h. Gas leakage and Fire Hazard

The biogas/methane gas is highly flammable and a naked flame can easily catch fire if leaked. This will cause loss of life and property. Moreover, emission of methane gas in atmosphere will contribute in greenhouse gas emission, which is almost 28 times more potent than carbon-dioxide on heating up our planet. However, the fire extinguisher can prevent such situation. In this regard, the envisaged *impact is direct, moderate in magnitude, site-specific to local and long term*.

i. Issues with drainage management

Proper management of drainage is necessary in order to channel rainwater without causing any damage to substrate storage area. If the drainage is not available, washoff of such organic waste can percolate into groundwater and nearby rivers which will have effects on water quality. Similarly, the drainage is necessary to manage wastewater generated from cleaning the plant units and to channelize the liquid effluent after decantation to avoid contamination of nearby water bodies and groundwater as these wastes are highly pathogenic. *The envisaged impact is direct, low, site-specific and long*

5.2.2.2 Biological Environment

a. Maintenance and Protection of greenery in the Sub-Project Area

There will not be any nuisance to the biological environment as the biogas plant will be installed in a well demarcated land area. Instead, plantation of trees will be done to maintain the greenery in the sub-project area.

5.2.2.3 Socio-economic Environment

a. Occupational health and safety

During the operation period, the workers are required to handle organic waste materials and slurry. Due to this, they are prone to get infected from various diseases. They are also exposed to noise from operation of plant. Prolong exposure to such activities without proper care of safety measures taken can affect their health in long run. Besides, they can also be injured due to mishandling of machineries and fire hazard. Communicable disease (COVID-19) risks are another risks in this recent situation and the workers can be at high risks if PPEs are not used and social distancing is not maintained. *The envisaged impact is direct, high, site-specific and long term.*

b. Issues related with health and sanitation in and around project site

The operation of biogas plant consists of handling waste like cow dung which might be pathogenic to some extent. Haphazard disposal and improper management can cause increase in vector borne diseases and can spread out to nearby community which could create agitation among the locals and oppose the project. The envisaged impact is high, site-specific and long term. Similarly, if machineries, dome, plant surroundings are not cleaned from time to time during operation phase, if there's no proper management of toilets and safe drinking water, employees and locals may get health problems. *The envisaged impact is direct, high, site-specific and long term*.

c. Conflict and grievances management

The project should always be prepared for the management of conflict and grievance management, as the mishandling of such grievances could invite social demonstration, opposition and conflict. *However, the envisaged impact is considered as indirect, moderate, site-specific to local and long term.*

d. Impacts on IPS and vulnerable communities

The settlement of a community is found nearly 100 m away from the project area, due to which, the impact is negligible. Hence, no impact is envisaged in this regard.

e. Inflow of People in the Project Area

There will be 12 full time staffs during the operation phase. Similarly, due to unique nature of renewable energy industry, different people from diverse society may also visit the sub-project site. This may hinder the local culture and traditional activities of the local people which might create misunderstandings and conflict. However, since only few numbers of workers will be employed for the plant operation and management. Therefore, the envisaged impact is considered to be direct, site specific ,low and long term.

f. Issues related Sexual Exploitation Abuse and Sexual Harassment (SEA/SH)

The influx of labor in the sub-project area during the construction phase could poses a risk related to sexual exploitation and abuse/sexual harassment (SEA/SH). The interaction between workers and community members could lead to increased risks of GBV in the local communities. Additionally, there may be incidents of gender-based violence (GBV), sexual exploitation, and harassment among workers, sub-project staff, and local people. Therefore, effective and timely mitigation measures must be implemented to address and mitigate the potential risks of SEA/SH and abusive behaviors between sub-project-related staff and the local population. *The impact will be direct in nature, high in magnitude, local in extent and short term in duration*.

g. Gender discrimination and child labour

Male and female workers may be paid unequally for the same or similar works. Similarly, contractor may select male and female workers for selective works rather than the capacity of individual workers. Such gender discrimination on works and pay scale may create dispute at workplace and hindrance on progress of works. Similarly, there is probability of using children in the subproject as cheap construction labour. The impact will be indirect in nature, moderate in magnitude, site specific in extent and short term in duration.

i) Stakeholder Engagement and information disclosure

Stakeholder engagement and information disclosure is very important for the successful implementation of the proposed subproject. Avoiding or evading the stakeholders on proposed subproject activities may hamper the progress and sustainability of the subproject. Likewise, if information regarding the subproject is not shared with concerned stakeholders and locals, it can also create problem in subproject implementation and sustainability. The impact will be indirect in nature, moderate in magnitude, local in extent and long term in duration.

Impact Assessment Matrix

Table 27 Impact assessment

S.N	Environmental Issues	Impacts	Direct / Indirect Impact	Extent	Duration	Magnitude	Significance
	A. Beneficial Impacts						
A.1	Construction Phase						
A.1.1	Employment Opportunity to Locals	Unskilled human resource will be full filled from local area	D	L(20)	ST (5)	Mo (20)	45 Significant
	Skill Development of Local and improvement in livelihood	Unskilled labor will get skill and capacity. Retails shop and restaurants will get business.	D	L(20)	ST (5)	Lo (10)	35 insignificant
A.2	Operation Phase						
A.2.1	Employment Opportunity to Locals	Locals will be hired for regular jobs.	D	L(20)	LT (20)	Mo (20)	60 Significant
A.2.2	Skill Development of Local	Locals will learn skills and build their capacity.	D	L(20)	LT (20)	Lo (10)	50 Significant
A.2.3	Sustainable Waste Management	Manage organic waste, prevent from disposing in landfill.	D	L(20)	LT (20)	Mo (20)	60 Significant
A.2.4	Availability of organic Fertilizer and CNG	Organic Fertilizer and Bio CNG will be produced	D	R(60)	LT (20)	Mo (20)	100 Significant
A.2.	Reduction in Greenhouse Gas Emission	Biodegradable waste will be converted to useful gas.	D	R(60)	LT (20)	Mo (20)	100 Significant

	B. Adverse Issues/Impacts							
B.1	Construction Phase							
B.1.1	Physical Environment							
B.1.1.1	Change in Land use	Residual impact, existing agricultural land will be converted in project structures	D	S (10)	LT (20)	Lo (10)	40 Insignificant	
B.1.1.2	Issues related with air	Emission of dust, smoke, CO ₂ and other harmful gases through vehicular movement, excavation and related construction activities	D	S (10)	ST (5)	Lo (10)	25 Insignificant	
B.1.1.3	Issues related with water	 Pollution of groundwater through percolation of wash water from construction materials, spillage of lubricants Formation of muddy ditches during rainy season 	D	L (20)	ST (5)	Lo (10)	35 Insignificant	
B.1.1.4	Issues related with soil pollution	Degradation in soil fertility due to haphazard disposal of construction spoils, stockpiles and spillage of lubricants	D	S (10)	ST (5)	Lo (10)	25 Insignificant	
B.1.1.5	Increase in noise level due to construction activities	Increase in noise from operation of machineries, excavation and vehicular activities	D	S (10)	ST (5)	Lo (10)	25 Insignificant	

B.1.1.6	Issues related with spoil disposal and stockpiling of construction materials	 Degradation in aesthetic beauty Percolation of chemical content in waste water from construction material into agricultural land Loss of soil fertility Formation of muddy ditches during rainy season 	D	S (10)	ST (5)	Lo (10)	25 Insignificant
B.1.1.7	Traffic management	Traffic congestion on access road while transporting construction materials	D	L (20)	ST (5)	Lo (10)	35 Insignificant
B.1.2	Biological Environment						
B.1.2.1	Loss of Vegetation	No need to fell down any trees (Impact not envisaged)	-	-	-	-	-
B.1.3	Socio-economic and Culture	al Environment	I			1	
B.1.3.1	Occupational health and safety of worker	Exposure to fugitive emission, noise and risk of physical injury and communicable disease (COVID-19) risk, Health risks associated with poor labor camp, unsafe water and unhygienic condition, due to influx of outside and migrant laborers. Inadequate living space for laborers	D	S (10)	MT (10)	H (60)	80 Very Significant
B.1.3.2	Pressure on utilities and infrastructure	Due to shorter construction period and limited construction workers, the impact is not envisaged	-	-	-	-	-

B.1.3.3	Trespassing and nuisance to nearby community	 Intrusion of workforce to nearby community Intrusion of unauthorized personnel at construction site Annoyance and conflict 	ID	S (10)	ST (5)	Lo (10)	25 Insignificant
		between construction workforce and community					
B.1.3.4	Health and Sanitation Related Issues In and Around Sub-Project Site	 Injuries to workers while handling machineries Community children getting into accidents 	D	L (20)	ST (5)	Mo (20)	45 Significant
B.1.3.5	Conflict and grievances management	Conflict and grievances related with improper management of construction materials, aesthetic degradation, conflicts	ID	L (20)	LT (20)	Mo (20)	60 Significant
C.1	Operation Phase						
C.1.1	Physical Environment						
C.1.1.1	Issues related with management of raw materials storage and post digestate waste	Contamination of land and water sources if leaching of raw materials into underground water due to its improper storage system	D	L (20)	LT (20)	Mo (20)	60 Significant
C.1.1.2	Impact associated with collection and transportation of Waste	 Foul smell along the transportation route Possibility of dropping the waste on road Vehicular emission 	D	L (20)	ST (5)	Mo (20)	45 Significant

C.1.1.3	Issue related to odor during storage of raw materials and slurry production	Increase in flies and vector disease due to improper raw material storage system and haphazard disposal of post digestate	D	S (10)	LT (20)	Mo (20)	50 Significant
C.1.1.4	Impact of spilled chemicals from gas cleaning facilities	The project will adopt ferrous and biogenic scrubbing, so no impact is envisaged	-	-	-	-	-
C.1.1.5	Increase in noise from plant operation	 Increase in noise due to operation of biogas plant components. Temporary hearing loss, annoyance among the staff due to prolonged exposure 	D	S (10)	LT (20)	Lo (10)	40 Insignificant
C.1.1.6	Gas leakage and fire hazard	 Methane gas being highly flammable can cause fire hazard; loss of property and life Contribution to GHG emission due to leakage 	D	L (20)	LT (20)	Mo (20)	60 Significant
C.1.1.7	Issues with drainage management	 Percolation of wash-off water of organic feedstock and post digestate into groundwater and nearby river Alter in water quality parameter 	D	S (10)	LT (20)	Lo (10)	40 Insignificant
C.1.1.8	Over Extraction of Groundwater	About 65m³/day of water is required for dilution purpose out of which only 40m³ of	D	L (20)	LT (20)	Lo (10)	50 Significant

C.1.1.9	Management of	fresh water will be extracted from underground and remaining will be covered through separated water from slurry. • Excessive use of underground could lower the water table and could cause impact on availability of water in the locality that depends on underground water. • Increase in BOD, turbidity	D	L (20)	LT (20)	Mo (20)	60
C.1.1.9	Wastewater from Digested Slurry	 and TS of nearby water body if discharged directly into it Groundwater pollution 			21 (20)	1010 (20)	Significant
C.1.2	Biological environment	Groundwater ponduon		<u> </u>			
C.1,2.1	Maintenance and Protection of greenery in sub-project area.	Although no trees will be required to cut down during construction phase, greenery will be maintained.	-	-	-	-	-
C.1.3	Socioeconomic and Cultura	Environment					
C.1.3.1	Occupational health and safety	Physical injury to staffs Prone to catch disease from organic waste handling, COVID- 19 pandemic	D	S (10)	LT (20)	H (60)	90 Very Significant

C.1.3.2	Issues related with health and sanitation in and around project site	Spread of vector borne disease among the 3 HHs in the direct impact area and staffs due to improper management of organic waste, toilets, drinking water.	D	S (20)	LT (20)	H (60)	90 Very Significant
C.1.3.3	Conflict and grievances management	Conflict and grievances with aesthetics, odor, noise, haphazard disposal of digestate from local residents resulting opposition and conflict	ID	L (20)	LT (20)	Mo (20)	60 Significant
C.1.1.4	Inflow of People in Project Area	Increase in quarrel and debates among workforce and community	D	S (10)	LT (20)	Lo (10)	40 Insignificant
C.1.1.5	Issues related Sexual Exploitation Abuse and Sexual Harassment	Sexual Exploitation Abuse and Sexual Harassment	ID	L (20)	ST (5)	Lo (10)	35 Insignificant
C.1.1.6	Gender discrimination and child labour	Pay Parity in gender,child as cheap labour	ID	S(10)	ST(5)	Mo(20)	35 Insignificant
C.1.1.7	Impacts on IPS and vulnerable communities						

C.1.1.8	Stakeholder	Avoiding stakeholders, not	ID	L (20)	LT (20)	Mo (20)	60
	Engagement and	sharing information to locals					Significant
	information disclosure						

Note: D= Direct; ID = Indirect, S= Site specific; L = Local, R = Regional; ST= short term, NA = Not Applicable of No impact, MT = Medium Term, LT = Long Term; LO = Low, MO = Moderate, H = High

Impact Weightage Criteria, National EIA Guidelines (1993)

TABLE 28 Impact weightage criteria, national eia guidelines (1993)

Magnitude		Extent		Duration	
High (H)	60	Regional (R)	60	Long Term (LT)	20
Moderate (Mo)	20	Local (L)	20	Medium Term (MT)	10
Low (Lo)	10	Site Specific (S)	10	Short Term (ST)	5

Using this system, the maximum score is 140 points and the minimum 25

Significance of Impact

Total Score: Upto 44: Insignificant 45-74: Significant

Greater than 75: Very Significant

6. ENVIRONMENTAL AND SOCIAL IMPACT MITIGATION

This section of the report has prescribed the practical and cost-effective mitigation measures to avoid, minimize and compensate the effects of adverse impacts to acceptable level. The project proponent ensures to implement these measures during the construction and operation of the project.

6.1 Mitigation Measures

In order to reduce or prevent the likely environmental impacts identified in previous section, Table 5-1 presents prescribed environmental mitigation measures and their estimated mitigation costs.

Table 29 Mitigating Measures

S.N	Environmental Impacts		Mitigation Measures	Time of Action	Mitigation Cost (NRs.)	Responsibility
A. Co						
A.1 Ph	ysical Environment					
A.1.1	Change in land use	•	Minimum land disturbance will be made while sub-project construction. Greenery will be maintained	During Construction Phase	20,000.00	Sub-project Developer
A.1.2	Emission of dust, smoke, CO ₂ and other harmful gases through vehicular movement, excavation and related construction activities	•	All vehicles and machineries used in construction work shall be in compliance with emission standard set for vehicles and machineries by MoFE Regular maintenance of vehicles and machineries Regular spray of water in the construction site and access road Cover stockpiled construction materials with tarpaulin	During Construction Phase		Sub-project Developer/Contractor
A.1.3	Pollution of groundwater through percolation of wash water from construction materials, spillage of lubricants	•	Mixing and washing of aggregates should be done in designated area or Temporary construction of silt trap or sedimentation tank to collect washed off of aggregates. Storage of spent oil and greases in containers and its safe disposal	During Construction phase	-	Sub-project Developer/Contractor

		Provision of proper drainage system			
	Formation of muddy ditches during rainy season	 Provision of proper drainage system Using construction spoils to fill up low land area, ditches and land development work 	During Construction phase	-	
A.1.4	Degradation in soil fertility due to haphazard disposal of construction spoils, stockpiles and spillage of lubricants	 Stockpiling the materials in designated place within the construction site Storage of spent oil ,lubricant and greases in containers and its safe disposal Using construction spoils to fill up low land area, ditches and land development work 	During Construction Phase		Sub-project Developer/Contractor
A.1.5	Increase in noise from operation of machineries, excavation and vehicular activities	 Provision of low sound emitting machineries Regular maintenance of vehicles and machines Prohibition of construction activities in night time and early morning 	During Construction Phase	-	Sub-project Developer/Contractor

A.1.6	 Degradation in aesthetic beauty Percolation of wash water from construction material into agricultural land and groundwater Formation of muddy ditches during rainy season 	materials and spoil in designated area within construction site Compaction of spoil Covering of stockpiles to avoid washout during rainy season Provision of appropriate drainage to avoid muddy surface formation	During Construction phase		Sub-project Developer/Contractor
A.1.7	Traffic congestion on road while transporting construction materials	 Avoid transporting construction material during rush hour Avoid stockpiling of construction materials in access road. Prepare Traffic Management Plan 	During Construction phase		Sub-project Developer/Contractor
A.2 Bi	ological Environment				
A.2.1	Vegetation Loss	No vegetation will be removed.	-	-	-
A.3 So	cio-economic Environment	,			
A.3.1	 Exposure to fugitive emission, noise and risk of physical injury 	Provision of personnel protective equipment (PPE) like helmets, masks, safety jacket, gloves, safety boots and safety harness to construction workers	During Construction Phase	Included in construction cost	Sub-project Developer/Contractor

		 Provision of first aid kits Adequate lighting and safety signal devices be installed for work safety. Adequate warning signs and safety barriers will be provided for work safety Prepare Occupational Health and Safety Plan and Emergency Preparedness and Response Plan, maintain social distancing, and follow guidelines of Nepal Government considering challenges posed by communicable disease to control possible spread of diseases among the construction workers and between the workers and host community. 			
A.3.2	 Injuries to workers while handling machineries Community children caught in accidents Transmission of communicable diseases 	 Provision of PPE and Safety Aid boxes Provision of well barricade wall in construction site Provision of security personnel Emergency preparedness plan, Occupational Health and Safety Plan considering disease of highly contagious nature 	During construction phase	50,000.00	Sub-project Developer/Contractor

Community Health and Safety
Plan (Prepared by trained staff
appointed by proponent)
Provision of community health
and safety plan
Rehabilitation of existing
infrastructures (roads, public
and private properties) if
affected by subproject related
activities
The subproject site will be
barricaded to avoid the
trespass of unauthorized
person in subproject site
Sprinkle the water on the
road that passes through
community to control the
dust while transporting
material to the subproject site
Awareness and orientation to
construction workers to respect
locals
Provision of reporting
mechanism if any incidents
occurs

Make restriction of entry of children in construction area Construction workers will be trained in job hazards, emergency procedures and in

		any other relevant safety measures.			
A.3.4	Conflict and grievances: There is no land acquisition issues since the poultry has its own land but due to flies and vector borne diseases and foul smell in the project site, it has to be dealt with little bit sensitively with locals to avoid the situation.	 Grievance redress Committee (GRC) at subproject level will be established Management of record keeping system of the grievance received at field level Suggestion box will be place at the entrance of subproject premises to receive the suggestions and complaints from community people. Appoint ESS Focal Prson for handling grievances under Grievance Redress Mechanism Periodic consultations with locals to provide them project updates and make them aware of benefits of biogas plants as a supportive role in removing the poultry waste and foul smell efficiently. Instruct construction company to proceed construction work in compliance to ESIA report Establish subproject specific Grievance Redress Mechanism 	During Construction Phase and operation Phase	NRs. 100,000	Sub-project Developer

	Impact associated with gender and SEA/SH • Contractors, project employee and the workforce could discriminate against women and vulnerable groups • The contractor could pay differently to the male and female worker for the same work • The exploitation of children in the construction work	 Code of Conduct (CoC) including SEA/SH for subproject staff will be implemented Appoint SEA/SH Focal person for handling grievances related to SEA/SH Orientation of SEA/SH and gender based violence to the staff and workers of sub pojects The use of child labour in subproject construction will be strongly prohibited (Record keeping of labour with identity card showing age will be maintained) Both women and men and people of excluded groups will be given equal opportunity for employment and no gender discrimination will be done in terms of wages for the same or similar works. 			
	Operation Phase				
	1 Physical Environment		1		
B.1.1	 Contamination of land and water sources Leaching of raw feedstock into groundwater during rainy season due to improper storage system 	Avoid direct discharge of slurry and decanted liquid waste into nearby water bodies and agricultural field	During Post Construction/ Operation Phase	Included in project cost	Sub-project Developer

	Alter in water quality parameter	 Storing the raw materials in roofed unit with impermeable base Provision of decantation unit with sealing of base for settling solid and liquid slurry and use of slurry to make compost 			
B.1.2	Increase in flies and vector disease due to improper storage system of feedstock poultry waste and haphazard disposal of post digestate	 Storing of feedstock(OW) and post digestate in designated area Covering of feedstock and post digestate Regular cleaning around the decantation unit and feedstock storage area 	During operation phase	50,000.00	Sub-project Developer
B.1.3	 Methane gas being highly flammable can cause fire hazard; loss of property and life Contribution of GHG emission 	 Avoid naked flame near the plant Provision of good and reliable fire extinguisher and emergency fire-fighting water storage Designation of assembly location for workers in case of occurrence of firing Regular checking of leakage in plant 	During Operation Phase	150,000.00	Sub-project Developer
B.1.4	 Percolation of wash-off water of organic feedstock and post digestate into groundwater and nearby rivers 	 Provision of proper storm water drainage channel Storing post digestate and feedstock in designated area 	During Operation Phase	-	Sub-project Developer

B.1.5	•	Alter in water quality parameter Increase in BOD, turbidity and TS of nearby water body if discharged directly into it Groundwater pollution	 Provision of proper drainage system Prohibition of direct disposal into nearby agricultural field and water body 	During Operation Phase	-	Sub-project Developer
B.1.6	•	Foul smell along the transportation route Possibility of dropping the waste on road Vehicular emission	 Proper covering of feedstock while transporting Proper compaction of feedstock to avoid dropping Use of vehicles complying Vehicle Mass Emission Standard, 2069 	During Operation Phase	100,000.00	Sub-project Developer
B.1.3	•	Excessive use of underground could lower the water table and could cause impact on availability of water in the locality that depends on underground water.	Extraction of groundwater as required quantity only. If required, extraction permit shall be collected from municipality.	During operation phase	-	Sub-project Developer
B. 2 B.2.1	•	Biological Environment Maintenance and protection of greenery in the sub- project periphery	 Avoid throwing of waste generated by the workers in vegetated land. A strict rule for workforce not to degrade nearby greenery. 	During operation phase	Operation costs, gardening and cleaning workforce would be hired.	Sub-project Developer

		Maintenance of garden in the					
		subproject area.					
B. 3		mic and Cultural Environment					
B.3.1	Physical injury to staff Prone to catch disease due to handling of organic waste and highly contagious diseases. It is a solution of the contagion of the con	 Workers shall be provided with personal protective equipment (PPE) like helmet, safety boots, safety jacket, gloves and masks Provision of First Aid Kit Staffs shall undergo a regular medical checkup and should be administered necessary vaccines, such as prescribed by a medical doctor Proper orientation and training should be provided to the staff on safety so that accidents and disease can be avoided Provision of necessary safety cautions, signposts and instructions at construction site as well as near moving machineries Prepare Occupational Health and Safety Plan and Emergency Preparedness and Response Plan, considering the highly contagious diseases and orient workers on responsible behavior amid the crisis. 	Phase	100,000.00	Sub-project Developer		

		 Provision of proper record of labor, well maintained registration sheet with personal details as well as emergency contact details (native and migrant worker) 			
B.3.2	 Spread of vector borne disease around the community and staffs due to improper management of organic waste Opposition from community against the project 	 Keeping the unit areas clean with disinfectants Avoid haphazard disposal of digestate Awareness and training to staffs regarding sanitation and operation of plant Prepare Community Health and Safety Plan with focus on communicable disease 	During Operation Phase	-	Sub-project Developer
B.3.3	• Conflict and grievances: Though there won't be any land acquisition issues but flies and vector borne diseases and foul smell during operation of biogas may lead to conflict which needs to be dealt with little bit sensitively with locals. But only two HHs are present in the 100 m vicinity.	 Arrangement of handling grievances from community and proceed immediate action thereof, if any. Regular consultations with locals and some awareness program to nearby villagers and awareness on benefits of biogas plants. Instruct construction company to proceed construction work in compliance to ESA report Employment opportunities to the locals. 	During Construction Phase and operation Phase		Sub-project Developer

		 Provision of periodic consultation with the nearest community and concerned stakeholders 			
B.3.4	Grievances regarding aesthetics, odor, water and noise pollution from local residents resulting opposition and conflict	 Implement mitigation measures to avoid potential impacts mentioned in B.1, B.2 and B.3 Establish Grievance Redress Mechanism (GRM) Arrangement of handling grievances from community and proceed immediate action through Grievance Redress Mechanism Meeting with locals and awareness program to the nearby settlement regarding the nature of the project Employment opportunities to the locals 	During Operation Phase	150,000.00	Sub-project Developer

7. STAKEHOLDER CONSULTATION, COMMUNITY PARTICIPATION AND DISCLOSURE

7.1 Public Consultation

Public Consultations with regard to the sub-project development and operation was accomplished in different forums during the field survey. The relevant issues raised by the locals and concerned stakeholders in such forum was considered in these study.

A stakeholder consultation meeting including government officials and ESA team was carried out on 23th of Falgun 2080 (7th March, 2024) at ward office of Ward no. 3 of Jagarnathpur Rural Municipality in presence of Chairman of the ward- Nagina Raut Ahir, officias of Shivan Jaivik Khad tatha Urja Pvt. Ltd, ward members, environment officer and representative of Innovative and Sustainable Technology Solution (ISTS) Pvt. Ltd. During the meeting, a brief discussion was carried out on construction and operation of biogas plant at Shivan Jaivik Khad tatha Urja Pvt. Ltd. The factors like physical, biological, social impacts and their mitigation measures were discussed briefly. ESA team also met with some local people and consulted with them at the project location.

Major agendas of the meeting were:

- 1. Information about biogas and the construction of plant
- 2. Collection of thoughts and suggestions from the stakeholder
- 3. Miscellaneous

Decisions made during the meeting regarding above-mentioned agendas were:

- 1. The representative of ISTS Pvt. Ltd. informed about the biogas plant to be constructed at Shivan Jaivik Khad tatha Urja Pvt. Ltd of Ward-3 of Jagarnathpur Rural Municipality under Commercial project. He also briefed about the importance of biogas plant and its uses.
- 2. Following suggestions were received from the stakeholders for Environmental and Social Assessment (ESA):
 - i) It's good to start a biogas plant in the local area. The employment opportunities for the construction and operation of such plant must be given to the local people if the locals have the required skills and capabilities.
 - ii) During any phase (construction/operation), there should not be any impacts on the environment. If impacts are seen then they should be minimized.
 - iii) During the construction and operation of the biogas plant, if any kind of pollution or foul smell is observed, the poultry itself should be responsible for minimizing the impacts.
 - iv) The compost produced after the operation of the biogas plant must be made available to the local people in subsidized rate.
 - v) Since biogas plant is useful in minimizing the pollution and is beneficial for the environment, other poultry farms and industries must also consider constructing biogas plants.
 - vi) During the construction and operation of the plant, safety and health must be considered.

- 3. Since the construction and operation of biogas plant at Shivan Jaivik Khad tatha Urja Pvt. Ltd., it seems beneficial in minimizing the environmental impacts, all the stakeholders attending the meeting decided and agreed to help in the construction and operation of the biogas plant.
 - During meeting, the issues raised by the public during the consultation meeting were noted, collected and incorporated in report and adequately addressed in mitigation measures. They were consulted for large biogas project in Jagarnathpur Rural Municipality and discussed about different aspects of biogas and environmental aspects. Meeting minute of public consultation is attached in Annex A-3. In the meeting it was agreed to install the large biogas at the land provided by the rural municipality and it was also agreed by company to give the job opportunity preference to them during large biogas installation and similarly, to provide fertilizer produced from the slurry to the local community in subsidized amount. It is also prescribed to establish grievance handling committee where locals can raise and register their grievances, if any, during the construction and operation phase of the project. Such grievances will be forwarded to grievance redress committee at first then to proponent or project management unit, if not resolved.

8. ALTERNATIVE ANALYSIS

In order to ensure the subproject as an environmentally sound, alternative analysis was carried out to choose better alternative from the environmental perspective and without compromising the process flow or production. The aim of alternative analysis is to arrive at a development option, which maximizes the benefits while minimizing the unwanted impacts. While exercising the alternative analysis, the following aspects were taken into account.

8.1 No Project Option

No action option for the proposed project implies non implementation of the proposed extension of subproject as an alternative to LPG gas. The large biogas project is supposed to reduce the large municipal waste (65 TPD) into usable biogas 2100m³ per day. The efficient use of waste will be beneficial situation for the proponent and in addition that also directly help in conserving environment through risk of leaching, reduce risk of flies and vectors borne diseases, reduce foul smell and protect aesthetic value. Hence, no action option is rejected.

8.2 Design Alternative/Technology

There are several anaerobic digestion technologies to generate biogas from anaerobic digestion. Modified GGC is the native anaerobic digestion technology promoted in Nepal. While, in this project, high efficient CSTR technology with heating is adopted for higher energy yield. Due to prior successfully tested and commissioned of biomethanation plant, the same technology has been proposed.

8.3 Alternative Resource

The construction materials will be sourced from Nepalese market by competitive bidding process. The project machineries will be imported from India. During operation phase, raw materials are chosen in order to assure the quality aspects as well as economically viable. All the raw materials used will be sourced from the internal market as far as possible.

8.4 Alternative Project Site

The project site's land is owned by the proponent. The proposed land lies in the flat region, so, this region is suitable for the proposed design of the plant. Similarly, the area is very near from the highway. In the context of the transportation, both roadways and airways within the reach of the area. Hence, alternative project site is not required.

8.5 Alternative Time-schedule

The project will be accomplished in day time as the local residents will be affected from sound pollution during the night. For the use of machineries, time schedule from 9am in the morning to 5pm in the evening has been proposed

9. ENVIRONMENTAL MONITORING

9.1 Project Management Responsibility

The implementation of mitigation measures responsibility is entrusted to the project proponent. Because of small nature of project, the monitoring of environmental parameters in the construction and operation period should also be done by the proponent.

9.2 Environmental Standards

The GoN has endorsed few environmental standards on air, water and noise quality. These environmental standards shall be treated as other acts and regulations until GoN enforces standards in the specified sector for the project environmental compliance propose. Considering this, the environmental standards are proposed for proposed subproject construction and operation for compliance which is attached in Annex A-7.

9.3 Environmental Monitoring Plan

The environmental monitoring plan designed for the project has three main objectives;

- To ensure that the subproject baseline conditions were adequately documented such that a comparative assessment of the project baseline before and after the project could be made objectively for impact evaluation
- To ensure that the mitigation commitments to minimize the predicted adverse impacts and maximize the beneficial impacts including the environmental enhancement programs were actually complied and implemented in time and with sincerity by the subproject.
- To verify that the subproject impacts were within the limits of the impact prediction or some unforeseen impacts also occurred during project development and what measures were taken to minimize the unforeseen impacts

As baseline environment of the proposal development area is known and also documented in this report, the proponent itself will carry out compliance and impact monitoring of the sub-project construction and operation sub-period. In addition, to ensure the effective implementation of ESMP, the environmental and social safeguard compliance monitoring will be conducted by the safeguards staffs (E&S) of AEPC/MGEAP will be responsible to carry out monitoring during different stages of the subproject cycle i.e., construction and operation phases. The ESCO will be responsible to prepare monthly progress report and submit it to the AEPC/MGEAP and AEPC will be responsible to prepare quarterly monitoring reports and submit it to the World Bank. The monitoring management plan for baseline, compliance and impact is presented in Table below.

Table 30 Baseline monitoring, construction and operation phase

S.N	Provisions of compliance	Individuals responsible	Methods	Frequency /Time	Monitoring authority	Place	Financial commitment (NRs.)			
Prior (Prior Construction Phase									
1	Groundwater quality testing of nearby River	Proponent	Laboratory Analysis	Prior to construction period	AEPC	Sub-project Site	15,000.00			
2	Air Quality (TSP, PM 2.5, PM 10, Methane fraction)	Proponent	Low Volume Sampler, Gas Analyzer	Prior to construction phase	AEPC	Sub-project Site	75,000.00			
3	Noise level monitoring of project location	Proponent	Noise level Meter	Prior to construction period	AEPC	Sub-project Site	10,000.00			

Table 31 Compliance monitoring, construction and operation phase

S.N.	Provisions of compliance	Individuals responsible	Methods	Frequency /Time	Monitoring authority	Place	Financial commitment (NRs.)			
Const	Construction Phase									
1	Vehicular emission in compliance	Proponent	Site Observation/	throughout	Proponent	Sub-project	-			
	with standard set for vehicles and		records	the	_	Site				
	machineries by MoFE			construction						
	Regular maintenance of vehicles			period						
	and machineries									

	Regular spray of water in construction site						
	Storing of spent oil and greases in containers and designated place	Proponent	Site Observation/ records	During construction period	Proponent	Project Site	-
	 Stockpiling of construction materials in designated place within construction site Provision of drainage Using of construction spoils to fill up low land area and ditches 	Proponent	Site Observation/ records	During construction period	Proponent	Project Site	-
2	 Provision of low sound emitting machineries Regular maintenance of vehicles and machines Prohibition of construction activities in nighttime and early morning 	Proponent	Site Observation/ records	During construction period	Proponent	Project Site and nearby community	-
3	 Stockpiling of construction materials and spoil in designated area within construction site Compaction of spoil Covering of stockpiles to avoid washout water during rainy season Provision of appropriate drainage to avoid muddy surface formation 	Proponent	Site observation and records	During construction period	proponent	Project site	20,000.00
4	Provision of personnel protective equipment (PPE) like helmet,	Proponent	Site Observation/ consultation	During construction period	Proponent	Project Site	50,000.00

	safety boots, safety jacket, gloves and masks Provision of First Aid Kit Staffs shall undergo a regular medical checkup and should be administered necessary vaccines, such as prescribed by a medical doctor Prepare Occupational Health and Safety Plan and Emergency Preparedness and Response Plan, considering the highly contagious diseases and orient workers on responsible behavior amid the crisis. Provision of proper record of labor, well maintained registration sheet with personal details as well as emergency contact details (native and migrant worker)						
5	 Awareness and orientation to construction workers Provision of barricade Provision of necessary safety cautions, signposts and instructions at construction site as well as near moving machineries 	Proponent	Site Observation/ records	During construction period	Proponent	Project Site	50,000.00

 Proper orientation and training should be provided to the staff on safety so that accidents and disease can be avoided 						
Establishment of GRC at subproject level and Record book for registration of grievances at subproject level Implement Grievance Redress Mechanism Appoint a staff for handling grievances Meetings with locals and some awareness program to nearby villagers and awareness on benefits of biogas plants to manage poultry waste efficiently. Instruct construction company to proceed construction work in compliance to ESA report Placement of suggestion boxes Period consultation with	Proponent/ Rural Municipality	Site Observation/Records Meetings/ awareness program	During Construction Period	Proponent/ Rural Municipality	Project Site	50,000.00
relevant stakeholders						

1	 Avoiding direct discharge of slurry and decanted liquid to nearby water bodies Storage of raw materials in 	Proponent	Site Observation	Before Operation Phase	Proponent	Project Site	-
	roofed unit with impermeable base • Provision of decantation unit with proper seal of base						
2	 Proper covering of feedstock while transporting Proper compaction of feedstock to avoid dropping Vehicular emission in compliance with emission standards 	Rural Municipality	Photographs/ Records	Monthly inspection during Operation Phase	Proponent/ Rural Municipality	Project Site	
3	 Storage of feedstock and post digestate on designated area Covering of feedstock and post-digestate Regular cleaning around the decantation unit and feedstock storage area Sprinkle the road to avoid dust during the trasportation 	Proponent	Observation	Before Operation Phase	Proponent	Project Site	50,000.00
4	 Avoidance of naked flame near plant Provision of fire extinguisher Scheduled maintenance and testing of gas leakage in plant 	Proponent	Observation/ Discussion/Record	Before Operation Phase	Proponent	Project Site	20,000.00

5	 Provision of proper storm water discharge channel Storing of post digested and feedstock in designated place 	Proponent	Site observation	During operation phase	Proponent	Project site	
6	 Provision of personal protective equipment to workers Provision of first aid kit Regular check-up of staffs Proper training to staffs about operating plant and waste handling Provision of labor registration log with their personal details as well as emergency contact details 	Proponent	Observation	During construction Phase	Proponent	Project Site	50,000.00
7	 Cleaning the plant area regularly Avoidance of haphazard disposal of digested Awareness and training to staffs regarding sanitation and operation plant 	Proponent	Observation/ Discussion/Record	During Operation Phase	Proponent	Project Site	20,000.00
8	Implement Grievance Redress Mechanism Arrangement of handling grievances from community and proceed immediate action thereof, if any.	Proponent/ Rural Municipality	Observation/Record/ Discussion with locals	During operation phase	Proponent/ Rural Municipality	Project site	

Regular consultations with locals			
and some awareness program to			
nearby villagers and awareness on			
benefits of biogas plants to manage			
poultry waste efficiently.			
Instruct construction company to			
proceed construction work in			
compliance to ESA report			
Employment opportunities to the			
locals.			

Table32 Impact monitoring, construction and operation phase

S.N.	Monitoring Indicator	Individuals responsible	Methods	Frequency /Time	Monitoring authority	Place	Financial commitment (NRs.)
Cons	truction Phase						
1	Effect on productivity of nearby farmland due to construction waste and percolated water	Proponent	Discussion with local people, visual observation	twice during construction period	Proponent	Nearby farmland	-
2	Increased Noise level	Proponent	Discussion with local people, noise level meter	once during peak construction work	Proponent	Nearby settlement	-
Oper	ration Phase						
1	Aesthetic degradation due to haphazard disposal of organic slurry in nearby water bodies and area	Proponent	Discussion with local people	Twicein a year	Proponent	Nearby settlement/f arm land	-
2	Occupational Health and Safety of the staffs/workers	Proponent	Clinical checkup/ Records/interv iew with staffs/workers	Once in a month	Proponent	Project Site	-
3	Number of grievances received from community	Proponent	Registered file/complains	Every Month	Proponent/ Municipality	Nearby community	-
4	Water Quality	Proponent	Water quality tests of source of water supply	Once during operation period			

			(borewell				
			water)				
5	Air quality	Proponent	Visual	Once during			
			inspection	operation			
				period			
6	Increased noise level	Proponent	Discussion	Once during	Proponent	Project site/	-
			with local	operation		Nearby	
			people, noise	period		Community	
			level meter				
7	Methane Leakage	Proponent	Gas Analyzer	Twice in a	Proponent	Project site	-
	-		_	year	_	-	

Table 33Summary of Environmental Monitoring Cost

Item	Quantity	Rate per month	Rate per year (NRs)	Total (NRs)
Construction Phase				
Water Quality Monitoring	-	-	30,000 (Once)	30,000.00
Noise Monitoring	-	-	10,000.00	10,000.00
Operation Phase				
Water Quality Monitoring	-	-	15,000.00 (annual)	15,000.00
Noise Monitoring	-	-	10,000.00 (annual)	10,000.00
Methane Leakage	-	-	15,000.00 (annual)	15,000.00
Human Resource				

Environment and Social	1	60,000	120,000 (Two month input in	120,000.00
Officer (ESS Focal Person)			each year)	
Total				200,000.00

10. INSTITUTIONAL ARRANGEMENT AND GRIEVANCE REDRESS MECHANISM

10.1 Project Environmental Management Plan Structure and Stakeholders Responsibility

The Project Environmental Management Framework of the proposed project is prepared to show linkages with different parties to be involved directly or indirectly during the different phases of project development and operation in compliance with the existing Act and Rules.

Overall project environmental and social management is the responsibility of **Proponent** of the proposed subproject. Key stakeholders to be involved for project environmental and social management in the hierarchy order are:

- Alternative Energy Promotion Center (AEPC)/World Bank (WB)/ SREP
- Monitoring Unit of AEPC
- Proponent (through Project Management Unit PMU)
- Construction Contractor (CC)Representative from Subproject Affected Rural Municipality (SPARMR)




Figure 8 PEM Framework

10.2 Grievance Redress Mechanism

Grievance addressing and feedback is important so as to know what negative impact has been occurred in the community due to the implementation of the project. Such grievances should be taken care in order to avoid conflicts in the society regarding the project. Grievance readdress not only prevents conflicts but will also help the developer to take necessary steps to further improve the plant operation and management system.

As the project location is within the landfill site that is already related with public fear of degradation of their economic land value, flies and vector borne diseases and foul smell. Hence, grievances from the community and nearby inhabitants should be dealt with little bit sensitively to avoid conflict and to ensure smooth running of the project. In case, if any grievances arose, those complains will be assessed by the current Grievance Redress Committee (GRC).

Grievance Redress Mechanism Process

The figure below describes the process that will be used to resolve any grievances related to this project:




Figure 9 GRM framework

The management team of GRC is listed below:

A. Sub-Project Level Grievance Redress Committee (GRC)

- 1. Chairperson/Representative of the ward office/ of respective Municipality and Ward
- 2. Representative from Project Affected People– Member (2)
- 3. Representative from local NGO/CBO Member (1)
- 4. ESS focal person of the perspective developer/Project manager Member Secretary
- 5. Sexual Exploitation Abuse and Sexual Harassment (SEA/SH) Focal Person-Female member Note: To be ensured that at least one member of the GRC should be female/vulnerable group (Representatives of developers/CSOs/PAP).

The central monitoring may be done by AEPC during the operation phase at any time of the sub-project cycle.

The grievance redress mechanism will be assessed as described below:

- ESS focal person of the developer/Project Manager/Site In-charge will be appointed as the focal person (Member Secretary of project Level GRC) to receive/handle any kind of grievance related to the project. His/her name and contact number will be displayed at the entrance of the project site, so that affected people can have direct access to him/her.
- SEA/SH Focal Person will be female representative from developers/CSOs/PAP of GRC formed at subproject level and she will be responsible to record and handle any kind of grievances related SEA/SH.
- A register will be maintained including the name of grievant, date and time of grievance recorded, issue raised and time frame to redress the received grievance. (format presented in Annex A-6). The register will provide information on how the grievance was resolved.
- A suggestion box will be place at the entrance of the project site as well as in project site premises to collect grievances from employees.
- Grievances can be registered via website: http://www.aepc.gov.np/gform/gform.php
- If the project level GRC will not be able to redress the grievance, it will be forwarded to the national level GRC.
- Grievances received have to be resolved within 3 weeks of receipt of complaint.
- Affected persons have the option of accessing the court of law in case of dissatisfaction with the decision of the GRC.

10.3 Capacity Development and Enhancement Measures

During the construction period, the job priorities will be given to local people with equal opportunities to women as well. The skill development training such as unskilled construction works, scaffolding, casting etc. will be given to the workers so that they are able to use the learned skills in other similar projects and earn their living. The project will require 10 additional skilled and semiskilled workers during operation phase. The priority shall be given to locals for skilled job, if they have required skill and qualifications.

Enhancement Measures: There are no households within 100 m of project location. Gadhaiya villages with around 79 households lies in indirect impact zone i.e. within 500 m. Thus, the following enhancement measures have been proposed to ensure that the project fully respects the dignity, human rights, economies, values and cultures of vulnerable groups, especially women and girls and the IPs.

- Prior to the construction of the project, the representatives of HHs will be consulted to address all the sensitive issues.
- Skill development training such as, driving, mechanics, plumbing, electrician etc. and/or income generation training such as poultry farming, piggery will be offered.
- Priority will be given to the needy families for job opportunities.
- Prior to the project, the people will be consulted if they have any special requirement/demands.

11. COMPANY'S ENVIRONMENTAL HEALTH AND SAFETY PLAN

11.1 Health and Safety Plan

To provide a safe working environment to in-house staffs, visitors and the surrounding settlements, it is very necessary to be fully aware of the safety requirements to avoid accidents from the implementation of biogas plant. These provisions are prepared based on mitigation measures suggested against probable impacts. This plan will be prepared by developer. The following issues are identified and brief safety plans are provided as follow:

a. General House Keeping

- Workers should be given orientation about the safety/emergency preparedness plan during construction and operation phase.
- Security should inform the concerned staff when visitors arrive. The designated staff should guide the visitor.
- Every person who enters the biogas plant premises should display a valid identification card.
- The sub-project area should be regularly cleaned and ensure that all the floors are free from oil spillage and other harmful substances that are flammable.
- No pipe line, power cable shall run across the path ways causing a tripping hazard.

b. Fire Hazard

- Provision of alarm to notify the fire disaster.
- Provision of fire extinguisher, fire hydrant and first aid kit.
- Update contact number of fire brigade and ambulance for accidental cases.

c. Vandalism

- Appointing a day and night security guard.
- Provision of physical and technological barriers such as fences, gates, ID card access.
- Ensure lighting of the premises during nighttime.

d. Leakage Detection

- Regular Monitoring of the gas leakage
- Provide training to handle gas leakage
- Odor

e. Infectious Disease Outbreak

- Effective Vector Control Measures such as regular cleaning in the sub-project site
- Using gloves, masks and other safety equipment while handling organic materials and feedstock.
- Food and Water Safety measures to follow within the project premises.
- In case of an outbreak immediately report to the nearest health authority.

f. Occupational Health and Safety Plan

- Provision of safety equipment such as gloves, masks, safety boots, safety jacket, harness during construction and operation phase.
- Adaptation of directives and guidelines issued by the government and WHO in relation to limiting the spread contagious diseases.
- Provision related to making workers aware of contagious diseases .pandemic and orient them in adopting precautionary measures such as wearing facemask, maintaining social distance, regular hand washing, among other
- Awareness about potential health impacts while handling organic matters to staff.

11.2 Emergency Preparedness Plan

The Emergency Preparedness Plan is prepared in order to take immediate action to minimize the loss. The following section gives protective measures to follow incase hazardous events occur in the sub-project site.

a. During Catastrophe

- Provision of sensor/ alarm to notify the disaster
- Awareness and orientation program with the workers during construction and operation stage in regular basis to discuss about the possible disaster and its evacuation method
- Allocating emergency exit
- Designation of emergency assembly area for evacuation

b. Malfunction of the System

- Regular maintenance of the equipment
- Proper segregation of waste before feeding to inlet
- Employing skilled technicians to operate the plant
- Regular orientation, instruction and guidance to staffs about plant operation

c. Leakage and burst

- Provision of fire alarm, extinguisher and sprinklers
- Project insurance to cover the cost of loss from the event
- Proper orientation and training to staff to operate the plant
- Preparation of emergency exit map and orienting the staffs about it
- Orienting staffs to follow proper safety measures during construction and operation phase.
- Provision of First Aid Kit.
- Regular check-up of staffs during operation phase.
- Maintain registration log of both native and migrant worker with their detail i.e.; name address, nationality, contact number, emergency contact person and their respective numbers, etc.

• Follow Occupation Health and Safety Plan of AEPC during construction period in order to minimizing and managing the risk of spread of communicable disease.

11.3 Gender Action Plan

- Job priority will be based on the qualification irrespective of the gender.
- Ensure female worker's security at work place.
- Provide equal wage to female workers as male workers.
- Special effort will be made to get feedback from women and girls during project cycle.

11.4 Substrate Handling and Slurry Management Plan

- The base, side walls of decanter and storage lagoon will be made waterproof to avoid leaching.
- Regular cleaning of the facility will be done to prevent flies and safety of workers.
- The solid slurry separated from decanter will be dried and sold in the market.
- The liquid will be reused as dilution water in the digester. Remaining liquid slurry will be sold as manure.

11.5 Labor Management Plan

Labor Management Plan describes the requirements for the proposed subproject with regards to labor and working conditions during construction. It aims to ensure the management and control of activities that may pose labor-related risks. Following measures shall be taken by developers to manage labor during construction

- Promote fair and equitable labor practices for the fair treatment, non-discrimination and equal opportunity of workers
- Make sure that there is no child and forced labor during construction and operation phases
- Establish, manage and promote a healthy management-worker relationship
- Protect workers' rights including migrant and third-party workers
- Promote healthy, safe, secure and comfortable accommodation that does not impact negatively on the communities in the surrounding area

12. Conclusion

Shivam Jaivik Khad Tatha Urja Pvt. Ltd. Will be executing this project under Scaling Renewable Energy Program (SREP) by Alternative Energy Promotion Center (AEPC), using a Continuous Stirred-Tank Reactor (CSTR) with a capacity of 5000 m3, producing 1120 m3/Kg (of refined bio CNG gas which gas which can be stored in cylinder and sold and distributed to hotels and industries and slurry will be converted to fertilizer and will be supplied to the nearby communities in a subsidized rates.

The project is conducted at Jagarnathpur rural municipality, Parsa. Prior to the commencement of the project, Environment Assessment Study was carried out considering physical, biological and socio-economic aspect. Different impacts were identified during the study. Both beneficial and adverse impact were taken in to account while carrying out the study. The identified impacts can be mitigated by adopting prescribed mitigation measures in this report. By adopting additional mitigation measures stipulated in this ESIA, the project will have very less negative implications on environment. Compliance measures, environmental monitoring plan, institutional arrangement for grievance management mechanism and occupational health safety measures were also stated in the report.

Impacts during the implementation of the project has been foreseen by the ESIA report. The report and also suggested mitigation measures to minimize or reduce the impacts. The proponent of the project should strictly follow the mitigation measures as prescribed out in this report and if any impacts, not mentioned in this study, if perceived during construction as well as operation phase, shall also be mitigated with proper mitigation measures. The biogas plant is going to be installed at the location area in order to reduce or manage the large organic waste from poultry, cattle farm, sugar industry with capacity of 60 TPD with the aim of generating revenue from waste by producing gas and accessible slurry for use in agriculture fields. It is supposed to minimize the risk of flies and vector-borne disease, as well as waste flooding during the rainy season and foul odor after waste decomposition. Apart from that, if all mitigating steps and compliance monitoring are followed, it is relatively safe and secure. As a result, the project is extremely feasible and can be implemented at the project site.

13. ANNEXES

Annex A-1: Company Registration Certificate



Figure 10 Company registration of proponent




Figure 11 PAN application

Annex A-2: Environmental and Social Screening Checklist

Table34 Environmental and social screening checklist

	Construction phase Operational phase					1 1	
Potential impact		1		Operational phase			
area	Adverse	No	Beneficial	Adverse	No	Beneficial	
	effect	effect	effect	effect	effect	effect	
A D1. 1							
A. Physical							
condition							
Soil type							
Erosion							
Ground cover							
Deposition (
sedimentation,							
precipitation)							
Slides stability							
Stress-strain							
(earthquakes)							
Floods							
waste control							
Operational failure							
B. Land Use							
Open space							
Recreational							
Agricultural							
Residential							
Commercial							
Industrial							
C. Water							
resources							
Quality							
Irrigation							
Drainage							
Ground water							
D A . 114							
D. Air quality							
Oxides (sulphur,							
carbon, nitrogen,							
methane)							

Particulate matters			
Chemicals			
Odors			
Gases			
E. Public			
service			
systems			
Schools			
Police			
Fire protection			
Water and power			
system			
Sewerage system			
Refuse disposal			
F. Biological			
conditions			
Wildlife			
Trees, shrubs			
NTFPs			
C Transportati			
G. Transportati			
on systems Automobiles			
Trucking Safety			
Movement			
MIOVEINEIL			
H. Noise and			
vibration			
On-site			
Off-site			
I. Aesthetic		 	
Scenery			
Structures			
J. Community			
structures			
Relocation			
Mobility			
Services			

Recreation						
Employment						
Housing quality						
Name of Beneficiary VDCs and its population						
K. Other						

Questionnaire for interview, interaction and discussion

1.	In your view; what are the major adverse environmental impacts in Physical, Biological and Socio-economic and cultural aspects with the construction and operation of large biogas?
2.	What could be the major beneficial impacts with the implementation of the project for Biogas?
3.	In your view, what should be done to mitigate the adverse environmental impacts that you have mentioned?
4.	Are there any other likely impacts with its implementation?
5.	Do you have any suggestions to safeguard social and environmental condition of the project area with its implementation and operation?
6.	Is there any possibility of generation of employment opportunities with the construction and operation of biogas?

SOCIAL SCREENING CHECKLIST

1. Title of the Sub project: Commercial () Project through Anaerobic Digestion (Biogas)								
Technology in Shivam Javik Khad tatha Urja Pvt. Ltd								
1.1 Site Locality: Jagarnathpur-03,	Parsa							
1.2 Sub project activities: Construc	tion of biogas digester							
1.3 Contact Details: Jagarnathpur,	Parsa, Nepal							
2. Impact on specific assets due to project intervention								
2.1 What are the asset(s) that	☑ Land							
would be affected due to	☐ Physical Structure (d	welling or com	mercial)				
Subproject Interventions? ☑Yes	☐ Community Resource	es						
□ No	☐ Natural Resources (V	Vater bodies/ Fo	orest/ P	ublic Pond)				
	☐ Others (please specif	y)						
2.1.1 Land	Currently Owned	Private		Public				
	Total Area	Institution ow	ned					
		=14889.66m ²						
	Land use	Fallow						
	Additional	Private		Public				
	requirement							
	Total Area -							
	Land use	_						
	Permanent/temporary	-						
	Land Procurement	l Voluntary Doi	nation	l Voluntary				
		lDirect Purchas	e	Donation				
				l Land				
				Acquisition				
	Presence of □Squatter/	□Encroacher/□	lleaseho	older in				
	Private/Public land:							
	□Yes ☑ No							
	If Yes,							
	 Total number of 							
	 Possibility of ph 	·						
	Procurement Procedure							
2.1.2 Physical Structures		Private	Public					
(Specify Private (P), Squatter (S),	Houses to be resettled:	-						
Encroacher (E), Leaseholder (L)	Community resources:							
etc) Commercial/business -								
2.1.3 Is there any Community	Community Resource	No. of be	neficiar	y households				
Resource Properties resources Property								
	X	X						

that might be affected due to	X	X				
project intervention?						
□Yes ☑ No						
2.1.4 Is there any natural	Natural Resource	Dependent households				
resources that might be affected	X	X				
due to project intervention?						
□Yes ☑No						
3. Impact in Livelihood						
□ Yes ☑No	Impact	No. of families				
(Specify Private (P), Squatter (S),	□Loss of shelter and					
Encroacher (E), Leaseholder (L)	housing structure					
etc)	□Loss of income source					
	□Loss of grazing field					
	□Loss of a g ricultural					
	land					
	□Others					
4. Impact on Trees and Crops						
4.1 Vegetation clearance	Tentative number of trees	to be felled:				
□Private Land □Governmental	• Tree size <u>Not</u>	<u>Required</u>				
Forest □Community Forest		Required				
4.2 Agricultural Crop/Fruit	Agricultural Land	Horticulture (Fruits)				
bearing trees loss	Χ	X				
(Specify Private (P), Squatter (S),						
Encroacher (E), Leaseholder (L) etc)						
5. Vulnerable Groups						
5.1 Area there Vulnerable	If Yes, does project interve	ntion affect these groups?				
Groups	☐ Land					
(Adibasi/Janajati/Dalit/Women	☐ Physical Structure					
headed households residing	☐ Income generating activ	ities				
within or adjacent to project site?						
□Yes ☑No						
5.2If Yes, displacement of these	-					
people needed?						
5.3 Is there any way that	No					
proposed project may pose any						
threat to cultural tradition and						
way of life of vulnerable groups?						
5. Community Benefits from sub-project intervention						
The inhabitants of the ruralmunicipality will get renewable energy and local community						
get relief from odour due to wastes from poultry, cattle farm, sugar industry.						
 And get the fertilizer in the 	low rate.					
6. Perception toward project						

6.1 Community Perception	☑Positive	□ Negative
toward project		

ENVIRONMENTAL SCREENING CHECKLIST

Project Brief

Company Name/ Registration/	Shivam Jaivik Khad tatha Urja Pvt. Ltd, Janakitola,
Address	Jagarnathpur-03, Parsa
Contact Details (Telephone,	Email: Ashok Kumar Yadav,Dilip Sharma
Email)	<u>Ph:</u> 9855036664,9855023153
Technology (type and capacity)	CSTR Biogas Proposed Plant of capacity 5000m ³
Implementation approach	Construction of Biogas plant
(approach, schedule, institution	Institution Involved: AEPC,
involved, and stakeholders)	
Total Project Cost	NRs. 186,942,245.28

Environmental setting of the project locality

2.1 Location					
Location of the project (settlement/	Jagarnathpur-03, Janakitola , Parsa				
ward/ VDC/ District)					
Adjoining/nearby settlement(s):					
Community facilities (school,	-				
playground, etc.):					
Is the project located in forest area or	close to forest	Yes	⊠No		
If Yes,					
Name of forest					
Management regime					
Does vegetation need to be					
removed for the project? Give					
estimate?					
Permission to operate in the forest?					
Is the project located in the protected	area or any protected area	Yes	⊠No		
in vicinity					
Is Yes, please provide details on					
(a) name of PA					
(b) area to be acquired					
(c) distance to PA from the project					
site					
(d) access from the project to the					
PA					
2.2 Water sources/ water bodies					
Area there any water sources/ water	bodies in and around the	✓Yes	No		
project site					


If Yes provide details on							
Location/Type	Ga	Gangol Nadi- 700m E and Uriya Nadi-1.65km W					
Use of water			Gangor waar 700m 2 and errya rwaar 1.00km 77				
			one as there	is no possible intri	usion of	slurry into the	
l l l l l l l l l l l l l l l l l l l	-)		ær.	r		j i j	
2.3 Air pollution							
Number and type of vehic	les to be		Not requi	red			
used per day							
Capacity of vehicles			-				
Condition of the road (asp	halted,		-				
earthen)							
2.4 Land use							
Facilities	Required	l Ar	ea	Land use type	Loca	tion	
(1) industry Own Land	14889.66	m^2		Fallow	Jagar	nathpur-03,	
					Parsa	1	
2.4.1 Impact due to land u	se change						
a) Loss of private land							
b) Loss of agricultural prod	duct		No)			
c) Loss of private structure							
d) Loss of Forest and vege	tation	• • • • •	No			•	
e) others				.No			
2.5 Waste input for the pr	oject						
Define waste (type)	Waste from	n th	ne municipa	ality			
Quantity of waste	26.46 Tons	s of	waste per d	lay			
Location of collection	Collection	cha	amber throu	igh the digester			
Workers involved	Local worl	kers	6				
Legal clearance	No						
required							
2.6 Technology							
Type	Modified (GG	C 2047 Mod	lel (Further define l	y DPR)	1	
Capacity	$5000m^{3}$						
Components	nents Mixing ,Digester, Fertilizer Tanks						
Gas production	3200 M ³ /d	lay					
Feed to digester slurry	13500 kg p	er o	day				
Feed to digester slurry							
Remarks					1	T-	
2.7 Waste from the project	t impleme	ntat	ion		Yes	No	
Generation of solid waste? If Yes, in the form of slurry					Yes		
-	Are any wastes required to be stored on-site either for reuse or off-site Yes						
disposal? If Yes,	disposal? If Yes,						

The slurry shall either be					
community or need to be					
Are effluents required to	be discharged to a sewer or combined		No		
drainage system? If Yes, .					
2.8 Health and Safety Iss	ues	Yes	No		
a. Does project inter	vention affect health and safety condition?	Yes			
b. List of likely healt	h and safety issues during construction				
period					
Construction relat	red accidents				
c. List of likely healt	h and safety issues during implementation				
period					
 handling of slurry 					
Accidents associate					
 And possibility of 	leakage of slurry.				
2.9 Other observations					
Can vector disease	Yes				
spread to the adjoining					
settlements?					
Can foul odor affect the	Yes				
adjoining settlement?					
Slurry use (proposed)	Slurry use for the fertilizer and they plan to	sell it to	the nearby		
community. There was good market for slurry as fertilizer.					

Recommendations

As the project itself reduces waste generated from the institution and proposed to generate biogas energy, the negative impacts are not envisaged. However, negligible impacts listed above might prevail during construction and operation phase. The overall impact caused by the sub project intervention can be classified as "Category B" with no or minimal environmental impact and hence there is no need of conduction of further environmental assessments. Nevertheless, in order to reduce above mentioned identified adverse impacts, "Environmental and Social Assessment (ESA)" shall be prepared prior to construction start.

Annex A-3: Meeting Minute of Public Consultation



क्षित्र- कर देवी (3012413/82-3 85 ER क्रांजीता देवी अंदे देह 日本の からなる あるかかかから कार्य कार्य देश अभिना भारत क्रिका (क्रका राज्ये 257 3/64 अमि प्रकार भारत शक वर्षेश भारत 柳川柳 थाने आहेव काक काम क्रिकी किली ५५६० अन्मन्द्र किर्के क्ष्यंद काहक 547 3410 शम परेका भारत STATESTOS / Zuna किक प्रकार इन्स्प्रेक्श्वक्ष्य विकेष्या का) क्रिका है अमार माद्र । ezerogeser Wenne



NEW10 82:-

- केलकार किरकारक कर वर्षी एक कार्ट कर कर कर
- 2) राम कुनाप अंध्यम सम्मान्त्री
- 3) रिक्र वर् अम्बन्द्रभा

7019 82:-

- अं हत्यने गर्यवर्ष आ त्रिक्षणात्त्रेन कामा ग्राम्थ त्रीत्रेष्ट भरते त्या त्रीत्र्य कार्य भा त्रिक्षणात्त्रेन कामा ग्राम्थ त्रीत्रेष्ट भरते त्या त्रीत्र्य कार्य न) त्रेत्राम् कर न भामा द्राप्तित भरते त्याच्या त्रीत्रेष्ट क्या (या) त्या क्या त्या

र्चाभ क्षेत्रकोत

- ९) २ मानित्र देवमा ७६वित २ माम्बा (हुन श्रमी ७ एडी तथा उपता हो जापात्र तथा विद्वास र शंचलकुषा २ मीनिय छाई सीप तथा रूमता हो जापाद मा श्री खारा अदान ठार्सन एई द
- 2) व्याना विक्रोण प्रकार कार क्रान्स क्रान्स



अंश अम्मक्री का प्रेटनकी का एका स्टब्स्ट कार्र हवानका अंश अमक्री का प्रेटनकी का एका स्टब्स्ट कार्र हवानका अंशिन प्रेट्

Comt



Figure 12 Minute



Figure 13 Public consolidation

Annex A-4: Description of Technology

CSTR Digester

Biogas is generated when bacteria degrade biological material in the absence of oxygen, in a process known as anaerobic digestion. Since biogas is a mixture of methane (also known as marsh gas or natural gas, CH4) and carbon dioxide it is a renewable fuel produced from waste treatment. Anaerobic digestion is basically a simple process carried out in a number of steps that can use almost any organic material as a substrate. Conventional anaerobic digestion has been a "liquid" process, where waste is mixed with water to facilitate digestion.

CSTR Digester

Anaerobic co-digestion of many different substrates has achieved the most success when utilizing a Continuous Stirred-Tank Reactor (CSTR). This is the most popular, and proven technology worldwide. CSTR systems are very large, heated insulated tanks, constructed of metal or concrete.

Biogas production is a complex process resulting from incomplete anaerobic mineralization of biomass, carried out in four steps in single-phase. Organic acids formed in the hydrolysis and acidogenesis are intermediates of the biological process and can be described as nutrients for the microbes in the acetogenesis and methanogenesis. A key design parameter for CSTR digester system is the overall loading rate. Loading rates are commonly expressed as the number of days of retention time or the quantity of organic matter applied to a given tank volume. Common detention times for digesters are roughly 20-30 days. Experience has shown that this time represents an optimum time where gas yield is maximized without over designing the residence time. Facilities that are co-digesting more complex wastes that include fats and proteins will commonly have retention times higher than 30 days. The CSTR is a proven digester design consisting of an above-ground tank with a Flexible Double membrane roof. Biogas is collected at the top of the tank and is pumped to a separate gas holder. Digestate is removed from the base of the digester tank. CSTR tanks are manufactured from RCC and can be insulated externally with 100mm of mineral wool and protected with plastic-coated steel panels. Except submersible agitators there is no mechanical equipment within the CSTR digester tank.

Mixing Inside Digester

Continuous stirred tank reactors (CSTR) are used for producing biogas organic residues. When using this type of biogas digester, the stirring of the substrate in the digesters is vital for the biogas formation process. The purpose of stirring is to distribute the nutrients in the biogas digester uniformly, to form a suspension of liquid and solid parts, to avoid sedimentation of particles, to ensure uniform heat distribution, to prevent foam formation and to enable gas lift from the fermentation substrate at high dry matter (DM) contents. In digester applications there can be a tendency for oily and fatty compounds to float out of solution and rise to the top of the digester's contents. If there is not adequate mixing to keep tank contents completely agitated this floating layer can accumulate to significant thickness if not properly managed. The best approach to managing a floating layer is to properly engineer the mixing system ahead of time to ensure proper agitation to prevent its formation. The theory of the CSTR is that, through rigorous mixing, the composition of the contents of the reactor in any given spot in the tank is the same as in any other spot in the tank.

Temperature & Heating System

The lower temperature, mesophillic systems can provide the benefit of a faster growing, more robust bacteria population vs thermophilic which have slower growing bacteria. The Digester is heated by an internal concentric-tube heat exchanger. Hot water is circulated through the heat exchanger by a central-heating pump. There will be 8 rounds of pipeline of stainless steel with hot water flowing through it. The digester temperature will be maintained at 38° C. The inlet temperature will be about 80° C and the outlet temperature will be same as the temperature of the digester which will be recirculated to the system. There will be automatic temperature control system, however the temperature can be monitored and maintained manually as well.

Others

Digester tank controls include: continuous digester level monitoring, lightening protection electrode, temperature monitoring, gas pressure/vacuum relief valve and an emergency relief valve. The digester is discharged through Level box which withdraws digestate from the base of the digester. The amount of digestate discharged and the time between each discharge is variable and can be adjusted by the operator. The biogas flow is measured at the gas consumers from the double membrane gas holder via low level condensate traps. The gas holder is inflated by an air blower and pressure is maintained at a constant level of 1 to 1.5 kPa by an automatic control valve.

Technology used for generation of biogas:

The Plant will run using sophisticated and proven Anaerobic Digestion CSTR technology for generation of Raw Biogas and Pressure Swing Adsorption (PSA) technology for Biogas Purification. Anaerobic digestion is a renewable energy generation process in which microorganisms break down biodegradable material in the absence of oxygen.

Compound	Formula	%
Methane	CH ₄	55-75
Carbon Dioxide	CO ₂	25-45
Nitrogen	N ₂	0-10
Hydrogen	H ₂	0-1
Hydrogen Sulphide	H ₂ S	0-3
Oxygen	O ₂	0-0.5

Pre-Treatment/Slurry Preparation and Handling

The collected waste will be dumped in the plant site. The waste will be fed to the organic and inorganic waste separator. The organic waste will be treated to the biogas plant. Some of the useful recyclable inorganic waste will be sold.


Feeding

The total waste will be 65 TPD with DS of 20 % which will require 65000 liter of water each day to maintain the DS of the slurry to 10%. The organic waste and water will be put into a Feed preparation pit. The submersible mixer, which will mix different feedstock and bring it to unpacked, fluffy and consistency. From time to time it releases small quantities of feedstock into an open mouth pump with capacity of 50 m³/hr. The liquid itself comes in the beginning of the daily preparation period from a Fertilizer pit or sometimes directly from digester. The mixture of feedstock and effluent will be pumped into the digester. Both, the Fertilizer pit and the Feed prep pit are complete of the same design. Digester will be comprised of a standing cylindrical tank of

reinforced concrete with a net volume of 5000 m3, including a freeboard head space for gas release. Digester will also be covered with a membrane gas roof with inbuilt gas storage capacity. This will reduce emission as well as it increases the gas storage capacity of the whole system. The Fertilizer pit and the Feed preparation pit are fully mixed by high quality submersible agitators. Whilst its way from the Feed prep pit to the digester, the biomass passes through an additional chopper to refine the whole mixture for better pumping, piping and mixing consistence. This way of maintaining an acceptable fluid viscosity even of high dry mater containing mixtures will also reduce the demand of electrical self-consumption of the plant.

Digester design and sizing suitable for multi-feedstock:

The feeding of the anaerobic digester will work as a semi-automatic storage-flow-process, by which the bio mass is guided into the digester from the feed prep pit per day. Any process of pumping from, and to any containment will be monitored by level switches, which are connected to the PLC-System, and will supervise the pumping system. The Digester will be fully mixed by high quality submersible agitator and will be operated in a mesophilic (38 °C ± 1°C) temperature range. The hydraulic retention time for the slurry inside the digester will be for 30 days. This leads to a stable process and an economical optimized demand for process heat. So, a maximum gas yield which results in maximum greenhouse gas reduction will be guaranteed. The digester will be comprised of a standing cylindrical tank of reinforced concrete with a net volume of 2200 m3 including a freeboard head space for gas release. The Digester will cover with double membrane gas roof for storage of Raw Biogas. The solids that are fed into the Digestion System for decomposition or degradation of the Volatile Solids (VS) (Organic Dry Matter) present inside the feed substrate. The degradation is done in the one digester. The plant will work on a storage flow-process. Bio mass is guided into the single digester by the pumping system several times per day. Additionally, re-circulated slurry will be pumped into the digester. The treated sludge will be pumped to the liquid fertilizer tank when indicators show a certain level within the digester is reached. As described above, the digesters will be fully mixed by high quality submersible agitators and will be operated in a Mesospheric temperature range. This combination leads to a stable process with good Hygienic results and a minimized effort as far as area requirements and digester volume are concerned. On the other hand it aims at maximum gas yield which results in maximum greenhouse gas reduction.



Biogas Storage

The digester will be covered with Flexible Double Membrane Roof and an approximate pressure of 1 to 1.5 kPa gas pressure is maintained.

- Outer-membrane & inner-membrane Material: Euro-standard membrane, anti-UV, self-clean (PVDF coating), Anti-corrosion, anti-aging, acid proof, alkali proof and high strength.
- Double membrane roof will be fully controlled by PLC/ Control panel with additional benefits Electric control cabinet Display system: pressure/volume/control process display.
- Function control system: LCC more than 20 functions.
- Sensor system: pressure / volume sensor made of stainless steel, explosion proof.
- Operation cabinet: Air boost blower, Non return valve
- Safety function design: more than 8 ways,

The technology used is CSTR (continuously stirred reactors). The Agitators ensure extremely homogenous mixing of the slurry. The digested feed material has VS content in it to produce a gas comprising of maximum methane CH4 and the rest containing of CO₂ and H₂S. After digestion the feed material is taken for further storage. This technology ensures that the maximum biodegradable feedstock is degraded and maximum efficiency is attained out of the biogas generation plant.

Biogas Up-Gradation/Purification/Enrichment Technology

Biogas that is produced after the digestion process consists of pure biogas and Carbon-dioxide (CO₂) along with some traces gases such as Water Vapor, Hydrogen Sulphide, Nitrogen, Hydrogen and Oxygen.

Pressure swing adsorption (PSA):

Pressure Swing Adsorption, or PSA, is a method for the separation of carbon dioxide from CBG by adsorption /desorption of carbon dioxide on zeolites or activated carbon at different pressure levels. The adsorption material adsorbs hydrogen sulphide irreversibly and is thus poisoned by hydrogen sulphide. For this reason a hydrogen sulphide removing step is often included in the PSA process. The upgrading system consists of two or four absorber vessels filled with adsorption material. During normal operation each absorber operates in an alternating cycle of adsorption, regeneration and pressure build-up. During the adsorption phase biogas enters from the bottom into one of the absorbers. When passing the absorber vessel, carbon dioxide, oxygen and nitrogen are adsorbed on the adsorbent material surface. The gas leaving the top of the absorber vessel contains > 95% pure CNG. Before the adsorbent material is completely saturated with the adsorbed feed gas components, the adsorption phase is stopped and another absorber vessel that has been regenerated is switched into adsorption mode to achieve continuous operation. Regeneration of the saturated adsorbent material is performed by a stepwise depressurization of the absorber vessel to atmospheric pressure and finally to near vacuum conditions. Initially the pressure is reduced by a pressure balance with an already regenerated absorber vessel. This is followed by a second depressurization step to almost atmospheric pressure. The gas leaving the vessel during this step contains significant amounts of pure biogas and is recycled to the gas inlet. Before the adsorption phase starts again, the absorber vessel is depressurized stepwise to the final adsorption pressure. After a pressure balance with an absorber that has been in adsorption mode

before, the final pressure build-up is achieved with feed gas. It has been observed that PSA is economical technology which is available for cleaning the raw biogas. By adopting PSA technology raw biogas can be easily cleaning from hydrogen sulphide and carbon dioxide but the main issue being purging of clean gas (loss of valuable cleaned gas @ 0-5%). Mixing both water absorption along with the PSA system is possible but it proved to be quite expensive and because it could not justify the economics of the project it had been opted for a cleaning and upgrading system which guarantees us the end product with sufficient pressure and without any loss in the clean gas. Various points had been taken into considerations such as electricity consumption, water consumption and cost economics and came to a conclusion that the fusion of ZnO based hydrogen sulphide removal system along removal of carbon dioxide from biogas by adsorption process in which the PSA is used with further drying the gas for final application and pressurizing at the desired levels proves to be well proven and this system ensures negligible losses of gas from the entire system. The apex in case of PSA system is optimum and there good recovery of gas is also present. Carbon Dioxide and trace gases such as Water Vapor and H2S must be removed before the biogas can be used because:

The Hydrogen Sulphide gas is corrosive

Water Vapour may cause corrosion when combined with H2S on metal surfaces and reduce the heating value.

After up-gradation of biogas, the gas goes to a filling unit via high pressure compressor. BioCNG will be filled into transporting cylinders cascades at the filling unit at pressure of 200 bars.

DESIGN BASIS FOR BIOGAS PURIFICATION UNIT:

Influent characteristics

The composition of biogas and plant load characteristics is indicated in the tables below.

Flow	125 M³/hr
CH4	65%
H2S	1000 PPM (± 400 PPM)
CO2	34% (± 2%)
Pressure	50 k Pa

Flow	65-70 M³/hr
CH4	95% (± 3 %)
H2S	<8 PPM
CO2	<4 %
Pressure	20 kPa

While one set of towers are purifying the gas, the other towers is taken for regeneration which is achieved by

- a. Depressurization of the tower.
- b. Creating partial vacuum in the tower
- c. Providing small purge of pure gas in the reverse direction in the tower.

The changeover from one tower to another is fully automatic and accordingly continuous supply of purified gas is available at the outlet of the system. The outgoing purified gas can be used for combustion purpose.

Post Treatment of Digested Slurry:

The digester will release overflow digested slurry after digestion. The suspended solids out of this slurry can be effectively used directly in field as a bio-manure (Dry) after drying with Solid Liquid Separators. A part of overflow will be used again by the feeding system to prepare a mixture from biomass for feeding into the digester. This practice guarantees real zero pollution and will not release any effluent back to environment or for discharge. Being enriched in humus and complex building capacity it will also guarantee an organic cycle of extraction and supply to the soil, and increasing water holding capability and fertility for the farmland.

Description of Major Components

Mixing Tank: The raw material will be decanted in the mixing tank. The raw material will be mixed with water in this tank. The agitator with capacity with 7.5 HP will agitate the mixture. Then the raw material will be fed to the digester tank through automated conveyor operated through Programme Logistic Control (PLC)

Digester Tank: The volume of Digester tank will be of 5000 m3. In the digester highly controlled biological reaction process will happen comprising the use of specifically and finely cultured microbial ecosystem for aerobic and anaerobic digestion of organic feedstock. The digester will have heating systems, agitators, pumps, sensors and other instrumentations. There will be 8 rounds of pipeline of stainless steel with hot water flowing through it. There will be 5 High flow Agitators for Mixing, scum breaking and Circulation of slurry mixture with different capacity. The digester tank will be covered by double membrane roof.

Fertilizer Tank: The volume of the Fertilizer Tank will be of 58.87m3. The digested slurry from digester will be released to the fertilizer tank. The tank will have pump for slurry transfer to solid liquid separator.

Biogas Purification Unit: The unit will have high pressure compressor of capacity of 50m3. The PSA based purification will have 2 towers purification Unit for removal of H2S, moisture and CO2, with inline standby equipment for raw gas based on pressure swing adsorption technology. There will be skid mounted, blower, receiver tank, measurement equipment, and internal gas piping stainless steel, valves, NR-valves, safety equipment, flame arrester & fittings as per requirement, desulphurization unit for removal of H2S from a level of max. 3,000 ppm down below a level of max 5 ppm. The maintained pressure at delivery limit will be of 0.2 bar - 0.4 bar. There will be Gas analyser for CH4, Co2, H2S and Moisture. The high pressure manifold will have 20 cylinders filling points. The biogas will be filled in high pressure cascade with capacity of 750 litres water capacity of each stack with valve each having 75 Ltr W.C., working pressure of 204 Kgf/cm² and OD 267 mm, cylinders assembled in single Bank configuration with SS & Brass fittings & SS tube.

Electrical Control Panel: There will be Electrical Control Panel for Biogas Generation, with all Preventers, Ampere meter on every connection, Voltage Indicator. The Programmable Logic Control (PLC) included for all automatized operation connected with all sensors and SCADA for Report generation. The system will be timer based, programmable, expandable. The system includes phase drop preventer, for protection of drives against fade out by phase drop, fluctuating voltage, reverse phase connection, overload, or dry run.

Process design:

The biogas plant will be 5820 m3 CSTR biogas plant. The technological option of the plant is shown in table below:

Type of digestion	Wet	Temperature	37+/-2 ⊚C
Stage	Single stage	Continuous/batch	Continuous

The parameters considered for the design is given in below table

Design and sizing criteria for all process units are listed in table below:

Digester feed		Total	digester	Volume	
(m3/day)	HRT (days)	(m3)			Biogas plant volume (m3)
140	30	4200			5000
Mass loading to	digester (wet)	140000	0.0		kg solids/day
% DS		21			no water added
Digester feed %	DS	10.0%			
Dilution water i	required	60000			l/day
OLR		2.64			kg VS/(m3 * day)
C:N ratio		18.3			
VS destruction			20.0		
Digester Slurry mass dry		60%			kg solids/day
Digester Slurry Mass wet		7362.0			kg/day
Digester Slurry DS%		140000			%DS
VS load (kg/day)		VS dest (kg/day)			
11096.0			6657.0		

Compost DS%	70.0%	%DS
Compost production	17500	kg/day

Waste	Fed Waste
Poultry Waste (Kg/Day)	8,000.00
Cow Dung (Kg/Day)	46,000.00
Press Mud (Kg/Day)	5,000.00
Organic Waste (Kg/Day)	1,000.00
	60,000.00

Annex A-5 : Land Document




Figure 14 Layout of land

Annex A-6: Reviews of Plans/ Policies/Legislations and Guidelines

The Constitution of Nepal

The Constitution has prioritized the human rights and protection of environment. Article 30 (1) of the Constitution asserts that every person shall have the right to live in a healthy environment. Similarly, Article 51 (G) asserts that; the State shall make such arrangements as may be required to keep the environment clean and stated Policies relating to protection, promotion and use of natural resources. The State shall give priority to the prevention of adverse impacts in the environment from physical development activities, by increasing the awareness of the general public about environmental cleanliness, as well as to the protection of the environment and special safeguard of the rare wildlife. The State shall make arrangements for the protection of, sustainable uses of, and the equitable distribution of benefits derived from, the flora and fauna and biological diversity.

1. Plans and Policies

a. National Environment Policy, 2076

National Environment Policy, 2076 B.S. aims to protect constitutional right of citizens to live in clean and healthy environment conferred in article 30 of the Constitution of Nepal. The policy is structured around six major policy measures to achieve the goal and objectives adopted. These include pollution prevention, control and minimization, environmental mainstreaming, environmental justice, public participation, sustainable development, and good governance, research and capacity development. The policy among others, adopts the policy to promote the use of environment friendly technologies while operating industries, factories, hospitals and vehicles. The policy recognizes the need of environmental and social assessments for implementation of any policy, program of project and that the environmental aspects are internalized at each stage.

The policy aims minimize the adverse environmental impacts due to development projects through enhancement of impact mitigation and adaptation measures. Similarly, the policy targets to instate appropriate mechanism to ensure objectivity and reliability of the Environmental Impact Assessment reports.

With reference to the policy of environmental justice, the policy internalizes the measure of "polluter pay principle" and provisions rationale compensation to the community directly affected by adverse environmental impacts from the respective development project. The policy targets to strengthen and make more effective the role of multiple-stakeholders in environmental management.

b. National Forest Policy, 2076

It guides sub sectoral programmes relating to forests, plant resources, wildlife, biodiversity, medicinal plants, and soil and watershed conservation. It also covers periodic assessment and updating on information on forest resources of the country

c. National Transport Policy, 2058

The principal objective of the National Transport Policy is to develop a reliable, cost effective, safe facility oriented and sustainable transport system that promotes and sustains the economic, social, cultural and tourism development of the Nepal as a whole. The policy include provision for the construction and development of transport infrastructure in central and local level, connection of roads to the headquarters of all the districts, connection of roads to northern border, etc. it also include action plan for transport infrastructure, motor vehicles, involvement of private sectors, standard of service, institutional structure, etc.

d. Fifteenth Plan (2076/77-2080/81)

In alignment with the broader national aspiration, GoN has adopted the 15th Periodic Plan along with the 25-year Long Term Vision that aims at achieving transformational development and bringing about structural changes in the economy. Thirty-four indicators for the long-term vision and 60 indicators for the 15th Periodic Plan have been identified as milestone targets. This plan has envisioned the strategy for environmental protection by developing standards and guidelines to control and prevention of all kinds of pollutions in soil, water, air, noise, radioactive and hazardous pollutions. It has set the national strategy to sustainable economic growth and increase the production as well as productivity of major grains, fish and livestock products to be self-dependent on food items.

e. Climate Change Policy, 2076

This has various objectives that includes advancing capacity on CCA, developing ecosystem resilience, promoting green economy by adopting low carbon economic development concept, mobilizing national and international financial resources, making effective the information service, mainstreaming climate change into relevant policy, strategy, plan and programmes, and also mainstreaming gender and social inclusion, including in climate change mitigation and adaptation programmes.

f. Renewable Energy Subsidy Policy, 2073

The Policy aims to develop the renewable energy sector and encourage very poor households to use renewables by providing subsidy for deployment.

It revises the subsidy determined in the Renewable Energy Subsidy Policy – 2012 and Urban Solar System Subsidy and Credit Mobilization Guidelines. The subsidy amount is expected to cover 40% of the total costs; with around 30% coming from credit and around 30% from private sector investment and/or community or households contribution (cash or in kind).

The policy primarily focusses on off-grid applications and provides subsidies for mini/micro hydropower, improved water mill, solar energy (home systems, mini-grids, grid connected), biogas, biomass energy, wind energy and wind-solar hybrids. Detail of the subsidy for each

technology type is provided in the policy document. The subsidy amount differs according to technology and the region - with higher subsidy being offered for remote areas. Selected examples are:

Solar PV mini-grid:

- Generation equip. (per kWp): NPR 175,000 to 150,000/kWp (USD 1640 to 1410).
- Distribution (per household): NPR 32,000 to 28,000/household (USD 300 to 260).

Mini/micro hydropower

- Generation equip. (per kW): NPR 125,000 to 80,000/kWp (USD 1175 to 750).
- Generation civil. (per kW): NPR 80,000 to 20,000/kWp (USD 300 to 190).
- Distribution (per household): NPR 35,500 to 28,000/household (USD 333 to 260).

For technologies producing electricity output, the subsidy is not only given for equipment and civil work but also, where applicable, for development of distribution infrastructure.

Subsidy will also be provided for installation of solar PV systems in grid connected areas with irregular supply. This includes subsidies for solar street lighting in urban and rural areas and for solar PV systems in households, public educational institutions, public health facilities and religious places.

A subsidy delivery mechanism will be prepared by the Alternative Energy Promotion Centre (AEPC) and implemented after approval from the Ministry.

g. National Energy Crisis Reduction and Electricity Development Concept Paper, 2072

The Ministry of Energy ("MOF") has declared the decade 2016-2026 as the National Energy Crisis Reduction and Electricity Development Decade ("Energy Emergency Decade"). In this regard, the MOF has issued a Concept Paper on Elimination of Energy Emergency and Electricity Development Decade, 2015 (2072) ("Concept Paper") on February 18, 2016, with the objective to substantially end the power outage within the next one year, completely end power outage (even in the dry season) within the next two years, and to ensure energy security within the next decade.

It is relevant to note that this is the third time the Government of Nepal ("GON") has declared "Energy Emergency" in the last eight years. However, this time around, the GON has identified a detailed action plan with timelines, to ensure that the aforesaid objectives are met. Some of the key reforms proposed by the Concept Paper includes topics like Force Majeure Event, Convertible Currency denominated PPA, Certain provisions under the PPA, Government Guarantee for NEA Payments, One-Time Recommendation for Foreign Currency Payments, Shares to Public, Land Acquisition, Environmental Clearances.

2. Acts

a. Environment Protection Act, 2076

The Act focuses on that development project before implementation, requires either Brief Environmental Examination or Initial Environmental Examination or Environmental Impact Assessment depending upon the location, type and size of the projects [(Schedule 2 (10)].

It has provisioned for the preparation of Environmental Management Plan (EMP) [Schedule 2 (10)] and Supplementary Environmental Impact Assessment (SEIA) [Schedule 2 (11)].

The Parliament enacted the Environment Protection Act, 2076 B.S. (2019 A.D.) (the "Act") on July 19th, 2019. As a result, the earlier Environment Protection Act, 2053 B.S. (the "1997, Act") is now repealed.

One of the main features of the Act in contrast to the 1997 Act, is that it mandates several compliances to Project Developers while developing a Proposal of a Project, to ensure that the implementation of the Project does not harm the environment.

The 1997 Act, mandated a project developer to only comply with Initial Environment Examination and Environmental Impact Assessment. As per the present Act, a Project Developer needs to comply with the following compliances while developing a Project:

Environmental Study Report - is to be prepared prior to initiation of the Proposal, depending on the Proposal, and includes the following:

- Summary Environmental Study (environmental study report in short)
- Initial Environment Examination (examination of the possible impact on the environment and measures to mitigate it) or
- Environmental Impact Assessment (assessment of possible impact on the environment and solutions that can be opted)

This EPA:

Sets out the review and approval process of Environmental Study Reports, that involve informing and consulting stakeholders;

- stipulates that no one is to create pollution that would cause significant adverse impacts on the environment or harm to public life and health, or to generate pollution beyond the prescribed standards;
- specifies for the Ministry in charge of environment (currently the MoFE) to conduct inspection of approved projects to ensure that pollution prevention, control or mitigation is carried out according to the approved Environmental Study Report;
- provides for the protection of objects and places of national heritage and places with rare plants, wildlife and biological diversity; and
- states that any person/party affected by pollution or adverse environmental impact caused by anybody may apply to the prescribed authority for compensation to be recovered from the polluter/pollution generator.

b. Bagmati Province Environment Protection Act, 2077

This is a legal provision to protect the environment of Bagmati Province. Section 2 of this act specifies provision for environment study report. The environment study reportshould be

prepred as per article 3 of this section 2. Foer the purpose of sub article 1 of article 3, the proposer shall conduct brief environmental study as per schedule 1, IEE as per schedule 2 and EIA as per schedule3.

c. Local Government Operation Act, 2074

Local Government Operation Act outlines work, responsibility and powers of the local governments (Rural Sub Metropolitan City and Sub Metropolitan City levels). It specifies authorities devolved by the Constitution of Nepal to the local bodies. Section 3 of the act specifies the authorities of the local government bodies. Article 11 empowers local government to formulate local level policy for the environmental conversation and biodiversity and requires the local bodies to act for the environmental risk reduction, pollution control and control of hazardous substances.

d. Labor Act, 2074

This Act strictly prohibits the concerned parties who hire the work force to over utilize them during its different activities. Section 5 of the Act prohibits child labor engagement. Similarly, Section 6 prohibits any kind of discriminations like religion, gender, caste ethnicity, mother tongue etc. among employees. Section 22 states that prior work permit is required for non-Nepali citizens and they are allowed to work in Nepal for certain period only in the area where the Nepali work force is not available or not competent. Section 28 provisioned the working hours as 8 hours a day and 48 hours a week. The same section provisioned that thirty minutes must be allowed for rest and/or refreshments should be given in every five hours of work. Likewise, Section 30 allows employer to engage employee additional of 4 hours per day or 24 hours per week and shall provide over-time payment as 1.5 times the normal wage as per Section 31. Section 74 emphasizes constitution of Safety and Health Committee where 20 or more employees are engaged.

e. Land Acquisition Act, 2034

It guides the compulsory acquisition of land. It also describes that GoN can acquire land at any place and in any quantity by giving compensation pursuant to the act for the land acquired for any public purposes or for operation of any development project initiated by GoN.

f. Child Labor (Prohibition and Regulation) Act, 2056

The Child Labor (Prohibition and Regulation) Act 2056 is the main legal expedient to prohibit engaging children in factories, mines or similar risky activities and to make necessary provisions with regard to their health, security, services and facilities while engaging them in other activities. Under the Section 3 of the Act, child having not attained the age of 14 years is strictly prohibited to be engaged in works as a laborer. Similarly, under Section 4, engagement of child in works as a laborer against his/her will by way of persuasion, misrepresentation or by subjecting him/her to any influence or fear or threat or coercion or by any other means is prohibited. Under Section 6, in case any Enterprise has to engage a child in works, an approval has to be obtained from the concerned Labor Office or any authority or official prescribed by that office and form the father, mother or guardian of the child.

g. Soil and Water resource conservation Act, 2039

This Act is enacted to manage the watersheds of Nepal. Section 3 empowers the government to declare any area as a protected watershed area. Section 4 provides that a watershed conservation officer has the authority to implement the following works in protected watershed areas

h. Solid Waste Management Act, 2068

The Solid Waste Management Act, 2011 emphasize on the responsibility of waste producers (individuals/institutions) for the treatment and management of hazardous waste, health care waste, chemical and industrial waste as per the mandated standards. This act also outlines the duties of local government to take actions to control haphazard waste generation, disposal or collection and has provisions for various measures against those engaged in activities detrimental to the intentions of the act. Section 5 emphasizes any individual, organization or institution shall have to reduce the amount of generated solid waste as much as possible while carrying out any work or business. Section 38 of the Act states that: to throw, keep, discharge or cause to discharge chemical waste, industrial waste, medical waste or hazardous waste haphazardly are considered as offensive and could led to punishment and penalties as mentioned in Section 39 of the Act

i. Water Resources Act, 1992

The Water Resources Act (1992) makes arrangements for the rational use of surface and underground water. The Act seeks to prevent environmental and hazardous effects from the use of water and prohibit water pollution by chemicals, industrial waste or litter. Water may only be used in a manner that does not permit soil erosion, landslide or flood. Pollution of drinking water is prohibited under the Nepal Drinking Water Corporation Act (1989).

j. Forest Act, 2076

- The Act facilitates (i) to manage the national forest in the form of Government Managed Forest, Forest Protection Zone, Community Forest, Partnership Forest, Lease-hold Forest & Religious Forest and (ii) to contribute for national prosperity by conserving, promoting and utilizing the wild life, environment, watersheds and bio-diversity, while promoting the private, public and urban forest
- •Chapter 12 of this act has provisions related to development projects. It states in regard to the use of forest area that "Notwithstanding anything contained elsewhere in this Act, if there is no other alternative to the using of forest area for the operation of a national priority project, plan of which investment is approved by the Investment Board, project of national pride and it appears from the environment examination referred to in the prevailing law that the operation of such plan does not result in significant adverse effects on the environment, the Government of Nepal may give approval, as prescribed, to use any part of the national forest for the purpose of operating such plan.
- It also states that "If there is no other alternative to the using of forest area for the operation of any development project by the Province or and it appears from the environment examination referred to in the prevailing law that the operation of such plan does not result in significant

adverse effects on the environment, it may request the Government of Nepal for acquisition of the land in such forest area for the operation of the project.

3. Rules

a. Environment Protection Rules, 2077

For effective implementation of the EPA (2076), Environment Protection Rules (EPR) has been enforced. EPR contains the elaborative provisions on the process to be followed during preparation and approval of projects requiring EIA and IEE including scoping document, terms of reference, information dissemination, public consultation and hearing, and environmental monitoring and auditing. EPR calls for the public consultation prior to the preparation of Terms of Reference and public hearing prior to the approval of IEE Report

b. Solid waste Management Rules, 2070

Government of Nepal, Ministry of Federal Affairs and Local Development (MOFALD) has enacted Solid Waste Management Regulation 2070 as per the power conferred by the section 50 of Solid Waste Management Act 2068. Rule three of the regulation has the provision about the segregation and management of solid wastes. The rule legal obliges to segregate the hazardous and chemical wastes while segregating the degradable and non-degradable waste at source. Sub rule 2 of Rule three requires the waste producing body to manage the chemical and hazardous waste by the producers themselves. Rule 5 requires that the hazardous, chemical, degradable and non-degradable waste be not mixed together, that collection, deposition and handling of such wastes should be carefully done. Rule 4 of the act mentions about the role of local government in disposal of solid waste. Rule 24 has the provision that local authority can direct the waste producers to adopt the measures and techniques for reduction the waste at source, to adopt the certain method for minimizing the waste, to pay the fee in due time and sub-rule 3 of rule 24 obliges the waste producers to follow such direction. Rule 25 of the regulation has the provision for monitoring of such matters.

c. Labor Rules, 2075

The Labor Rule, 2075 is formulated in accordance to Section 182 of Labor Act, 2074. Rule 7 of this Rule states, prior work permit is required to employ any non-Nepali citizens and according to Sub-section 3 of Section 22 of the Act, all the information about the labor should be enlisted. Rule 16 provisioned that working hours should be allocated according to the nature of work and Rule 17 provisioned, women with child not more than 3 years old or pregnant women should be given additional thirty minutes of time than stated in Section 28 of the Act to rest/ feed their child. Rule 34 emphasizes on making guidelines of occupational health and safety measures of the worker in the workplace and Rule 39 emphasizes on the safety against the possible injuries eye injury, impact of chemicals in workplace and fire hazards. Laborers involved in construction as well as operation activity should be given the personal protective equipment's and should be given first aid as soon as possible according to the Rule 53.

4. Guidelines/Frameworks and Standards

a. National EIA Guidelines, 1993

To address environmental impact assessment as envisaged by NCS, 1987, National Environmental Impact Assessment (EIA) Guidelines were endorsed by Government of Nepal on 27 September 1992 and gazetted on 19 July in 1993, Volume 43, Number 5. The guideline provides criteria for project screening and initial environmental examination (IEE). This also includes scoping, preparation of terms of reference for EIA, methods of EIA report, impact identification and prediction, impact mitigation measures, review of the draft EIA report, impact monitoring, evaluation of impact studies, impact auditing, community participation and schedules and annexes to IEE and EIA.

Many of the guideline provisions are now included in the Environment Protection Act, 1997, and Environment Protection Regulation, 1997. However, as the National EIA Guidelines, 1993 have not been issued under the Environment Protection Act (1997); they do not have any legal force. It is a policy guideline issued by the Government that is still followed in the matters which are not covered by the Environment Protection Act (1997) and Environment Protection Regulations (1997).

b. EIA guidelines for forestry sector, 2052

Nepal's socio-economic development largely depends upon the conservation, management and sustainable use of renewable natural resource base, particularly the forests. Inadequate ex ante consideration of the environmental aspects, in the past, led to the degradation of the forest environment in particular. Economic growth which proceeds without proper attention to the management and sustainable use of the forestry resources may even be detrimental to the whole process of improving the quality of life. Numerous examples confirm the fact that development and conservation must go hand in hand for sustainability. With this in perspective, His Majesty's Government of Nepal endorsed this Environmental Impact Assessment Guidelines for the Forestry Sector on 3 April 1995 in order to ensure the integration of environmental aspects in Nepal's forestry development proposals or the development proposals of other sectors to be implemented in the forest areas. These Guidelines were prepared entirely through a participatory process to produce a document suitable to the Nepalese context. These Guidelines are in line with the National Environmental impact Assessment Guidelines, 1993 and details the steps required to ensure the incorporation of environmental aspects in project planning and implementation processes. His Majesty's Government of Nepal has framed the following Guidelines in order to minimize or avoid adverse impacts on the environment of development projects by integrating environmental aspects in the planning cycle of the forestry development proposals or other development works that affect forest areas.

The guideline provides criteria for project screening and initial environmental examination (IEE). This also includes scoping, preparation of terms of reference for EIA, methods of EIA report, impact identification and prediction, impact mitigation measures, review of the draft EIA report,

impact monitoring, evaluation of impact studies, impact auditing, community participation and schedules and annexes to IEE and EIA.

c. Environment Friendly Local Governance Framework, 2070

- This has been issued to add value to the environment friendly local development concept encouraging environmental protection through local bodies.
- One of its expected results is to bring improvement in the field of environment protection, waste management, climate change adaptation and disaster management throughout the nation

d. Other Directives related to forest

Other guidelines include Forest Encroachment Control and Managements strategy 2068, Directive of District Forest Co-ordination committee, 2068, Pratibandhit Ban Paidawar, Rastriya Prathamikta Prapta yojana ka lagi Rastriya Ban Kshetra proyog garne sambandhi karyabidhi, 2074, Ban Kshetra ka bibhinna Karya yojana nirman Prakriya sanga sambandhit Ban bibhag bata parit bishaya suchi ko sangalo, etc.

e. National Ambient Air Quality Standards, 2069

The National Ambient Air Quality Standards, 2003 enforced by GoN has set quality standards for seven parameters: TSP, PM10, Sulphur Dioxide, Nitrogen Oxide, Carbon Mono-Oxide, Lead and Benzene for the maintenance of the ambient air quality. The project during its construction and operation will have to comply with the standards for the ambient air quality.

f. Noise Level Standard of Nepal, 2069

Due to increased urbanization and industrialization high noise level has been experienced. The noise level standard sets ambient noise level relating to different areas like high traffic, low traffic, public places, residential and commercial places and so on. It provides standards for improving the noise quality so as to reduce impacts on human health. The threshold limit of noise for Leq in decibel as prescribed by the National Standard of Noise 2069 has for different sector in day and night are as follows:

Type of environment	Noise limit Leq (Noise limit Leq (db)		
	Day	Night		
Industrial Area	75	70		
Commercial Area	65	55		
Rural Settlement Area	45	40		
Urban Residential Area	55	50		
Mixed Residential Area	63	55		
Peaceful Area	50	40		

g. Generic Standard for discharging industrial effluent in inland surface water, 2058.

The Ministry of Environment has set tolerance limits for the industrial effluents to be discharged into the inland surface water through Gazette Notification. Since the project is considered as an industry it will have to comply with the tolerance limits set in the generic standard prior to the discharge of the effluents into the inland surface water during the construction and operation period.

h. National Diesel Generator Emission Standard, 2068

The MoPE introduced in October 2012 AD the National Diesel Generator Emission Standard (NDGES) for new and in-use diesel generators with a capacity of 8 kW-560 kW (under the 1997 Environment Protection Act). In doing so they followed the Indian standards for construction equipment rather than for diesel generators. Hence the Nepal emission standards for new and in-use diesel generators are less stringent than in India. The emissions standards set for new diesel generator imports is equivalent to Bharat Stage III standards and, for in-use diesel generators, is equivalent to Bharat Stage II.

Equipment	Maximum (db)
Diesel Generator	90

5. International Treaty Agreement

a. Convention on Biodiversity (CBD), 1992

The main objectives of this Convention, to be pursued in accordance with its relevant provisions, are the conservation of biological diversity, the sustainable use of its components and the fair and equitable sharing of the benefits arising out of the utilization of genetic resources, including by appropriate access to genetic resources and by appropriate transfer of relevant technologies, taking into account all rights over those resources and to technologies, and by appropriate funding.

b. UN framework convention on Climate Change, 1992

Parties to take precautionary measures to anticipate, prevent or minimize the causes of climate change and mitigate its adverse effects. This IEE study will enforce the implementation of environmental management plans as measure to minimize the causes of climate change

Annex A-7: Environmental Standards

Table35Standards for effluents discharged into inland waters

SN	Parameters	Tolerance Limits	
1	Total Supended solids, mg/L, Max	30-200	
2	Particle size of total suspended particles	Shall pass 850-micron Sieve.	
3	рН	5.5 to 9.0	
4	Temperature	Shall not exceed 40 degree C in any section	
5	Biochemical oxygen demand (BOD) for 5 days	30-100	
6	Oils and grease, mg/L, Max	10	
7	Phenolic compounds, mg/L, Max	1	
8	Cyanides (as CN), mg/L, Max	0.2	
9	Sulphides (as S), mg/L, Max	2	
10	Radioactive materials:		
11	a. Alpha emitters, c/ml, Max	7 OCT	
12	b. Beta emitters, c/ml, Max	8 OCT	
13	Insecticides	Absent	
14	Total residual chlorine, mg/L	1	
15	Fluorides (as F), mg/L, Max	2	
16	Arsenic (as As), mg/L, Max	0.2	
17	Cadmium (as, Cd), mg/L, Max	2	
18	Hexavalent chromium (as Cr), mg/L, Max	0.1	
19	Copper (as Cu), mg/L, Max	3	
20	Lead (as Pb), mg/L, Max	0.1	
21	Mercury (as Hg), mg/L, Max	.01	
22	Nickel (as Ni), mg/L, Max	3	
23	Selenium (as Se), mg/L, Max	0.05	
24	Zinc (as Zn), mg/L, Max	5	
25	Ammonical nitrogen, mg/L, Max	50	
26	Chemical Oxygen Demand, mg/L, Max	250	
27	Silver, mg/L, Max	0.1	

(Source: Standards adopted from MoEST, gazette on 2058/01/17 by GoN)

Table36Drinking water quality standards

SN	Parameters	Desirable Limits	Maximum Tolerable
1.	Colour, Hazen units, Max	10	15
2.	Odour	Unobjectionable	
3.	Taste	Agreeable	

4.	Turbidity, NTU, Max	5^{1}	10
5.	Total Dissolved Solids, mg/l, Max	500	1500
6.	pH value	6.5 - 8.5	May be relaxed up to 5.5
			on the lower and up to 9
			on higher side.
7.	Total Hardness (as CaCO ₃) mg/l, Max	250	
8.	Calcium (as Ca), mg/l, Max	75	
9.	Magnesium (as Mg), mg/l, Max	30	
10.	Copper (as Cu), mg/l, Max	1	may be extended up to 1.5
11.	Iron (as Fe), mg/l, Max	0.3	
12.	Manganese (as Mn), mg/l, Max	0.1	may be extended up to 0.5
13.	Chlorides (as Cl), mg/l, Max	250	
14.	Sulphate, (as SO ₄), mg/l, Max	150 ³	
15.	Nitrate (as NO3), mg/l, Max	45	No relaxation
16.	Fluoride (as F), mg/l, Max	1.5	
17.	Phenolic compounds, (as C ₆ H ₅ OH), mg/l,	0.001	May be relaxed up to 0.002
18.	Mercury (as Hg), mg/l, Max	0.001	No relaxation
19.	Cadmium (as Cd), mg/l, Max	0.01	No relaxation
20.	Selenium (as Se), mg/l, Max	0.01	No relaxation
21.	Lead (as Pb), mg/l, Max	0.01	No relaxation
22.	Arsenic (as As), mg/l, Max	0.05	No relaxation
23.	Cyanide (as CN), mg/l, Max	0.05	No relaxation
24.	Chromium (as Cr ⁶⁺), mg/l, Max	0.05	No relaxation
25.	Residual free Chlorine, (as Cl), mg/l, Min	0.2	
26.	Ammonia, mg/l, Max	1.5	
27.	Aluminium, mg/l, max	0.2	
28.	Boron mg/l, max	0.3	
29.	Nickel, mg/l, max	0.02	
30.	Hydrogen sulphide, mg/l, max	0.1	
31.	Zinc, mg/l, max	3	

(Source: Standards adopted from Department of Water Supply & Sewerage)

Table37National standard for noise quality

SN	Area of Exposure	Noise Limit (Leq) in decibels
		Day Time	Night Time
1.	Industrial Area	75	70
2.	Commercial Area	65	55
3.	Rural Residential Area	45	40
4.	Urban Residential Area	55	50
5.	Mixed Residential Area	63	55
6.	Quiet Area	50	40

(Source: Gazette Notification, 2012)

 2 Value for turbidity is 5 in FAR(for mineral water), PFA, BS, WHO 3 Value for Sulphate BS:200, FAR(for mineral water) and PFA:250

Table 38Permissible emission standards for biogas generator (adopted from diesel generator standard)

CATEGORY (KW)	CO (g/kWh)	HC+NOx (g/kWh)	PM (g/kWh)
kW<8	8.00	7.50	0.80
8=kW<19	6.60	7.50	0.80
19=kW<37	5.50	7.50	0.60
37=kW<75	5.00	4.70	0.40
75=kW<130	5.00	4.00	0.30
130=kW<560	3.50	4.00	0.20

Source: Nepal Gazette (Nepal Gazette Notification, 2069 Kartik 13, BS)

Annex A-8: Grievance Redress Format

Name of Grievant:	Contact detail
	Work Phone:
	Home Phone:
	Mobile No.:
Home Mailing Address:	Work Mailing Address:
Date, time and place of grievance recorded:	
Detailed description of grievance:	
Proposed solution to grievance:	
and the second s	
Cianalana af Cairana	Ciamatama (Caiama Danima
Signature of Grievant	Signature of Grievance Receiver

Table39Grievance redress format

S.N.	Name of Grievant	Date	Time of Grievance Recorded	Issue Raised	Time Frame to Resolve

Annex A-9: Plant Layout and Drawings




Figure 15 Plant layout

Annex A-10: Emergency Preparedness Plan

Emergency Response Plan for Biogas Plants

1. Types of Incident, Severity and Level of Response

Severity	Level of Response
Level 1 – Minor: localized	Level 1
fire	• can be dealt with by the person
Level 2 – Serious:	identifying the problem
containable fire	• supervisor should be informed and
	the incident formally logged
fire	• do not involve plant evacuation or
	Emergency Response Team
	Level 2
	Immediate action should be taken
	• the person identifying the problem
	call Security to summon ERT
	assistance
	• ERT takes necessary emergency
	actions
	May involve plant evacuation
	Level 3
	Immediate action should be taken
	• the person identifying the problem call Security to summon ERT
	assistance
	• ERT takes necessary emergency
	actions
	 Must involve plant evacuation and
	Emergency Response Team
	Level 1 – Minor: localized fire Level 2 – Serious: containable fire Level 3 – Severe: serious

ERT – Emergency Response Team

2. The Emergency Organization

Operating	ERT	External Services	Others
Personnel			

Problem Identifier	Incident controller	Ambulance	Crisis Management
Supervisor	First Aiders	Fire	Team
	Fire checkers	Medical	ESS specialist
	Pump checkers	Health & Safety	Site in charge
	Gas line checkers	Security	
	Roll Call Co-		
	coordinator		
	others		

3. Emergency Response Equipment

Emergency Response Equipment	Location	Capability functions	Inspection frequency
Smoke Purge Generator	Utilities	To Extract Smoke To power in emergency	Monthly and quarterly
Fire pumps	Fire system pump house	To supply sprinkler water to the plant	Weekly
Fire alarm	Reception and plant rooms	To audibly alert all personnel of the presences of a Fire or Smoke	Weekly
Spill kits	Security	To contain potential local leaks	Monthly
Radio	Individually held and Reception	To ensure clear open communication in event of emergency	Weekly
Fire Extinguishers	Plant wide	To provide local, portable extinguishers for the suppression of a small fire	Annual
First Aid Kits	Security	To Supply Dressing/Burn Material	Weekly
Gas detector	Security	Gas detection CH4 leak and H2S leak	Weekly

Responsibility for operation should be defined

4. Training

То	On what
Employees	Emergency response and evacuation
Contractors	Emergency response and evacuation
Visitors	
Emergency Response Team	Emergency response procedure
	Basic fire response procedure
	Chemical Spill
	Gas leak
First aiders	First aid
Security	Call response and dealing with external threat
Incident controller	Incident control

5. Drill and communication – *should be taken annually*

6. Incident Response

Personal Injury/Medical Emergency					
Instructions for all	Instruction for First	Instruction for	Instructions for		
employees and	Aid Personnel	Supervisors	Security		
contractors					
If incident involves personal injury - remove the hazard if safe to do so	On instruction from Security or Incident Controller, proceed to scene of injured personnel	Liaise with First Aider and find out what further medical intervention is required.	Ask caller to Remain Calm		
General Site Evacuation	on				
should make safe any equipment you are using if safe to do so and immediately leave the building by					

the nearest				
emergency exit				
Proceed to your				
designated Assembly				
Point				
Fire	<u> </u>			
If trapped - Close as	Receive emergency			
many doors as	call			
possible between you	Fire alarm activation			
and the fire				
and the me	Sprinkler water flow alarm			
In case of smoke -	alaiii			
Stay as low as				
possible				
Chemical spill				
Others:				
Instructions for				
Emergency Response Team				
Pump House Checker				
Gas Leak Checkers				
Roll Call Coordinator				
Others				

7. Incident Report Checklist

A. Attendance				
Person	Present	Signature		
Fire checker				
Pump House checker				
Roll call coordinator				
B. Notification				
	Notified	Response		
Ambulance	Yes/No	Yes/No		
Fire brigade				
C. Responsibilities				
Issue	Who	What		
Gas Leak	Gas leak checker			
Radios				

Security	Security guard	Ensured no
		authorized entry

8. Directory of Emergency Contacts

Name	Organization	Contact Address	Contact No.
	Security		
Dr.	Physician		
	Hospital		
	Fire Brigade		
	Ambulance		
	Municipality		
	Ward Office		
	ESS Focal Person		
	Team Leader, ERT		
	Contractor		

Annex-A11: Occupational Health and Safety Plan

Management Commitment to Occupational Health Safety (OHS) Goals for OHS Plan:

- Develop, implement, and maintain a safe workplace for our employees consistent with all applicable national regulations
- Consistently improve the safety program to minimize incidents, therefore ensuring employees' long-term safety and wellness.

Person responsible for implementing and monitoring the Safety Program: *TBD* Managing Director:

Date:

Employer Responsibilities

To provide employees with a workplace free of hazards that may cause illness or serious physical harm.

To comply with standards, rules, and regulations

- Allow employees free access to tools and equipment necessary to do a job safely.
- Provide employees with training/orientation on specific safety issues and equipment.
- Conduct regular inspections.
- Following up after safety incidents with thorough accident investigations, correcting problems and post-accident employee training.
- Recognize employees with the best OHS practices.

Employee Responsibilities

- Handle equipment and work processes in accordance with established procedures and documented protocols.
- Report any unsafe conditions, defects in equipment, or injuries to management immediately.
- Complying with all management instructions for safe conduct.
- Attend OHS related trainings/orientations and practice drills.
- Obtain permission to operate equipment.
- Never participate in horseplay, scuffling, and other acts that endanger the safety or wellbeing of the team.
- Not report to work under the influence of alcohol and/or drugs or during illness.

Employee Injury and Illness Reporting

All injuries must be reported to immediate supervisor or Emergency Response Team. Information

Location of First-aid box and fire extinguisher

- Emergency contact number
- Emergency health centre location:
- Evacuation location:

Report any hazard to:

Supervisor's Name:

Contact No.:

After hours/weekends:

Incident Investigation

In an emergency situation, **dial 100** immediately

- All injuries and illnesses should be reported, no matter how large or small.
- Fill up incident reporting Form.
- Document the injury/illness completely while doing a thorough root cause analysis of the incident so that corrective action can be determined to prevent future incidents.
- Part of the safety corrections may include employee orientation and counseling to correct unsafe behaviors, prevent injuries, and improve safety.

Hazard Identification and Assessment

Information available in the workplace may include:

- Equipment and machinery operating manuals.
- Material Safety Data Sheets (MSDS)
- Records of previous injuries and illnesses
- Patterns/trends of frequently occurring injuries and illnesses
- Existing safety and health programs, such tagout, confined spaces, process safety management, personal protective equipment etc
- Input from workers

General Safety Programs

- Confined space entry
- Driving safety
- Electrical safety (wiring methods, components and equipment, electrical system design)
- Emergency Action Plan
- Ergonomics (scientific study of people and their working environment)
- Fall protection
- Fire safety

Personal Protective Equipment

All personal protective equipment (PPE) and tools to safely perform the work will be provided to employees and properly maintained in accordance with manufacturer guidelines.

Organization's PPE plan – use of appropriate PPE

All employees will be trained on the personal protective equipment that is required to do their jobs effectively. The Company will review any employee feedback on the use of this equipment and potential improvements that can be made. This will be in line with the current COVID 19 situation and its long term implications in terms of health safety and contagion control. The following steps will be done for disinfection

- 1. Clean up and disinfect office space, common areas and construction site with soap/detergent water and/or disinfectant (such as 1% hypochlorite) where workers would have to move frequently
- 2. Disinfect frequently touched objects, surfaces and equipment
- 3. Provide hand washing facilities at the construction site (recommendation: use foot operated tap and soap dispenser)
- 4. Provide soap and water in toilet with hand drying facility such as disposable paper towel
- 5. Display poster on hand-washing steps

In case of someone at the construction site becomes ill with symptoms of communicable disease, developers/contractors shall develop an Emergency Response Plan to deal with the emergency situation. Project developers and contractors shall assume that everyone is potentially infectious at the construction site, thus shall introduce good infection control plan. If proper procedures are followed at all times, spread of disease can be avoided. Construction sites shall be provided with an appropriate first aid kit and at least one staff member shall be appointed as ESS focal person and trained in first aid. Moreover, Personal Protective Equipment (PPE) such as facemask, gloves, gowns, eye goggles and face shields should be provided on site

Education on Communicable Disease

- 1. Orient employees/workers on communicable disease like COVID-19, its symptoms and Occupational Health and Safety (OHS) Plan of the project
- 2. Provide notification on risk and scope of risk to make understanding on the disease
- 3. Provide up-to-date information on weekly basis from reliable and authentic sources such as GoN and WHO
- 4. Instruct workers to strictly follow guidelines/instruction of the Government of Nepal
- 5. Encourage workers to strictly follow OHS Plan along with GON prescribed measures to avoid and minimize the risk of Infection

Hazard Prevention and Control

Using the following standard methods:

- Safe Work Practices
- Engineering Control
- Training
- Enforcement
- Personal Protective Equipment
- Administrative Control
- Preventive Maintenance

Work Place Environment

- Light
- Temperature
- Ventilation
- Sound
- Working space Cleanliness
- Garbage Management
- Provision of Drinking Water
- Canteen
- Toilet Facility
- Resting time and resting place
- Safety provision in workplace

Communication

Standard methods for the communication with employees:

- Group orientation/individual induction
- Posters/signage/forms/formats
- Regular Meetings on OHS
- Safety suggestion box
- Online forms
- Hotline

Training and Education

Safety training will be provided for employees:

- During new hire on boarding.
- When beginning new job assignments.
- When cross training on new types of machinery/equipment.
- When new substances, processes, procedures, or equipment are introduced to the workplace and represent a new hazard.

• Periodically, in the form of refresher training (this may be following a near miss or incident, which can be required).

The purpose of our training program is to provide employees with:

- Knowledge and skills needed to do their work safely and avoid creating hazards that could place themselves or others at risk.
- Provide awareness and understanding of workplace hazards and how to identify, report, and control them.
- Specialized training, when their work involves unique hazards.

Program Evaluation and Improvement

- Verify that the core elements of the program have been fully implemented. Ensure that the following key processes are in place and operating:
 - Reporting injuries, illnesses, incidents, hazards, and concerns.
 - Conducting workplace inspections and incident investigations.
 - Tracking progress in controlling identified hazards and ensuring that hazard control measures remain effective and is completed promptly.
 - Collecting and reporting any data needed to monitor progress and performance.
- Review the results of any compliance audits to confirm that any program shortcomings
 are being identified and that actions are being taken that will prevent recurrence.
- Review and update plans/processes based on the company's loss history.
- The person tasked with the overall responsibility to evaluate the Company's safety program and processes is:

Name: TBD	
Contact Information:	

Annex A -12: Land Lease Document

बहालनामाको कागज

वेउकी राउत अहिरको नाति, शंकर राउत अहिरको छोरा जिल्ला पसा गा.वि.स विजवनिया वडा नं. ७ परिवर्तित भई कायम ऐ जगरनाथपुर गाउपालिका वडा नं. ३ बस्ने वर्ष ... को (ना.प्र.प.नं. ३४९०९९/९६६ जारी मिति ०६६/०३/९४-पसा) अशोक कुमार यादव जसलाई यस वहालनामाको कागजमा प्रथम पक्ष भनिएको छ । जिल्ला पसा जगरनाथपुर गाउपालिका वडा नं ३ स्थित शिवम जैविक खाद तथा उजा प्रा.लि. (प्रा.लि. नं. २४८६२०-०७७/७६) को तर्णबाट ऐ का अध्यक्ष निगना कुमार यादव जसलाई यस बहालनामाको कागजमा दोश्रो पक्ष भनिएको छ । आगे म प्रथम पक्षको नाउ दता हकभोगको जिल्ला पसा गा.वि.स जानकीटोला वडा नं. ७ परिवर्तित भई कायम ऐ जगरनाथपुर गाउपालिका वडा नं. २ को कि न २९२ को ज.वि. ०-९४-० जग्गा दोश्रो पक्ष भाडामा लिई शिवम जैविक खाद तथा उजा प्रा.लि को कारोबार संचालन गर्नका लागि भाडामा दिन तपाई दोश्रो पक्षले माग गरेकोमा तपसिलमा उल्लेखित शर्तहरुको अधिनमा रही म प्रथम पक्ष सो जग्गा भाडामा दिन सहमत भएकोले दुवै पक्षको आपसी सहमतीले उल्लेखित जग्गा भाडामा लिन दिन मंजूर भई यो बहालनामाको कागज लेखि लेखाई सही छाप गरी एक एक प्रति लियौ दियौ साक्षी रोहबरको सदर।

शर्तहरु

- १ उल्लेखित जग्गाको बहाल प्रति कठा प्रति वर्ष र. २५००/०० (दुई हजार पाच सय मात्र) निर्धारित गरियो । सो बहाल रकममा प्रत्येक वर्ष मा मुल बहाल रकमामा १०% ले बृद्धि हुनेछ ।
- २ सो भाडा दोश्रो पक्षले प्रथम पक्षलाई महिनाको ४ गते भित्र बुकाईन पर्ने छ ।
- वहाल वापत लाग्ने कर दोश्रो पक्ष कम्पनी स्वयंले बुकाइ सी को निरसा प्रथम पक्षलाई दिन् पर्ने छ ।

- उल्लेखित जग्गामा आवश्यक पर्ने निर्माण कार्य,विध्त, पानी नगायतको सम्पूर्ण कार्य दोश्रो पक्षले आफी गराउन् पर्नेछ ।
- प्रथम पक्षले दोश्रो पक्षलाई वहालमा दिएको जग्गा जुन प्रयोजनको लागि लिएको हो सो बाहेक अन्य कुनै प्रयोजनमा प्रयोग गर्न पाउने छैनन ।
- ५ यो घरको बहाल अवधि आजको मितिले २० वर्षको लागि हुने छ । सो उपाल्न आवश्यक्ता अनुसार बहाल सम्बन्धमा सम्मौता गर्न सिकने छ । उक्त अवधि पश्चात नया सम्मौता हुन नसकी जग्गा खाली गरी दिने बबस्था आएमा दोश्री पक्षले निर्माण गरेका घर टहरा लगायत अन्य सामाग्रीहरु प्रथम पत्तले आपसी सहमितिले कायम मोन बुक्त बुक्तारथ गरी उक्त समानहरु राव्न सक्नेछन था कायम मोल तिन नसके दोश्री पक्षले उक्त समान लैजान पाउने छन ।
- वोश्रो पक्षले बहासमा लिएको जग्गा निर्धारित अवधि भन्दा पहिले छाउन चाहेमा प्रथम पक्षलाई ६ महिना पहिले लिखित जानकारी दिनु पर्नेछ ।
- यसमा लेखिएको शतंहरू दुवै पक्षलाई कानृन सरह लागृ हुने छ ।

प्रथम पक्ष

अशोक कमार यादव



दोश्रो पक्ष

शिवम जैविक खाद तथा उना श्री लिको तक्षयाट ऐका अध्यक्ष निमना कुमार यादव 1

रोहबर

जिल्ला पसां की म न पा बार्ड न ११ बस्ने वर्ष को दिलिए शर्मा ी

इति सम्बत २०७८ साल जेच्छ महिला गते रोज मा गुभम


बहालनामाको कागुज


बैजकी राउत अहिरको नाति, शकर राउत अहिरको छोरा जिल्ला पर्सा गा.वि.स. विजवनिया वडा न. ७ परिवर्तित भई कायम ऐ. जगरनाथपुर गाउपालिका वडा न. ३ वस्ने वर्ष २६ को ना.प.प.न.३४-०९-६९-०२६७९ जारी मिती २०६९,०६,०७ -पर्सा सुभाष कुमार यादव जसलाई यस बहालनामाको कागजमा प्रथम पक्ष भनिएको छ । जिल्ला पर्सा जगरनाथपुर गाउपालिका वडा न ३ स्थित शिवम जैविक खाद तथा उजा प्रा.लि. (प्रा.लि. न. २४८६२०-०७७/७६) को तर्फबाट ऐ का अध्यक्ष निगना कुमार यादव जसलाई यस बहालनामाको कागजमा दोशो पक्ष भनिएको छ । आगे म प्रथम पक्षको नाउ दर्बा दक्ष्मारको विज्ञा वर्षा कि भनिएको छ ।

अागे म प्रथम पक्षको नाउ दर्ता हक्सोगको जिल्ला पर्सा गा.वि.स विजवनिया वडा न ७ परिवर्तित भई कायम ऐ जगरनाथपुर गाउपालिका वडा नं ३ कि.नं २२४ का ज.वि ०-७-१०, र जिल्ला पर्सा गा.वि.स. जानकीटोला वडा नं ७ परिवर्तित भई कायम ऐ जगरनाथपुर गाउपालिका वडा नं २ ऐ कि.नं १९१ को ज.वि ०-९-४ तथा जिल्ला पर्सा गा.वि.स. जानकीटोला वडा नं ७ परिवर्तित भई ऐ जगरनाथपुर गाउपालिका वडा नं २ परिवर्तित भई ऐ जगरनाथपुर गाउपालिका वडा नं २ कि.नं २७५ को ज.वि. ०-७-४ समेत जम्मा ज वि. १-४-० जग्गा दोश्रो पक्ष माडामा लिई शिवम जैविक खाद तथा उर्जा प्रालि को कारोवार संचालन गनंका लागि भाडामा विन तपाई दोश्रो पक्षले मा्ग गरेकोमा तपसिलमा उल्लेखित शर्तहरूको अधिनमा रही म प्रथम पक्ष सो जग्गा भाडामा विन सहमत भएकोले द्वै पक्षको आपसी सहमतीले उल्लेखित जग्गा भाडामा लिन विन मज् भई यो वहालनामाको कागज लेखि लेखाई सही छाप गरी एक एक प्रति लियौ वियौ साक्षी रोहबरको सदर ।

शर्तहरु

- उल्लेखित जरगाको बहाल प्रति कठा प्रति वर्ष रु २४,००/०० (दुई हजार पांच सघ मात्र) निर्धारित गरियो । सो बहाल रकममा प्रत्येक वर्ष मा मुल बहाल रकमामा १०% ले बृद्धि हुनेछ ।
- २. सो भाडा दोश्रो पक्षले प्रथम पक्षलाई महिनाको ५ गते भित्र बुक्ताईनु पर्ने छ ।
- वहाल वापत लाग्ने कर दोश्रो पक्ष कम्पनी स्वयंले बुकाइ सो को निस्सा प्रथम पक्षलाई
 दिन पर्ने छ ।
- उल्लेखित जम्मामा आवश्यक पर्ने निर्माण कार्य,विध्त, पानी लगायतको सम्पूर्ण कार्य दोश्रो पक्षले आफै गराउन पर्नेछ ।
- प्रथम पक्षले दोश्रो पक्षलाई बहालमा दिएको जग्गा जुन प्रयोजनको लागि लिएको हो सो बाहेक अन्य क्नै प्रयोजनमा प्रयोग गर्न पाउने छैनन ।'
- ६ यो घरको बहाल अवधि आजको मितिले २० वर्षको लागि हुने छ । सो उपान्त आवश्यक्ता अनुसार बहाल सम्बन्धमा सम्भौता गर्न सिकिने छ । उक्त अवधि पण्यात नया सम्भौता हुन नसकी जम्मा खाली गरी दिने अवस्था आएमा दोश्रो पक्षले निर्माण गरेका घर टहरा लगायत अन्य सामाग्रीहरु प्रथम पक्षले आपसी सहमतिले कायम मोल युभ बुभारथ गरी उक्त समानहरु राख्न सक्नेछन वा कायम मोल तिर्न नसके दोश्रा पक्षले उक्त समान लैजान पाउने छन ।
- डोश्रो पक्षले बहालमा लिएको जग्गा निर्धारित अवधि भन्दा पहिले छाडन चाहेमा प्रथम पक्षलाई ६ महिना पहिले लिखित जानकारी दिनु पर्नेछ ।
- 🕳 यसमा लेखिएको भातहरू दुबै पक्षलाई कानुन सरह लागु हुने छ ।






रोहबर

जिल्ला पसां वी म न पा वार्ड न १९ वस्ने वर्ष को दिलिए शर्मा १

ं इति सम्बत २०७८ साल जेष्ठ महिना ... गते रोज मा शुमम



Annex A -13: Photos



Figure 16 Field location of project



Figure 17 Poultry farm for biogas production



Figure 18 Cattle farm for biogas production